


圆形 ▶ 锁紧螺母
径向锁紧型

代码	类型		形状	精度	端面偏摆	材质		热处理	表面处理
						国标	相当		
E-BKE01	经济型	径向锁紧型	三槽	6H	0.002~0.005	45	S45C	28~32HRC	发黑

- 特点：锁紧螺母的锁紧方向为两点或三点式径向锁定，适用于设计或装配上受限，无法使用其他产品的情况。
① 由于热处理工艺表面可能会出现少许发红。



视角标准：第一视角

型号		螺距	D	H	g	t	d	n-m	扭紧力矩 (NM)
代码	公称尺寸								
E-BKE01	M6	0.75	16	8	3	1.6	12	3-M4	3.5
		1.0							
	M8	0.75							
		1.0							
	M9	0.75							
		1.0							
	M10	1.5	18				15		
		1.0							
	M12	1.25							
		1.0	20				16		
	M14	1.0							
		1.25							
	M15	1.0	25				21		
		1.5							
	M16	1.0							
		1.5	28			23			
	M17	1.0							
	M18	1.5							
		1.0	30	10	4	25	3-M5	4.5	
	M20	1.5							
			32			27			
			35			30			
			38			33			
				12	5	2.5	40	3-M6	8
							46		
							52		
			65			59			
			14	6	3	64	3-M8	18	
			75			69			
			16	7					
				8	3.5	73			
						78			
						84			
			18			90			
						96			



请按图示订货

型号		
代码	公称尺寸	螺距
E-BKE01	M6	0.75
	M8	1

E-BKE01—M6—0.75



未税价(元)

● 优惠价


数量	1~9	10~
价格	100%	另行报价



交货期
5



Example
使用示例



- ① 用于锁紧机床主轴与零件间的配合，便于拆卸。主要用于机电设备、传送装置的锁紧等。