


# 内六角平圆头螺钉

| 代码    | 类型       | 螺纹 | 强度等级  | 材质     | 硬度       | 表面处理   |
|-------|----------|----|-------|--------|----------|--------|
| TAR12 | 内六角平圆头螺钉 | 粗牙 | 8.8   | 10B21  | —        | 发黑     |
| TAR14 |          |    |       |        |          | 镀蓝白锌   |
| TAR15 |          |    |       | 35K    |          | 镀镍     |
| TAR18 |          |    |       |        |          | 银灰色达克罗 |
| TAR01 |          |    | 10.9  | 10B21  | 37~42HRC | 发黑     |
| TAR04 |          |    |       |        |          | 镀镍     |
| TAR19 |          |    |       | 40Cr   |          | 银灰色达克罗 |
| TAR06 |          |    |       |        |          |        |
| TAR02 |          |    | 12.9  | SCM435 |          |        |
| TAR05 |          |    | A2-70 | SUS304 |          |        |
|       |          |    | A4-70 | SUS316 |          |        |



适用标准: ISO 7380-1-2011  
JIS B 1174-2006  
GB/T 70.2-2008



## 强度等级8.8

| 型号    | 代码    | M  | L                         | P 螺距 | D max | D min | K max | K min | S max | S min | h (min) | d    | a   |
|-------|-------|----|---------------------------|------|-------|-------|-------|-------|-------|-------|---------|------|-----|
| 10B21 | TAR12 | 3  | 4 5 6 8 10 12 14 16 18 20 | 0.5  | 5.7   | 5.4   | 1.65  | 1.4   | 2.08  | 2.02  | 1.04    | 3.6  | 1   |
|       | TAR14 | 4  | 5 6 8 10 12 14 16 18 20   | 0.7  | 7.6   | 7.24  | 2.2   | 1.95  | 2.58  | 2.52  | 1.3     | 4.7  | 1.4 |
|       | TAR14 | 5  | 6 8 10 12 14 16 18 20 25  | 0.8  | 9.5   | 9.14  | 2.75  | 2.5   | 3.08  | 3.02  | 1.56    | 5.7  | 1.6 |
|       | TAR15 | 6  | 8 10 12 14 16 18 20 25 30 | 1    | 10.5  | 10.07 | 3.3   | 3     | 4.095 | 4.02  | 2.08    | 6.8  | 2   |
|       | TAR15 | 8  | 10 12 14 16 18 20 25 30   | 1.25 | 14    | 13.57 | 4.4   | 4.1   | 5.14  | 5.02  | 2.6     | 9.2  | 2.5 |
| (35K) | TAR01 | 10 | 12 14 16 18 20 25 30      | 1.5  | 17.5  | 17.07 | 5.5   | 5.2   | 6.14  | 6.02  | 3.12    | 11.2 | 3   |
|       | TAR18 | 12 | 14 16 18 20 25 30         | 1.75 | 21    | 20.48 | 6.6   | 6.24  | 8.175 | 8.025 | 4.16    | 14.2 | 3.5 |

## 强度等级10.9

| 型号                     |     | L  |   |   |    |    |    |    |    |    |    |    | P    | D   |     |     | K    |      |       | S     |      | h     | d     | a    |        |        |      |      |      |     |     |     |
|------------------------|-----|----|---|---|----|----|----|----|----|----|----|----|------|-----|-----|-----|------|------|-------|-------|------|-------|-------|------|--------|--------|------|------|------|-----|-----|-----|
| 代码                     | M   |    |   |   |    |    |    |    |    |    |    |    | 螺距   | max | min | max | min  | max  | min   | (min) |      |       |       |      |        |        |      |      |      |     |     |     |
| 10B21<br>(发黑)<br>TAR01 | 2   | 4  | 5 | 6 | 8  | 10 | 12 | 16 | 20 |    |    |    | 0.4  | 3.5 | 3.3 | 1.3 | 1.16 | 1.36 | 1.32  | 0.6   | 2.5  | 0.8   |       |      |        |        |      |      |      |     |     |     |
|                        | 2.5 | 4  | 5 | 6 | 8  | 10 | 12 | 16 | 20 | 30 |    |    | 0.45 | 4.7 | 4.5 | 1.5 | 1.36 | 1.56 | 1.52  | 0.8   | 2.5  | 0.6   |       |      |        |        |      |      |      |     |     |     |
|                        | 3   | 4  | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35   | 40  | 45  | 50  | 0.5  | 5.7  | 5.4   | 1.65  | 1.4  | 2.08  | 2.02  | 1.04 | 3.6    | 1      |      |      |      |     |     |     |
|                        | 4   | 6  |   |   | 8  | 10 | 12 | 16 | 20 | 25 | 30 | 35 | 40   | 45  | 50  | 0.7 | 7.6  | 7.24 | 2.2   | 1.95  | 2.58 | 2.52  | 1.3   | 4.7  | 1.4    |        |      |      |      |     |     |     |
|                        | 5   | 6  |   |   | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35   | 40  | 45  | 50  | 0.8  | 9.5  | 9.14  | 2.75  | 2.5  | 3.08  | 3.02  | 1.56 | 5.7    | 1.6    |      |      |      |     |     |     |
|                        | 6   | 8  |   |   | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40   | 45  | 50  | 55  | 60   | 1    | 10.5  | 10.07 | 3.3  | 3     | 4.095 | 4.02 | 2.08   | 6.8    | 2    |      |      |     |     |     |
|                        | 8   | 10 |   |   | 12 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50   | 55  | 60  | 65  | 70   | 75   | 80    | 85    | 90   | 100   | 1.25  | 14   | 13.57  | 4.4    | 4.1  | 5.14 | 5.02 | 2.6 | 9.2 | 2.5 |
|                        | 10  | 16 |   |   | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60   | 65  | 70  | 75  | 80   | 90   | 100   | 1.5   | 17.5 | 17.07 | 5.5   | 5.2  | 6.14   | 6.02   | 3.12 | 11.2 | 3    |     |     |     |
|                        | 12  | 16 |   |   | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60   | 65  | 70  | 75  | 80   | 90   | 100   | 1.75  | 21   | 20.48 | 6.6   | 6.24 | 8.175  | 8.025  | 4.16 | 14.2 | 3.5  |     |     |     |
|                        | 16  | 16 |   |   | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60   | 65  | 70  | 75  | 80   | 90   | 100   | 2     | 28   | 27.48 | 8.8   | 8.44 | 10.175 | 10.025 | 5.2  | 18.2 | 4    |     |     |     |
| 10B21<br>(镀镍)<br>TAR04 | 3   | 6  |   |   | 8  | 10 | 12 | 16 | 20 | 25 | 30 | 35 | 40   | 45  | 50  |     |      |      | 0.5   | 5.7   | 5.4  | 1.65  | 1.4   | 2.08 | 2.02   | 1.04   | 3.6  | 1    |      |     |     |     |
|                        | 4   | 6  |   |   | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30   | 35  | 40  | 45  | 50   |      |       |       | 0.7  | 7.6   | 7.24  | 2.2  | 1.95   | 2.58   | 2.52 | 1.3  | 4.7  | 1.4 |     |     |
|                        | 5   | 6  |   |   | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35   | 40  | 45  | 50  |      |      |       | 0.8   | 9.5  | 9.14  | 2.75  | 2.5  | 3.08   | 3.02   | 1.56 | 5.7  | 1.6  |     |     |     |
|                        | 6   | 8  |   |   | 10 | 12 | 16 | 18 | 20 | 25 | 30 | 35 | 40   | 45  | 50  | 55  | 60   | 65   | 70    | 1     | 10.5 | 10.07 | 3.3   | 3    | 4.095  | 4.02   | 2.08 | 6.8  | 2    |     |     |     |
|                        | 8   | 10 |   |   | 12 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50   | 55  | 60  | 70  | 80   | 85   | 90    | 1.25  | 14   | 13.57 | 4.4   | 4.1  | 5.14   | 5.02   | 2.6  | 9.2  | 2.5  |     |     |     |
|                        | 10  | 16 |   |   | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60   |     |     |     | 1.5  | 17.5 | 17.07 | 5.5   | 5.2  | 6.14  | 6.02  | 3.12 | 11.2   | 3      |      |      |      |     |     |     |

## 强度等级10.9/12.9

| 型号                             |    | L                         | P<br>螺距 | D    |       | K    |      | S     |       | h<br>(min) | d    | a   |
|--------------------------------|----|---------------------------|---------|------|-------|------|------|-------|-------|------------|------|-----|
| 代码                             | M  |                           |         | max  | min   | max  | min  | max   | min   |            |      |     |
| 强度等级 10.9<br>(40Cr)<br>TAR19   | 3  | 4 5 6 8 10 12 14 16 18 20 | 0.5     | 5.7  | 5.4   | 1.65 | 1.4  | 2.08  | 2.02  | 1.04       | 3.6  | 1   |
|                                | 4  | 5 6 8 10 12 14 16 18 20   | 0.7     | 7.6  | 7.24  | 2.2  | 1.95 | 2.58  | 2.52  | 1.3        | 4.7  | 1.4 |
|                                | 5  | 6 8 10 12 14 16 18 20 25  | 0.8     | 9.5  | 9.14  | 2.75 | 2.5  | 3.08  | 3.02  | 1.56       | 5.7  | 1.6 |
|                                | 6  | 8 10 12 14 16 18 20 25 30 |         | 10.5 | 10.07 | 3.3  | 3    | 4.095 | 4.02  | 2.08       | 6.8  | 2   |
| 强度等级 12.9<br>(SCM435)<br>TAR06 | 8  | 10 12 14 16 18 20 25 30   | 1.25    | 14   | 13.57 | 4.4  | 4.1  | 5.14  | 5.02  | 2.6        | 9.2  | 2.5 |
|                                | 10 | 12 14 16 18 20 25 30      | 1.5     | 17.5 | 17.07 | 5.5  | 5.2  | 6.14  | 6.02  | 3.12       | 11.2 | 3   |
|                                | 12 | 14 16 18 20 25 30         | 1.75    | 21   | 20.48 | 6.6  | 6.24 | 8.175 | 8.025 | 4.16       | 14.2 | 3.5 |

## 强度等级A2-70

| 型号                |     | L  |    |    |    |    |    |    |    |    |    |    | P    | D   |     | K   |      | S    |       | h     | d    | a     |       |      |      |      |       |      |      |       |      |      |      |     |     |
|-------------------|-----|----|----|----|----|----|----|----|----|----|----|----|------|-----|-----|-----|------|------|-------|-------|------|-------|-------|------|------|------|-------|------|------|-------|------|------|------|-----|-----|
| 代码                | M   |    |    |    |    |    |    |    |    |    |    |    | 螺距   | max | min | max | min  | max  | min   | (min) |      |       |       |      |      |      |       |      |      |       |      |      |      |     |     |
| (SUS304)<br>TAR02 | 2.5 | 3  | 4  | 5  | 6  | 8  | 10 | 12 | 16 | 18 | 20 | 25 | 0.45 | 4.7 | 4.5 | 1.5 | 1.36 | 1.56 | 1.52  | 0.8   | 2.5  | 0.6   |       |      |      |      |       |      |      |       |      |      |      |     |     |
|                   | 3   | 4  | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35   | 40  | 45  | 50  | 0.5  | 5.7  | 5.4   | 1.65  | 1.4  | 2.08  | 2.02  | 1.04 | 3.6  | 1    |       |      |      |       |      |      |      |     |     |
|                   | 4   | 6  | 8  | 10 | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40   | 45  | 50  | 55  | 60   | 65   | 70    | 75    | 0.7  | 7.6   | 7.24  | 2.2  | 1.95 | 2.58 | 2.52  | 1.3  | 4.7  | 1.4   |      |      |      |     |     |
|                   | 5   | 6  | 8  | 10 | 12 | 14 | 15 | 16 | 18 | 20 | 25 | 30 | 35   | 40  | 45  | 50  | 55   | 60   | 65    | 70    | 75   | 80    | 85    | 90   | 100  | 0.8  | 9.5   | 9.14 | 2.75 | 2.5   | 3.08 | 3.02 | 1.56 | 5.7 | 1.6 |
|                   | 6   | 8  | 10 | 12 | 14 | 15 | 16 | 18 | 20 | 25 | 30 | 35 | 40   | 45  | 50  | 55  | 60   | 65   | 70    | 75    | 80   | 85    | 90    | 100  | 1    | 10.5 | 10.07 | 3.3  | 3    | 4.095 | 4.02 | 2.08 | 6.8  | 2   |     |
|                   | 8   | 12 | 14 | 16 | 18 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55   | 60  | 65  | 70  | 75   | 80   | 85    | 90    | 1.25 | 14    | 13.57 | 4.4  | 4.1  | 5.14 | 5.02  | 2.6  | 9.2  | 2.5   |      |      |      |     |     |
|                   | 10  | 16 | 18 | 20 | 22 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60   | 65  | 70  | 75  | 80   | 85   | 90    | 1.5   | 17.5 | 17.07 | 5.5   | 5.2  | 6.14 | 6.02 | 3.12  | 11.2 | 3    |       |      |      |      |     |     |
| 12                | 20  | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 60 | 65 | 70 | 75 | 80   | 85  | 90  | 100 | 1.75 | 21   | 20.48 | 6.6   | 6.24 | 8.175 | 8.025 | 4.16 | 14.2 | 3.5  |       |      |      |       |      |      |      |     |     |

## 强度等级A4-70

| 型号                |    |    |    |    |    |    |    |    |    |    |    |    | P  | D   |     | K    |       | S     |     | h     | d     | a     |      |      |     |   |
|-------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|-----|------|-------|-------|-----|-------|-------|-------|------|------|-----|---|
| 代碼                | M  | L  |    |    |    |    |    |    |    |    |    |    | 螺距 | max | min | max  | min   | max   | min | (min) |       |       |      |      |     |   |
| (SUS316)<br>TAR05 | 3  | 6  | 8  | 10 | 12 | 18 | 35 |    |    |    |    |    |    |     |     |      | 0.5   | 5.7   | 5.4 | 1.65  | 1.4   | 2.08  | 2.02 | 1.04 | 3.6 | 1 |
|                   | 4  | 6  | 8  | 10 | 12 | 14 | 16 | 20 | 25 | 30 | 35 | 40 | 55 | 65  | 75  | 0.7  | 7.6   | 7.24  | 2.2 | 1.95  | 2.58  | 2.52  | 1.3  | 4.7  | 1.4 |   |
|                   | 5  | 10 | 12 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 55 | 65 | 70  | 0.8 | 9.5  | 9.14  | 2.75  | 2.5 | 3.08  | 3.02  | 1.56  | 5.7  | 1.6  |     |   |
|                   | 6  | 10 | 12 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |    |    |     |     | 1    | 10.5  | 10.07 | 3.3 | 3     | 4.095 | 4.02  | 2.08 | 6.8  | 2   |   |
|                   | 8  | 12 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |    |    |    |     |     | 1.25 | 14    | 13.57 | 4.4 | 4.1   | 5.14  | 5.02  | 2.6  | 9.2  | 2.5 |   |
|                   | 10 | 16 | 20 | 25 | 30 | 35 | 40 | 45 | 50 | 60 | 70 | 80 |    |     | 1.5 | 17.5 | 17.07 | 5.5   | 5.2 | 6.14  | 6.02  | 3.12  | 11.2 | 3    |     |   |
|                   | 12 |    |    |    |    |    | 25 | 30 | 35 | 40 |    |    |    |     |     | 1.75 | 21    | 20.48 | 6.6 | 6.24  | 8.175 | 8.025 | 4.16 | 14.2 | 3.5 |   |



请按照图示订货

| 型号    | 代码 | M           | L |
|-------|----|-------------|---|
| TAR01 | 3  | 4 6 8 10 12 |   |
|       | 4  | 6 8 10 12   |   |

TAR01—M4—L12



未税价(元)

### 优惠价

数量 1~49 50~  
价格 100% 另行报价



### 交货期

5