



双面带防尘盖式 标准型

微型深沟球轴承

代码	类型	轴承类型 代码	轴承精度	后置代码	轴承材质	
					国标	相当
BAF	标准型	6	GB/T 307.1 6级	ZZ(双面带防尘盖)	GCr15	SUJ2
BAF...-SUS					2Cr13	SUS420
BAF07...-SUS					0Cr18Ni9	SUS304



- ❶ 不承诺品牌。
❷ 基本额定负载/容许转速/重量值不适用于SUS304和SUS420材质。



型号		d	D	B	r1 (min)	基本额定负载(N)		极限转速 rpm(参考)	安装尺寸			重量(g) (参考)
代码	轴承型号					Cr(动)	Cor(静)		db (min)	da (max)	r (max)	
BAF	682ZZ	5	2.3	0.08	80	51	74000	2.8	4.2	0.08	0.13	
	692ZZ	6	3	0.15	150	89	67000	3.2	4.8	0.15	0.31	
	602ZZ	7	3.5			125	62000	3.2	5.8	0.15	0.54	
	682AZZ	6	2.6	0.08	80	73	65000	3.1	4.8	0.08	0.22	
	692AZZ	7	3.5	0.15	150	96	59000	3.7	5.8	0.15	0.43	
	673ZZ	6	2.5	0.08	80	94	60000	3.6	5.4	0.08	0.2	
	683ZZ	7	3	0.1	100	130	58000	3.9	5.8	0.1	0.33	
	693ZZ	8	4			180	54000	6.8			0.61	
	603ZZ	9	5	0.15	150	219	50000	4.2	7.8	0.15	0.92	
	623ZZ	10	4			224	50000	8.8			1.6	
	633ZZ	13	5	0.2	1301	488	40000	4.6	11.4	0.2	3.43	
	674ZZ	7	2.5	0.08	222	88	60000	6.4	0.08	0.28		
	684ZZ	9				224	49000	5	7.8	0.1	0.76	
	694ZZ	11	4	0.15	150	276	45000	5.2	9.8	0.15	2	
	604ZZ	12		0.2	200	360	43000	5.6	10.4	0.2	2.3	
	624ZZ	13	5			490	42000	6	11.4		3.5	
	634ZZ	16	6	0.3	300	680	37000	6	14	0.3	5.1	
	675ZZ	8	2.5	0.08	80	91	49000	5.6	7.4	0.08	0.32	
	685ZZ	11	5	0.15	150	282	43000	6.2	9.8	0.15	1.1	
	695ZZ	13	4	0.2	200	430	40000	6.6	11.4	0.2	2.4	
	605ZZ	14	5			505	39000	6	12.4		3.5	
	625ZZ	16	6			680	37000	7	14		4.8	
	635ZZ	19	6	0.3	300	885	34000	7	17	0.3	8	
	676ZZ	10	3	0.1	496	218	45000	7.04	9.3	0.1	0.7	
	686ZZ	13	5	0.15	1080	440	39000	7	11.8	0.2	1.9	
	696ZZ	15	5	0.2	1350	530	37000	7.6	13.4		3.8	
	606ZZ	17	6			2190	38000	15			6	
	626ZZ	19	6	0.3	2340	885	34000	8	17	0.3	8.1	
	636ZZ	22	7			3333	30000	20			14.5	
	687ZZ	14	5	0.15	1170	505	37000	8.2	12.8	0.15	2.1	
	697ZZ	17				1610	715	35000	15		5.2	
	607ZZ	19	6	0.3	2240	910	34000	9	17	0.3	8	
	627ZZ	22	7			3350	1400	32000	20		13	
	678ZZ	12	3.5	0.1	543	274	40000	8	11.33	0.1	0.99	
	688ZZ	16	5	0.2	1610	1400	35000	9.6	14.4	0.2	3.1	
	698ZZ	19	6			1990	865	33000	17		7.3	
	608ZZ	22	7			3350	1400	32000	20		12	
	628ZZ	24	8	0.3	4000	1590	31000	10	22	0.3	17	
	638ZZ	28	9			4560	1983	28000	26		30.3	
	689ZZ	17	5	0.2	1720	820	33000	10.6	15.4	0.2	3.2	
	699ZZ	20	6			2480	1090	32000	18		8.2	
	609ZZ	24	7	0.3	3400	1450	31000	11	22	0.3	14	
	629ZZ	26	8	0.6	4550	1960	30000	13	22		20	

❶ 1KgF=9.81N

型号		d	D	B	r1 (min)	基本额定负载(N)		极限转速 rpm(参考)	安装尺寸			重量(g) (参考)
代码	轴承型号					Cr(动)	Cor(静)		d _b (min)	d _a (max)	r (max)	
BAF...SUS BAF07...-SUS	682ZZ	2	5	2.3	0.08	143	40	85000	2.7	3.9	0.08	0.17
	692ZZ		6	3	0.15	281	79	75000	3	4.8	0.15	0.38
	602ZZ		7	3.5		328	102	60000	3.2	5.8		0.58
	682AZZ		6	2.6	0.08	178	59	71000	3.7	4.9	0.08	0.29
	692AZZ	7	3.5	0.15	328	102	63000	3.85	5.65	0.15	0.55	
	673ZZ	3	6	2.5	0.08	242	94	71000	3.6	5.4	0.08	0.2
	683ZZ		7	3	0.1	390	130	63000	3.9	5.8	0.1	0.45
	693ZZ		8	4	560	180	60000	6.8	0.61			
	603ZZ		9	5	0.15	571	189	56000	4.2	7.8	0.15	1.13
	623ZZ	4	10	4	640	224	50000	8.8	1.6			
	633ZZ		13	5	0.2	1301	488	40000	4.6	11.4	0.2	3.43
	674ZZ		7	2.5	0.08	222	88	60000	6.4	0.08	0.28	
	684ZZ		9		0.15	640	224	53000	5	7.8	0.1	1.01
	694ZZ	11	4	715		276	48000	5.2	9.8	0.15	1.8	
	604ZZ	5	12		0.2	957	350	5.6	10.4	0.2	2.34	
	624ZZ		13	5	1310	490	40000	6	11.4		3.2	
	634ZZ		16	6	0.3	1340	523	36000	6	14	0.3	5.44
	675ZZ		8	2.5	0.1	218	131	53000	5.8	7.4	0.1	0.34
	685ZZ	6	11	5	0.15	715	282	45000	6.2	9.8		1.96
	695ZZ		13	4	0.2	1080	430	43000	6.6	11.4	0.2	2.4
	605ZZ		14	5	1330	505	40000	6	12.4		3.5	
	625ZZ		16	6	1760	680	36000	7	14		4.8	
	635ZZ	7	19	6	0.3	2336	896	32000	7	17	0.3	8.89
	676ZZ		10	3	0.1	496	218	45000	7.04	9.3	0.1	0.7
	686ZZ		13	5	0.16	1080	440	40000	7	11.8		2.69
	696ZZ		15	5	0.2	1350	530	40000	7.6	13.4	0.2	3.8
	606ZZ	8	17			2190	865	38000	15		6	
	626ZZ		19	6	0.3	2340	885	32000	8	17	0.3	8.1
	636ZZ		22	7		3333	1423	30000	20		14.5	
	687ZZ		14	5	0.15	1170	505	40000	8.2	12.8	0.15	2.97
	697ZZ	9	17			1610	710	36000	9	15		5.12
	607ZZ		19	6	0.3	2340	885	36000	9	17	0.3	7.51
	627ZZ		22	7		3300	1370	30000	20		12.9	
	678ZZ		12	3.5	0.1	543	274	40000	8	11.33	0.1	0.99
	688ZZ	10	16	5	0.2	1610	715	36000	9.6	14.4	0.2	4.02
	698ZZ		19	6		1990	865		17		7.3	
	608ZZ		22	7		3350	1400	34000	10	20	0.3	12
	628ZZ		24	8	0.3	4000	1590		10	22		17
	638ZZ	11	28	9		4560	1983	28000	26		30.3	
	689ZZ		17	5	0.2	1720	820	33000	10.6	15.4	0.2	3.2
	699ZZ		20	6		2480	1090	32000	11	18		8.2
	609ZZ		24	7	0.3	3400	1450	31000	11	22	0.3	14
	629ZZ		26	8	0.6	4550	1960	30000	13			20

❶ SUS304材质仅适用带*规格。

❶ 1KgF=9.81N



型号		d
代码	轴承型号	
BAF	682ZZ	2
	692ZZ	
	602ZZ	

BAF682ZZ



优惠价	
数量	价格
1~9	100%
10~	另行报价



❶ 深沟球轴承装配在导向块上，对其他工件起到导向的作用。

