


日标

代码	类型	材质		硬度	表面处理	适用标准
		国标	相当			
TBP11	E型	弹簧钢		42~51HRC	磷化黑	JIS B 2805-1978
TBP12		3Cr13	SUS420J2	34~42HRC	—	

TBP11



TBP12



视角标准：第一视角

型号	规格	d	D	H	t	d <sub>1</sub> 的分类			适用轴(参考)			
						大于	以下	d <sub>2</sub>	m	n (min)		
(弹簧钢) TBP11	1.2	1.2	3	±0.1	1	0.3	±0.025	1.4	2	1.23	0.4	0.6
	1.5	1.5	4		1.3			2	2.5	1.53		0.8
	2	2	5		1.7	0	±0.03	2.5	3.2	2.05	+0.06 0	0.5
	2.5	2.5	6		2.1	-0.25		3.2	4	2.55		1
	3	3	7		2.6			4	5	3.05		
(SUS420J2) TBP12	4	4	9	±0.2	3.5	0	±0.04	5	7	4.05	+0.075 0	0.7
	5	5	11		4.3	0		6	8	5.05		1.2
	6	6	12		5.2	-0.30		7	9	6.05		+0.1 0
	7	7	14		6.1			8	11	7.1		1.5
	8	8	16		6.9	0	±0.09 0	9	12	8.1		1.8
9	9	18		7.8			10	13	9.1		2.1	



型号	规格	d
TBP11	1.2	1.2
TBP12	1.5	1.5



● 优惠价  
数量 1~45 46~  
价格 100% 另行报价



交货期  
7


国标

代码	类型	材质		表面处理	适用标准
		国标	相当		
TBP41	E型	65Mn(弹簧钢)		发黑	GB/T 896-1986
TBP42		0Cr18Ni9	SUS304		

TBP41



TBP42



视角标准：第一视角

型号	规格	公称直径 d	极限偏差	挡圈尺寸				安装沟槽尺寸				轴径		
				基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差			
(弹簧钢) TBP41	1.2*	1.2		0.9	±0.08	0.3		3	1.2		0.4		1.0	1.4~2
	1.5	1.5		1.2				4	1.5					2~2.5
	2	2	-0.14	1.7		0.4	+0.03 -0.06	5	2.0	+0.06 0	0.5			2.5~3.2
	2.5	2.5		2.2	±0.125			6	2.5				1.2	3.2~4
	3	3		2.5		0.6	+0.04 -0.07	7	3.0		0.7			4~5
(SUS304) TBP42	3.5	3.5		3.0				8	3.5					
	4	4		3.5				9	4.0	+0.075 0	0.9	+0.14 0	1.5	5~7
	5	5	-0.18	4.5	±0.15	0.8	+0.04 -0.10	10	5.0					6~8
	6	6		5.5				12	6.0					7~9
	8	8		7.5		1.0	+0.05 -0.13	16	8.0	+0.09 0	1.1			9~12
9	9	-0.22	8.0	±0.18			18	9.0					2.0	10~14
12	12		10.5		1.2		24	12.0		1.3			2.5	13~16
15	15	-0.27	13.0	±0.215	1.5	+0.06 -0.15	30	15.0	+0.11 0	1.6			3.0	16~20

① 带\*号规格不适用TBP42。



型号	规格	公称直径 d
TBP41	1.2	1.2
TBP42	1.5	1.5



● 优惠价  
数量 1~45 46~  
价格 100% 另行报价



交货期  
7