


# 标准型 圆形连接器

# 弯式金属软管插头

WS系列 威浦品牌



代码	类型	接插方式	材质		
			外壳	绝缘体	接触件
WS系列	弯式金属软管插头	螺纹连接	锌合金(镀铬)	热塑塑料PPS	铜(镀金)



尺寸表

系列	WS20	WS24	WS28	WS32	WS40	WS48	WS55
D	27.5	31	35	39	49	57	64.5
H	50	51	54.5	63	73	89	97.5
L	60	60	64	82	87.5	94	115
管规	3/8"	3/8"	1/2"	3/4"	1"	1"	1 1/4"



插针

型号	配合直径	芯数	适配插座(常用)		以下系列型号均可适配	
			方形法兰插座(Z)	后螺母插座(ZM)		
WS20J2TR	20	2	WS20K2Z	WS20K2ZM	适配插座 WS...ZMQ WS...ZG WS...ZYB WS...ZY WS...ZQB WS...ZQ WS...ZPB WS...ZP WS...ZDB WS...ZD WS...ZR WS...ZS WS...ZC 详见 产品简介 插头插座 配置表 (Pxxx)	
WS20J3TR		3	WS20K3Z	WS20K3ZM		
WS20J4TR		4	WS20K4Z	WS20K4ZM		
WS20J5TR		5	WS20K5Z	WS20K5ZM		
WS20J6TR		6	WS20K6Z	WS20K6ZM		
WS20J7TR		7	WS20K7Z	WS20K7ZM		
WS20J9TR		9	WS20K9Z	WS20K9ZM		
WS20J12TR		12	WS20K12Z	WS20K12ZM		
WS24J2TR		24	2	WS24K2Z		WS24K2ZM
WS24J3TR			3	WS24K3Z		WS24K3ZM
WS24J4TR	4		WS24K4Z	WS24K4ZM		
WS24J9TR	9		WS24K9Z	WS24K9ZM		
WS24J10TR	10		WS24K10Z	WS24K10ZM		
WS24J12TR	12		WS24K12Z	WS24K12ZM		
WS24J19TR	19		WS24K19Z	WS24K19ZM		
WS28J2TR	28		2	WS28K2Z	WS28K2ZM	
WS28J3TR			3	WS28K3Z	WS28K3ZM	
WS28J4TR			4	WS28K4Z	WS28K4ZM	
WS28J7TR		7	WS28K7Z	WS28K7ZM		
WS28J8TR		8	WS28K8Z	WS28K8ZM		
WS28J9TR		9	WS28K9Z	WS28K9ZM		
WS28J10TR		10	WS28K10Z	WS28K10ZM		
WS28J12TR		12	WS28K12Z	WS28K12ZM		
WS28J16TR		16	WS28K16Z	WS28K16ZM		
WS28J17TR		17	WS28K17Z	WS28K17ZM		
WS28J20TR	32	20	WS28K20Z	WS28K20ZM		
WS28J24TR		24	WS28K24Z	WS28K24ZM		
WS28J26TR		26	WS28K26Z	WS28K26ZM		
WS32J4TR		32	4	WS32K4Z	WS32K4ZM	
WS32J6TR			6	WS32K6Z	WS32K6ZM	
WS32J8TR			8	WS32K8Z	WS32K8ZM	
WS32J10TR			10	WS32K10Z	WS32K10ZM	
WS32J11TR			11	WS32K11Z	WS32K11ZM	
WS32J12TR			12	WS32K12Z	WS32K12ZM	
WS32J13TR			13	WS32K13Z	WS32K13ZM	
WS32J19TR	19		WS32K19Z	WS32K19ZM		
WS40J5TR	40		5	WS40K5Z	WS40K5ZM	
WS40J9TR			9	WS40K9Z	WS40K9ZM	
WS40J15TR		15	WS40K15Z	WS40K15ZM		
WS40J26TR		26	WS40K26Z	WS40K26ZM		
WS40J31TR		31	WS40K31Z	WS40K31ZM		
WS40J52TR		52	WS40K52Z	WS40K52ZM		
WS48J5TR		48	5	WS48K5Z	WS48K5ZM	
WS48J7TR			7	WS48K7Z	WS48K7ZM	
WS48J20TR			20	WS48K20Z	WS48K20ZM	
WS48J27TR			27	WS48K27Z	WS48K27ZM	
WS48J38TR	38		WS48K38Z	WS48K38ZM		
WS48J42TR	42		WS48K42Z	WS48K42ZM		
WS55J4TR	55		4	WS55K4Z	WS55K4ZM	
WS55J7TR			7	WS55K7Z	WS55K7ZM	
WS55J40TR			40	WS55K40Z	WS55K40ZM	
WS55J53TR			53	WS55K53Z	WS55K53ZM	
WS55J61TR		61	WS55K61Z	WS55K61ZM		

插孔

型号	配合直径	芯数	适配插座(常用)		以下系列型号均可适配	
			方形法兰插座(Z)	后螺母插座(ZM)		
WS20K2TR	20	2	WS20J2Z	WS20J2ZM	适配插座 WS...ZMQ WS...ZG WS...ZYB WS...ZY WS...ZQB WS...ZQ WS...ZPB WS...ZP WS...ZDB WS...ZD WS...ZR WS...ZS WS...ZC 详见 产品简介 插头插座 配置表 (Pxxx)	
WS20K3TR		3	WS20J3Z	WS20J3ZM		
WS20K4TR		4	WS20J4Z	WS20J4ZM		
WS20K5TR		5	WS20J5Z	WS20J5ZM		
WS20K6TR		6	WS20J6Z	WS20J6ZM		
WS20K7TR		7	WS20J7Z	WS20J7ZM		
WS20K9TR		9	WS20J9Z	WS20J9ZM		
WS20K12TR		12	WS20J12Z	WS20J12ZM		
WS24K2TR		24	2	WS24J2Z		WS24J2ZM
WS24K3TR			3	WS24J3Z		WS24J3ZM
WS24K4TR	4		WS24J4Z	WS24J4ZM		
WS24K9TR	9		WS24J9Z	WS24J9ZM		
WS24K10TR	10		WS24J10Z	WS24J10ZM		
WS24K12TR	12		WS24J12Z	WS24J12ZM		
WS24K19TR	19		WS24J19Z	WS24J19ZM		
WS28K2TR	28		2	WS28J2Z	WS28J2ZM	
WS28K3TR			3	WS28J3Z	WS28J3ZM	
WS28K4TR			4	WS28J4Z	WS28J4ZM	
WS28K7TR		7	WS28J7Z	WS28J7ZM		
WS28K8TR		8	WS28J8Z	WS28J8ZM		
WS28K9TR		9	WS28J9Z	WS28J9ZM		
WS28K10TR		10	WS28J10Z	WS28J10ZM		
WS28K12TR		12	WS28J12Z	WS28J12ZM		
WS28K16TR		16	WS28J16Z	WS28J16ZM		
WS28K17TR		17	WS28J17Z	WS28J17ZM		
WS28K20TR	32	20	WS28J20Z	WS28J20ZM		
WS28K24TR		24	WS28J24Z	WS28J24ZM		
WS28K26TR		26	WS28J26Z	WS28J26ZM		
WS32K4TR		32	4	WS32J4Z	WS32J4ZM	
WS32K6TR			6	WS32J6Z	WS32J6ZM	
WS32K8TR			8	WS32J8Z	WS32J8ZM	
WS32K10TR			10	WS32J10Z	WS32J10ZM	
WS32K11TR			11	WS32J11Z	WS32J11ZM	
WS32K12TR			12	WS32J12Z	WS32J12ZM	
WS32K13TR			13	WS32J13Z	WS32J13ZM	
WS32K19TR	19		WS32J19Z	WS32J19ZM		
WS40K5TR	40		5	WS40J5Z	WS40J5ZM	
WS40K9TR			9	WS40J9Z	WS40J9ZM	
WS40K15TR		15	WS40J15Z	WS40J15ZM		
WS40K26TR		26	WS40J26Z	WS40J26ZM		
WS40K31TR		31	WS40J31Z	WS40J31ZM		
WS40K52TR		52	WS40J52Z	WS40J52ZM		
WS48K5TR		48	5	WS48J5Z	WS48J5ZM	
WS48K7TR			7	WS48J7Z	WS48J7ZM	
WS48K20TR			20	WS48J20Z	WS48J20ZM	
WS48K27TR			27	WS48J27Z	WS48J27ZM	
WS48K38TR	38		WS48J38Z	WS48J38ZM		
WS48K42TR	42		WS48J42Z	WS48J42ZM		
WS55K4TR	55		4	WS55J4Z	WS55J4ZM	
WS55K7TR			7	WS55J7Z	WS55J7ZM	
WS55K40TR			40	WS55J40Z	WS55J40ZM	
WS55K53TR			53	WS55J53Z	WS55J53ZM	
WS55K61TR		61	WS55J61Z	WS55J61ZM		

技术参数

接插方式	螺纹连接
接线方式	焊接
接插次数	500次
温度范围	-40℃~+85℃



型号  
WS20J2TR