


标准型·细牙
左旋螺纹·粗牙/细牙

六角螺母

标准型

代码	类型	螺纹	材质		表面处理	适用标准	强度等级
			国标	相当			
TBK58	标准型	细牙	45	S45C	发黑	GB/T 6171-2000	—
TBK59			0Cr18Ni9	SUS304	镀锌		
TBK60			10B21		发黑		




TBK58/60



TBK59



TBK65



视角标准：第一视角

型号		螺距 P	m		S		e
代码	M		(max)	(min)	(max)	(min)	(min)
(S45C) TBK58	8	1	6.8	6.44	13	12.73	14.38
	10		8.4	8.04	16	15.73	17.77
	12		1.25	10.8	10.37	18	17.73
	14	1.5	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20		18	16.9	30	29.16	32.95
	22		19.4	18.1	34	33	37.29
24	2	21.5	20.2	36	35	39.55	
(S45C) TBK59	10	1	8.4	8.04	16	15.73	17.77
	12	1.25	10.8	10.37	18	17.73	20.03
	14	1.5	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
(SUS304) TBK65	8	1	6.8	6.44	13	12.73	14.38
	10		8.4	8.04	16	15.73	17.77
	12		1.25	10.8	10.37	18	17.73
	14	1.5	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20		18	16.9	30	29.16	32.95
	22		19.4	18.1	34	33	37.29
(10B21) TBK60	8	1	6.8	6.44	13	12.73	14.38
	10		8.4	8.04	16	15.73	17.77
	12		1.25	10.8	10.37	18	17.73
	14	1.25	12.8	12.1	21	20.67	23.36
	16		14.8	14.1	24	23.67	26.75
	18		15.8	15.1	27	26.16	29.56
	20		18	16.9	30	29.16	32.95
	22		1.5	19.4	18.1	34	33
	24	2	21.5	20.2	36	35	39.55
	26	1.5	23.8	22.5	41	40	45.2
	27A	2					