

代码	类型	材质		抗拉强度	
		国标	相当		
Y-LBA02	标准型	A型	0Cr18Ni9	SUS304	600N/mm <sup>2</sup> 以上
Y-LBA04		B型			
Y-LBA06		C型			


□ L尺寸公差

L	公差
最短~10	<sup>0</sup> / <sub>-0.36</sub>
12~18	<sup>0</sup> / <sub>-0.43</sub>
20~28	<sup>0</sup> / <sub>-0.52</sub>
32~50	<sup>0</sup> / <sub>-0.62</sub>
56~80	<sup>0</sup> / <sub>-0.74</sub>
90~110	<sup>0</sup> / <sub>-0.87</sub>
125~180	<sup>0</sup> / <sub>-1.0</sub>
200	<sup>0</sup> / <sub>-1.15</sub>




□ 适用标准: GB/T 1096-2003


A型  
Y-LBA02



B型  
Y-LBA04



C型  
Y-LBA06



视角标准: 第一视角

型号		L										H	C										
代码	B <sub>h8</sub>	6	8	10	12	14	16	18	20	22	25	28	32	36	3	4	5	6	7	8	9	10	11
A型 Y-LBA02	3	6 8 10 12 14 16 18 20 22 25 28 32 36										3	0.16~0.25										
	4	8 10 12 14 16 18 20 22 25 28 32 36 40 45										4											
	5	10 12 14 16 18 20 22 25 28 32 36 40 45 50 56										5											
B型 Y-LBA04	6	14 16 18 20 22 25 28 32 36 40 45 50 56 63 70										6	0.25~0.40										
	8	18 20 22 25 28 32 36 40 45 50 56 63 70 80 90										7											
	10	22 25 28 32 36 40 45 50 56 63 70 80 90 100 110										8											
C型 Y-LBA06	12	28 32 36 40 45 50 56 63 70 80 90 100 110 125 140										8	0.40~0.60										
	14	36 40 45 50 56 63 70 80 90 100 110 125 140 160										9											
	16	45 50 56 63 70 80 90 100 110 125 140 160 180										10											
	18	50 56 63 70 80 90 100 110 125 140 160 180 200										11											



请按图示订货

型号			
代码	B <sub>h8</sub>	L	H
Y-LBA02	3	6 8 10	3
Y-LBA04	4	8 10	4

Y-LBA02—B3—L8



未税价(元)

● 优惠价

数量	1~200	201~
价格	100%	另行报价