

O型圈平面密封过渡接头

公制螺纹

直接头/90°弯接头/T型三通接头




直接头

| 代码 | 类型 | 材质 |
|-------|-----|--------|
| WSB01 | 外螺纹 | 碳钢 |
| WSB02 | 外螺纹 | SUS304 |

规格: 14/18/22/30/36

规格: 14A/16A/18A/22A/30A

规格: 14B/16B/22B/30B




视角标准: 第一视角

| 型号 | | M | N | A | B | L | S |
|----------------|-----|---------|---------|----|------|------|----|
| WSB01 WSB02 | 14 | | M14×1.5 | | | | |
| | 14A | M14×1.5 | M12×1.5 | | 11 | 28 | 17 |
| | 14B | M16×1.5 | M16×1.5 | | 12 | 31 | 22 |
| | 16A | M16×1.5 | M14×1.5 | 11 | 11 | 28 | 19 |
| | 16B | M18×1.5 | M18×1.5 | | 12 | 31 | 24 |
| | 18 | M18×1.5 | M18×1.5 | | 11 | 28 | 19 |
| | 18A | M18×1.5 | M16×1.5 | | 11.5 | 31.5 | 22 |

| 型号 | | M | N | A | B | L | S |
|----------------|-----|---------|---------|----|------|------|------|
| WSB01 WSB02 | 22 | | M22×1.5 | | 12 | 32 | 32 |
| | 22A | M22×1.5 | M18×1.5 | 12 | 12.5 | 34.5 | 34.5 |
| | 22B | M22×1.5 | M18×1.5 | | 12 | 33.5 | 33.5 |
| | 30 | | M30×1.5 | | 14 | 39 | 39 |
| | 30A | M30×1.5 | M27×2 | 14 | 18.5 | 43.5 | 43.5 |
| | 30B | M30×1.5 | M18×1.5 | | 12 | 38.5 | 38.5 |
| | 36 | M36×2 | M36×2 | | 16 | 43 | 45.5 |

90°弯接头-外螺纹

| 代码 | 类型 | 材质 |
|-------|-----|--------|
| WSB06 | 外螺纹 | 碳钢 |
| WSB07 | 外螺纹 | SUS304 |




视角标准: 第一视角

| 型号 | | M | A | S |
|----------------|----|---------|------|----|
| WSB06 WSB07 | 14 | M14×1.5 | 22.5 | 14 |
| | 18 | M18×1.5 | 26 | 19 |
| | 22 | M22×1.5 | 29 | 22 |
| | 30 | M30×1.5 | 35.5 | 30 |
| | 36 | M36×2 | 42 | 36 |

90°弯接头-内外螺纹

| 代码 | 类型 | 材质 |
|-------|------|--------|
| WSB08 | 内外螺纹 | 碳钢 |
| WSB09 | 内外螺纹 | SUS304 |





视角标准: 第一视角

| 型号 | | M | A | B | S | S ₁ |
|----------------|----|---------|------|-----|----|----------------|
| WSB08 WSB09 | 14 | M14×1.5 | 22.5 | 8.5 | 19 | 14 |
| | 18 | M18×1.5 | 26 | | 24 | 19 |
| | 22 | M22×1.5 | 29 | 10 | 27 | 22 |
| | 30 | M30×1.5 | 35.5 | 11 | 36 | 30 |
| | 36 | M36×2 | 42 | 13 | 41 | 36 |

T型三通接头

| 代码 | 类型 | 材质 |
|-------|-----|--------|
| WSB11 | 外螺纹 | 碳钢 |
| WSB12 | 外螺纹 | SUS304 |



视角标准: 第一视角

| 型号 | | M | A | S |
|----------------|----|---------|------|----|
| WSB11 WSB12 | 14 | M14×1.5 | 22.5 | 14 |
| | 18 | M18×1.5 | 26 | 19 |
| | 22 | M22×1.5 | 29 | 22 |
| | 30 | M30×1.5 | 35.5 | 30 |
| | 36 | M36×2 | 42 | 36 |

T型三通接头

| 型号 | | |
|-------|----|---------|
| 代码 | 规格 | M |
| WSB11 | 14 | M14×1.5 |
| WSB12 | 18 | M18×1.5 |

请按图示订货

WSB11-14

| | | | | |
|--------|-------|------|------|-----|
| 未税价(元) | ● 优惠价 | 数量 | 1~19 | 20~ |
| | ● 价格 | 100% | 另行报价 | |

| | |
|-----|---|
| 交货期 | 7 |
|-----|---|