


推力滚针轴承


代码	类型			材质
E-BKL	经济型	单件	带保持器止推滚针	SUJ2
E-BNL			止推圈	65Mn
E-BBL		套件	带保持器止推滚针+止推圈	SUJ2+65Mn




单件
带保持器止推滚针
E-BKL



止推圈
E-BNL



组件
带保持器止推滚针+止推圈
E-BBL



止推圈在交货时可能会有少许变形，使用前请以同心圆的方式施加最低200N轴向负载即可使之平整。



型号		带保持器止推滚珠					止推圈×2			极限转速 (rpm)	基本额定负载(KN)		参考重量(g)		
代码	轴承型号	d	D	A	E	E1	d1	D1	B		Cr(动)	Cor(静)	E-BKL	E-BNL	E-BBL
E-BKL E-BNL E-BBL	0414	4	14	-0.095 -0.365	13	5	4	14	-0.032 -0.302	15050	3.08	5.6	0.7	1	2.7
	0515	5	15	-0.11 -0.44	14	6	5	15	-0.040 -0.370	14420	3.325	6.44	0.8	1	2.8
	0619	6	19	-0.14 -0.61	18	7	6	19	-0.040 -0.370	13230	4.76	10.85	1	2	5
	0821	8	21	-0.14 -0.61	20	9	8	21	-0.040 -0.370	12460	5.46	13.58	2	2	6
	1024	10	24	-0.14 -0.61	23	12	10	24	-0.040 -0.370	11830	6.44	17.85	3	3	9
	1226	12	26	-0.14 -0.61	25	14	12	26	-0.040 -0.370	10640	6.93	20.3	3	3	9
	1528	15	28	-0.14 -0.61	27	17	15	28	-0.040 -0.370	9240	7.91	25.2	4	3	10
	1730	17	30	-0.14 -0.61	29	19	17	30	-0.040 -0.370	8470	8.33	27.65	4	4	12
	2035	20	35	-0.14 -0.61	34	22	20	35	-0.040 -0.370	7350	9.17	32.55	5	5	15
	2542	25	42	-0.14 -0.61	41	29	25	42	-0.040 -0.370	5880	10.29	40.6	7	7	21
	3047	30	47	-0.14 -0.61	46	34	30	47	-0.040 -0.370	5110	11.41	49	8	8	24
	3552	35	52	-0.14 -0.61	51	39	35	52	-0.040 -0.370	4550	12.46	56.7	10	9	28
	4060	40	60	-0.14 -0.61	58	45	40	60	-0.040 -0.370	3920	19.6	79.8	16	12	40
	4565	45	65	-0.14 -0.61	63	50	45	65	-0.040 -0.370	3570	21	89.6	18	13	44
	5070	50	70	-0.14 -0.61	68	55	50	70	-0.040 -0.370	3290	22.4	100.1	20	14	48
	5578	55	78	-0.14 -0.61	76	60	55	78	-0.040 -0.370	2980	26.6	130.2	28	18	64
	6085	60	85	-0.14 -0.61	83	65	60	85	-0.040 -0.370	2730	31.15	163.8	33	22	77
	6590	65	90	-0.14 -0.61	88	70	65	90	-0.040 -0.370	2560	39.76	178.5	35	24	83
	7095	70	95	-0.14 -0.61	93	74	70	95	-0.040 -0.370	2420	37.8	178.5	60	25	110
	75100	75	100	-0.14 -0.61	98	79	75	100	-0.040 -0.370	2280	38.5	185.5	61	27	115
	80105	80	105	-0.14 -0.61	103	84	80	105	-0.040 -0.370	2170	39.2	196	63	28	119
	85110	85	110	-0.14 -0.61	108	89	85	110	-0.040 -0.370	2070	40.6	203	67	29	125
	90120	90	120	-0.14 -0.61	118	94	90	120	-0.040 -0.370	1890	51.1	283.5	86	39	164
	100135	100	135	-0.14 -0.61	133	105	100	135	-0.040 -0.370	1690	63.7	392	104	50	204
	110145	110	145	-0.14 -0.61	143	115	110	145	-0.040 -0.370	1560	67.9	434	122	55	232
	120155	120	155	-0.14 -0.61	153	125	120	155	-0.040 -0.370	1450	71.4	476	131	59	249
	130170	130	170	-0.14 -0.61	167	136	130	170	-0.040 -0.370	1330	93.1	588	205	65	335
	140180	140	180	-0.14 -0.61	177	146	140	180	-0.040 -0.370	1250	96.6	630	219	79	377
	150190	150	190	-0.14 -0.61	187	156	150	190	-0.040 -0.370	1180	100.1	672	232	84	400
	160200	160	200	-0.14 -0.61	197	166	160	200	-0.040 -0.370	1110	103.6	714	246	89	424

d4~d8规格为尼龙保持架，d8以上规格为钢制保持架。

1Kg=9.81N



型号			d
代码	轴承型号		
E-BKL	0414		4
E-BNL	0515		5
E-BKL0414			



优惠价	数量	1~9	10~
价格	100%	另行报价	



交货期	5
-----	---