




标准型 圆形连接器

前螺母插座 WS系列 威浦品牌



代码	类型	接插方式	材质		
			外壳	绝缘体	接触件
WS系列	前螺母插座	螺纹连接	锌合金 (镀铬)	热塑塑料PPS	铜(镀金)



安装开孔尺寸

尺寸表

系列	WS16	WS20	WS24	WS28
m	M18×1	M22×1	M26×1	M30×1
M	M22×1	M26×1	M30×1	M34×1
L ₁	16	17	17	17
L	21.6	23	23	23
C	5	5	5	5
S	26.8	30.8	34.8	38.8
D	22	26	30	34
h	20.6	24.6	28.6	32.6



视角标准：第一视角

插针

型号	配合直径	芯数	适配插头(常用)		以下系列 型号 均可适配	
			直式电缆护套 插头(TQ)	弯式双压板电缆 插头(TS)		
WS16J2ZMQ	16	2	WS16K2TQ	WS16K2TS	适配插头 WS...TP WS...TD WS...TR WS...TC 详见 产品简介 插头插座 配置表 (Pxxx)	
WS16J3ZMQ		3	WS16K3TQ	WS16K3TS		
WS16J4ZMQ		4	WS16K4TQ	WS16K4TS		
WS16J5ZMQ		5	WS16K5TQ	WS16K5TS		
WS16J7ZMQ		7	WS16K7TQ	WS16K7TS		
WS16J9ZMQ		9	WS16K9TQ	WS16K9TS		
WS16J10ZMQ		10	WS16K10TQ	WS16K10TS		
WS20J2ZMQ		20	2	WS20K2TQ		WS20K2TS
WS20J3ZMQ			3	WS20K3TQ		WS20K3TS
WS20J4ZMQ			4	WS20K4TQ		WS20K4TS
WS20J5ZMQ	5		WS20K5TQ	WS20K5TS		
WS20J6ZMQ	6		WS20K6TQ	WS20K6TS		
WS20J7ZMQ	7		WS20K7TQ	WS20K7TS		
WS20J9ZMQ	9		WS20K9TQ	WS20K9TS		
WS20J12ZMQ	12		WS20K12TQ	WS20K12TS		
WS24J2ZMQ	24		2	WS24K2TQ	WS24K2TS	
WS24J3ZMQ			3	WS24K3TQ	WS24K3TS	
WS24J4ZMQ		4	WS24K4TQ	WS24K4TS		
WS24J9ZMQ		9	WS24K9TQ	WS24K9TS		
WS24J10ZMQ		10	WS24K10TQ	WS24K10TS		
WS24J12ZMQ		12	WS24K12TQ	WS24K12TS		
WS24J19ZMQ		19	WS24K19TQ	WS24K19TS		
WS28J2ZMQ		28	2	WS28K2TQ	WS28K2TS	
WS28J3ZMQ			3	WS28K3TQ	WS28K3TS	
WS28J4ZMQ			4	WS28K4TQ	WS28K4TS	
WS28J7ZMQ	7		WS28K7TQ	WS28K7TS		
WS28J8ZMQ	8		WS28K8TQ	WS28K8TS		
WS28J9ZMQ	9		WS28K9TQ	WS28K9TS		
WS28J10ZMQ	10		WS28K10TQ	WS28K10TS		
WS28J12ZMQ	12		WS28K12TQ	WS28K12TS		
WS28J16ZMQ	16	WS28K16TQ	WS28K16TS			
WS28J17ZMQ	17	WS28K17TQ	WS28K17TS			
WS28J20ZMQ	20	WS28K20TQ	WS28K20TS			
WS28J24ZMQ	24	WS28K24TQ	WS28K24TS			
WS28J26ZMQ	26	WS28K26TQ	WS28K26TS			

插孔

型号	配合直径	芯数	适配插头(常用)		以下系列 型号 均可适配	
			直式电缆护套 插头(TQ)	弯式双压板电缆 插头(TS)		
WS16K2ZMQ	16	2	WS16J2TQ	WS16J2TS	适配插头 WS...TP WS...TD WS...TR WS...TC 详见 产品简介 插头插座 配置表 (Pxxx)	
WS16K3ZMQ		3	WS16J3TQ	WS16J3TS		
WS16K4ZMQ		4	WS16J4TQ	WS16J4TS		
WS16K5ZMQ		5	WS16J5TQ	WS16J5TS		
WS16K7ZMQ		7	WS16J7TQ	WS16J7TS		
WS16K9ZMQ		9	WS16J9TQ	WS16J9TS		
WS16K10ZMQ		10	WS16J10TQ	WS16J10TS		
WS20K2ZMQ		20	2	WS20J2TQ		WS20J2TS
WS20K3ZMQ			3	WS20J3TQ		WS20J3TS
WS20K4ZMQ			4	WS20J4TQ		WS20J4TS
WS20K5ZMQ	5		WS20J5TQ	WS20J5TS		
WS20K6ZMQ	6		WS20J6TQ	WS20J6TS		
WS20K7ZMQ	7		WS20J7TQ	WS20J7TS		
WS20K9ZMQ	9		WS20J9TQ	WS20J9TS		
WS20K12ZMQ	12		WS20J12TQ	WS20J12TS		
WS24K2ZMQ	24		2	WS24J2TQ	WS24J2TS	
WS24K3ZMQ			3	WS24J3TQ	WS24J3TS	
WS24K4ZMQ		4	WS24J4TQ	WS24J4TS		
WS24K9ZMQ		9	WS24J9TQ	WS24J9TS		
WS24K10ZMQ		10	WS24J10TQ	WS24J10TS		
WS24K12ZMQ		12	WS24J12TQ	WS24J12TS		
WS24K19ZMQ		19	WS24J19TQ	WS24J19TS		
WS28K2ZMQ		28	2	WS28J2TQ	WS28J2TS	
WS28K3ZMQ			3	WS28J3TQ	WS28J3TS	
WS28K4ZMQ			4	WS28J4TQ	WS28J4TS	
WS28K7ZMQ	7		WS28J7TQ	WS28J7TS		
WS28K8ZMQ	8		WS28J8TQ	WS28J8TS		
WS28K9ZMQ	9		WS28J9TQ	WS28J9TS		
WS28K10ZMQ	10		WS28J10TQ	WS28J10TS		
WS28K12ZMQ	12		WS28J12TQ	WS28J12TS		
WS28K16ZMQ	16	WS28J16TQ	WS28J16TS			
WS28K17ZMQ	17	WS28J17TQ	WS28J17TS			
WS28K20ZMQ	20	WS28J20TQ	WS28J20TS			
WS28K24ZMQ	24	WS28J24TQ	WS28J24TS			
WS28K26ZMQ	26	WS28J26TQ	WS28J26TS			

技术参数

接插方式	螺纹连接
接线方式	焊接
接插次数	500次
温度范围	-40°C~+85°C



请按图示订货

型号

WS16J2ZMQ

