

## 标准型/直线轴承用/台阶型 ▶

## 调整环




代码	号 D 最小单位0.5	V 最小单位0.5 (V尺寸3以上)	L 最小单位0.1	同时研磨 最多数量
	₩ 4.0~15	0 1.5 2.0 2.6 3.0~8.0	1.0~55	100个
AT A	10.5~20	0 1.5 2.0 2.6 3.0~13.5	1.0~110	100-1-
UCE01	16.0~30	0 1.5 2.0 2.6 3.0~18.0		50个
UCE07	20.5~35	0 1.5 2.0 2.6 3.0~28.0	1.0~110	30
	30.5~40	0 1.5 2.0 2.6 3.0~37.5	1.0~110	20个
	40.0~60	0 1.5 2.0 2.6 3.0~48.0		201

## ○ 直线轴承用



型	号	L	-	
代码	规格	最小单位1	D	V
	3		7	4
	4		8	5
	5	3~60	10	6
	6		12	7
	8		15	9
	(V. 10		19	11
UCE51	12		21	13
	13	6~110	23	14
UCE56	16		28	17
	20		32	22
	25		40	27
	30		45	32
	35	9~160	52	37
	40		60	42
	50		80	52





UCE51-10-L50

! 当L长度过长时, 孔中间可能带有退刀槽。



● 优惠	价	
数量	1~9	10~
价格	100%	另行报价

视角标准:第一视角



## ◯ 台阶型

代码	类型	L尺寸 公差	材 国标	质 相当	表面处理	
UCH01 UCH02		0 -0.1	45	S45C	发黑 无电解镀镍	
UCH07	台阶型		0Cr18Ni9	SUS304		
UCH11 UCH12		+0.1	45	S45C	发黑 无电解镀镍	
UCH17			0Cr18Ni9	SUS304	_	
① 如对防 UCH01		请优先证	选用不锈 <b></b>	羽材质或		品. []
R0.5max + 图定制						
		H-02		0.8	Dh7	
UCH11	/12/17	-02	R0.5	max	0.8/ LHZ	OMATIONEXPE

型号	最小单位0.5			最小单位0.1	
代码	D <sub>h</sub> 7	V <sub>H7</sub>	Н	Т	L
	5.0~15	2.0~12	7.0~20		1.0~55
L公差-8.1 L公差+8.1 UCH01 UCH11 UCH02 UCH12 UCH07 UCH17	10.5~30	2.0~25	12.5~35	1.0~20.0	
	20.5~50	2.0~45	22.5~60		
	30.5~50	6.0~45	32.5~60		
4	40.5~60	10.0~55	42.5~65		





● 优惠价				
数量	1~99	100~		
价格	100%	另行报价		



环 圏

轴垫

C1