


# 带止动片眼型旋转吊环(橙色)

代码	类型	材质	表面处理
TCF43	带止动片眼型旋转吊环	合金钢	烤漆(橙色)



① 因烤漆工艺, 可能会导致产品吊装处部分区域未能烤漆。

代码	型号		M	安全系数	(A)	B	C	D	E	F	S	W	净重 (kg)								
	规格																				
TCF43	0.3T	8	4	40	25	8	9.5	12	26	6	44	0.15									
		10																			
	0.75T	12											47	30	10	11	18	32	8	52	0.2
		14																			
	1.5T	16											54	35	14	13	24	39	10	61	0.35
		18																			
	2.3T	20											63	40	16	15	30	47	12	70	0.6
		22																			
	3.2T	24											73	48	19	18	36	55	14	84	1
		27																			
	4.5T	30											91.5	60	24	22.5	45	67	17	105	2
		33																			
	7T	36											114	72	29	27	54	85	22	126	3
	9T	42											130	82	34	32.5	63	98		147	5
12T	48	151	96	38	36	72	114	27	168	7.5											

## 工作极限载荷

吊环安装方式												
吊环数量		1	2	1	2	2	2	2	3~4	3~4	3~4	
起吊角度		0°	0°	90°	90°	0~45°	45~60°	不对称	0~45°	45~60°	不对称	
型号		工作极限载荷(吨)										
代码	规格	螺纹										
TCF43	0.3T	M8	1	2	0.3	0.6	0.42	0.3	0.3	0.63	0.45	0.3
	0.4T	M10			0.4	0.8	0.56	0.4	0.4	0.8	0.6	0.4
	0.75T	M12	2	4	0.75	1.5	1	0.75	0.75	1.5	1.1	0.75
		M14										
	1.5T	M16	4	8	1.5	3	2.1	1.5	1.5	3.1	2.2	1.5
		M18										
	2.3T	M20	6	12	2.3	4.6	3.2	2.3	2.3	4.8	3.4	2.3
		M22										
	3.2T	M24	8	16	3.2	6.4	4.5	3.2	3.2	6.7	4.8	3.2
		M27										
	4.5T	M30	12	24	4.5	9	6.3	4.5	4.5	9.4	6.7	4.5
		M33										
	7T	M36	16	32	7	14	9.8	7	7	14.7	10.5	7
	9T	M42	24	48	9	18	12.6	9	9	18.9	13.5	9
12T	M48	32	64	12	24	16.8	12	12	25	18	12	



型号		M
代码	规格	
TCF43	0.3T	8
	0.4T	10

TCF43 — 0.3T — M8



优惠价	
数量	1~9 10~
价格	100% 另行报价

交货期	
数量	7