


压板

圆头内槽型/双圆头型



代码	类型	材质		热处理	表面处理
		国标	相当		
ZFB40	圆头内槽型	45	S45C	淬火回火 硬度32~38HRC	发黑
ZFB45	双圆头型				

① 如对防锈有要求，请优先选用不锈钢材质或无电解镀镍产品。

圆头内槽型
ZFB40



双圆头型
ZFB45



型号			W	W ₁	H	M	L ₁	L ₂	L ₃	L ₄	R	夹紧力 (N)	容许紧固扭矩 (N·m)
代码	规格	L											
ZFB40	8	50	19	9	12	8	12	14	42	5	10	4000~7600	17
		63			16		15	27	55			3100~8300	
		80						34	72			3400~8400	
	10	63	25	11	12			18	53	5	10	6400~12200	34
		80			16	10	15	32	70			7400~17700	
		100			19			40	90			8800~18800	
	12	63	32	13			14	14	52	6	12	13700~21600	71
		80			16	12		25	69			10300~21000	
		100					20	40	89			10900~25800	
	16	125	38	17	19			50	114	6	12	12900~27500	80
		80			16	16	18	17	65			16600~26000	

型号			W	W ₁	H	L ₂	L ₄	R	夹紧力 (N)	容许紧固扭矩 (N·m)
代码	规格	L								
ZFB45	8	50	19	9	12	26	5	10	4000~7600	17
		63				39			3100~8300	
		80			16	50			3400~8400	
	10	63	25	11	12	33	5	10	6400~12200	34
		80			16	50			7400~17700	
		100			19	70			8800~18800	
	12	63	32	13		35	6	12	13700~21600	71
		80			16	40			10300~21000	
		100				60			10900~25800	
	16	125	38	17	19	85	6	12	12900~27500	80
		80							16600~26000	



型号			
代码	规格	L	W
ZFB40	8	50	19
	63		

ZFB40—8—L50



优惠价		
数量	1~9	10~
价格	100%	另行报价

