



单列角接触球轴承

◀ 不配对

品牌	轴承类型 代码	轴承精度	后置代码	轴承材质		接触角(°)
				国标	相当	
HRB	7	P6	未标注: 内圈引导树脂保持架 TA: 外圈引导树脂保持架	GCr15	SUJ2	C: 15° AC: 25°
		P5				
		P4				

❗ 出厂前未封入润滑脂, 请在使用前封入。



型号			d	D	B	r ₁ (min)	r ₂ (min)	额定载荷(KN)		极限转速(r/min)		作用点 a	安装尺寸			重量 (kg) 参考				
P6精度	P5精度	P4精度						Cr(动)	Cor(静)	脂润滑	油润滑		d _a (min)	D _a (max)	f _a (max)					
7000C-HRB	—	7000C/P4-HRB	10	26	8	0.3	0.15	5	2.21	56000	75000	6	12	24	0.3	0.02				
7000AC-HRB		—				7000CTA/P4-HRB	4.72	2.14	50000	67000	8									
—		—				—	0.3	0.1	5.38	2.49	67000	100000					6			
—	7200C/P5-HRB	—	12	30	9	0.6	0.15	5.49	2.64	48000	63000	7	15	25	0.6	0.03				
7001C-HRB	—	—				5.23		—	45000	60000	9									
7001AC-HRB	—	—				7.02		3.31	40000	53000	10									
—	7201AC/P5-HRB	—	15	32	10	0.6	0.3	7.28	3.42	45000	60000	8	27	0.6	0.04					
—	7201C/P5-HRB	—				—	—	—	—	—	—	—				—	—			
—	—	71902ACTA/P4-HRB				28	7	0.1	4.54	2.53	50000	75000				9	17	26	0.02	
7002AC-HRB	—	—	17	32	9	0.3	0.15	5.99	3.24	38000	50000	10	30	0.3						
7002C-HRB	—	—				6.25	3.39	43000	56000	8										
—	7002ACTA/P5-HRB	7002ACTA/P4-HRB				0.1	6.33	3.53	45000	67000	10									
7202AC-HRB	—	—	20	35	11	0.6	0.15	7.77	4.03	34000	45000	12	20	0.6	0.04					
7202C-HRB	—	—				8.03	4.11	38000	50000	9										
—	—	71903ACTA/P4-HRB				30	7	0.1	4.76	2.8	45000	67000				9				
7003AC-HRB	—	—	17	35	10	0.3	0.15	6.89	3.82	34000	45000	11	19	33	0.3	0.04				
7003C-HRB	7003C/P5-HRB	—				7.27	4	38000	50000	9										
7203C-HRB	—	—				40	12	0.6	0.3	10.9	5.87	34000					45000	10	22	35
—	—	71904ACTA/P4-HRB	37	9	0.3	0.15	5.72	4.37	38000	56000	11	0.3	0.04							
7004AC-HRB	—	—	9.95	5.74	28000	38000	13													
—	7004C/P5-HRB	7004C/P4-HRB	20	42	12	0.6	0.3	10.5	6.02	32000	43000			10	25	37	0.6	0.07		
—	7004ACTA/P5-HRB	—				10.3	6.26	34000	50000	13										
7204AC-HRB	—	—				14.7	8.19	28000	38000	12										
7204AC-HRB	—	—	25	47	14	1	0.6	14	7.84	24000	34000	15	26	41	1	0.1				
—	7204ACTA/P5-HRB	—				0.3	15	8.63	32000	48000	12									
—	—	71905ACTA/P4-HRB				42	9	0.3	0.15	7.83	5.37	26000					36000	11	27	40
7005AC-HRB	7005AC/P5-HRB	7005C/P4-HRB	25	47	12	0.6	0.3	11.7	7.44	26000	36000	11	30	42	0.6	0.08				
—	7005ACTA/P5-HRB	—				11.1	7.08	22000	32000	15										
7205AC-HRB	—	—				11.6	7.62	28000	43000	15										
7205C-HRB	—	—	30	52	15	1	0.6	15.9	9.8	20000	30000	14	31	46	0.13					
7205ACTA-HRB	—	—				16.6	10.3	24000	34000	13										
7305AC-HRB	—	—				0.3	16.8	10.6	26000	40000	17									
—	—	71906ACTA/P4-HRB	30	47	9	0.3	0.15	8.49	6.12	26000	40000	14	32	45	1	0.05				
7006AC-HRB	7006AC/P5-HRB	7006C/P4-HRB				14.3	9.84	19000	28000	17										
—	7006ACTA/P5-HRB	—				15.2	10.3	20000	30000	12										
7206AC-HRB	—	—	35	62	16	1	0.6	15.1	10.5	24000	38000	17	36	49	0.11					
7306AC-HRB	—	—						22.1	14.1	24000	19	56				0.2				
—	—	7007C/P4-HRB						30.9	19.4	17000	23000	21				37	65	1.1	0.35	
7007AC-HRB	—	7007AC/P4-HRB	40	62	14	1	0.3	19.1	13.7	18000	26000	14	41	56	1	0.15				
7207AC-HRB	—	7207AC/P4-HRB				18.2	13.1	17000	24000	19										
7008AC-HRB	—	—				29.1	19.2	16000	22000	21	42	65					1.1	0.28		
7008C-HRB	—	—	45	68	15	1	0.3	18.7	14.2	15000	20000	20	46	68	1	0.19				
7208AC-HRB	—	—				19.8	15	17000	24000	15										
—	7208CTA/P5-HRB	—				0.6	30.6	21.5	14000	29000	17	47					73	1.1	0.34	
—	7009AC/P5-HRB	—	45	75	16	1	0.6	33.7	24.2	18000	30000	17	51	69	1	0.24				
7309AC-HRB	—	—				23.1	18.3	14000	19000	22	54	91					1.5	0.86		
7010AC-HRB	—	—				60.3	42.1	16000	29000	29	54	91					1.5	0.86		
7210AC-HRB	—	—	50	80	16	1	0.3	23.7	19.7	12000	17000	23	56	74	0.26					
7011AC-HRB	7011AC/P5-HRB	—				40.8	30.3	11000	16000	27	57	0.46								
7012AC-HRB	—	—				30.3	25.7	11000	16000	26	62	83				1	0.38			
7012ACTA-HRB	—	—	60	95	18	1	0.6	34.7	29.5	9500	14000	27	67	88	0.4					
7212AC-HRB	—	—						35.6	31.1	13000	20000	31				69	101	1.5	0.79	
7015AC-HRB	—	—						55.8	42.9	9000	13000	32				82	108	0.63		
7016C-HRB	—	—	80	125	22	1.1	1.1	46.8	43.8	8500	12000	25	87	118	0.86					
7216AC-HRB	—	7216ACTA/P5-HRB						52.1	49.5	7500	10000	39				90	130	2	1.46	
—	—	—						8500	14000	7500	11000	36				92	123	1	0.89	
7017AC-HRB	—	—	90	130	22	1.1	0.6	55.1	52.9	7500	11000	36	99	131	1.5	1.17				
7018AC-HRB	—	—				60.8	59.4	7000	9500	39	92	131					1.5	1.17		
7218AC-HRB	—	—				112	95.1	6700	9000	44	100	150					2	2.2		
7019C-HRB	—	—	95	160	30	2	1.5	71.1	69.5	7500	10000	28	104	136	1.5	1.2				
—	—	—						—	—	—	—	—					—	—	—	—

❗ 1KgF=9.81N

单列角接触球轴承

◀ 不配对

型号			d	D	B	r1 (min)	r2 (min)	额定载荷(KN)		极限转速(r/min)		作用 点 a	安装尺寸			重量 (kg) 参考
P6精度	P5精度	P4精度						Cr(动)	Cor(静)	脂润滑	油润滑		da (min)	Da (max)	ra (max)	
7020AC-HRB	7020AC/P5-HRB		100	150	24	1.5	1	73.8	73.1	6700	9000	41				
—	7020CTA/P5-HRB						0.6	80.7	80.8	8500	14000	29	109	141	1.5	1.23
	7020ACTA/P5-HRB							77.1	76.7	7500	12000	41				
7220AC-HRB		—	120	180	34	2.1	1.1	139	121	6000	8000	50	112	168		3.21
7024C-HRB							1	106	111	6300	8500	34				
7024AC-HRB	—							102	105	5600	7500	49	130	170	2	2.07
7224AC-HRB								181	169	4800	6300	60		203		5.38

1Kg=9.81N



请按图示订货

型号
7000C-HRB



未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价



交货期
7

怡合达®
AUTOMATION EXPERT 自动化专家

怡合达®
AUTOMATION EXPERT 自动化专家