




圆皮带用滑轮

梯形槽 开口式夹紧固定

代码	类型	材质		表面处理
		国标	相当	
ENS71	开口式夹紧固定 梯形槽	45	S45C	发黑
ENS72		铝合金		喷细砂本色阳极氧化

① 3D模型仅供参考，具体尺寸请以参数表为准，注意选型。



① M=M3时， $d_1=\varnothing 3.3$
M=M4时， $d_1=\varnothing 4.3$

视角标准：第一视角

型号		皮带半径	d _{H7} 选择	D	D ₁	D ₂	h	W	L	T	T ₁	V	X	Y	a	M	适用皮带直径	
代码	A																	
ENS71 ENS72	20	1	4 5	16	22	18							5	4.2	2	M3	2	
	30		4 5 6 6.35 8	20	32	28	1	2.2	11	5	2.5		7	5	4			
	40				42	38					2.5							
	30	1.5	4 5 6 6.35 8	20	32	27			16				7	5	4	M3	3	
	40		4 5 6 6.35 8		42	37												
	45		4 5 6 6.35 8 10 11 12	25	47	42	1.5	3.3				4.5	9	6.2	5.2	M4		
	60				62	57			20									
	23				25	19												
	28	2	4 5 6 6.35 8	20	30	24			16				2.5	7	5	4	M3	4
	30				32	26												
	40				42	36	2	4.4										
	45			47	41													
	48		4 5 6 6.35 8 10 11 12	25	50	44			20				4.5	9	6.2	5.2	M4	
	60				62	56												
	80				82	76												
	28	2.5	4 5 6 6.35 8	20	30	23			16				2.5	7	5	4	M3	5
	40				42	35				10	5							
	48				50	43												
	50		4 5 6 6.35 8 10 11 12	25	52	45	2.5	5.5	20				4.5	9	6.2	5.2	M4	
	60				62	55												
	75				77	70												
	80				82	75												
	28	3	4 5 6 6.35 8	20	30	22			16				2.5	7	5	4	M3	6
	38		4 5 6 6.35		40	32							6.5	4.5	2.5			
	48				50	42												
	50				52	44												
58				60	52	3	6.6	20				4.5	9	6.2	5.2	M4		
60		4 5 6 6.35 8 10 11 12	25	62	54													
75				77	69													
95				97	89													
100				102	94													



型号	代码	A	皮带半径	dH7选择
ENS71	20	1	4 5	16
ENS72	30	1	4 5 6 6.35 8	20

ENS71—A20—1—d5



● 优惠价
数量 1~9 10~
价格 100% 另行报价



交货期
7