



公制螺纹/英制管螺纹/美制JIC螺纹

直接头

过板式过渡接头

公制螺纹-24°锥面密封


代码	类型	材质
WSD01	外螺纹	碳钢
WSD02		SUS304
WSD03		碳钢
WSD04		SUS304



视角标准：第一视角

公制螺纹-74°锥面密封

代码	类型	材质
WSD06	外螺纹	碳钢
WSD07		SUS304





视角标准：第一视角

型号	规格	适用管 外径D	M	A	B	S	压力 (Mpa)
轻系列 WSD01 WSD02	14	8	M14×1.5	8	27	19	31.5
	18	12	M18×1.5	10	29	24	
	22	15	M22×1.5	12	31	27	
	30	22	M30×2	16.5	34.5	36	16
	36	28	M36×2	18.5	35.5	41	
重系列 WSD03 WSD04	14	6	M14×1.5	12	29	19	63
	18	10	M18×1.5	14.5	29.5	24	
	22	14	M22×1.5	17	32	30	
	30	20	M30×2	17.5	33.5	41	40
	36	25	M36×2	20	35	46	

型号	规格	适用管 外径D	M	A	B	L	S
WSD06 WSD07	14	8	M14×1.5	17	40	65	17
	18	12	M18×1.5	18	43	69	24
	22	14	M22×1.5	19.5	44	73.5	27
	30	20	M30×1.5	23	53	87	34
	36	25	M36×2	25	56	94	41

公制螺纹-平面带O型圈密封

代码	类型	材质
WSD08	外螺纹	碳钢
WSD09		SUS304




视角标准：第一视角

型号	规格	M	A	B	L	S
WSD08 WSD09	14	M14×1.5	11	32.5	49.5	19
	18	M18×1.5	12	33	52	24
	22	M22×1.5	12	35.5	58	27
	30	M30×1.5	14	38	63	36
	36	M36×2	16	42	71	41

英制管螺纹-60°内锥面密封

代码	类型	材质
WSD10	外螺纹	碳钢
WSD11		SUS304




视角标准：第一视角

型号	规格	M	A	B	L	S
WSD10 WSD11	02	G1/8"×28	10	33	49	14
	04	G1/4"×19	12	35	53	19
	06	G3/8"×19	13.5	36	56.5	22
	08	G1/2"×14	16	39	65	27
	10	G5/8"×14	17.5	40	67.5	30
	12	G3/4"×14	18.5	42	71.5	32

美制JIC螺纹-74°外锥面密封

代码	类型	材质
WSD12	外螺纹	碳钢
WSD13		SUS304



视角标准：第一视角

型号	规格	M	A	B	L	S
WSD12 WSD13	04	7/16"×20	14	32.5	52.5	19
	05	1/2"×20	14	32.5	52.5	19
	06	9/16"×18	14.1	32.5	54.5	22
	08	3/4"×16	16.7	36.5	61.5	24
	10	7/8"×14	19.3	40	69.5	30
	12	1.1/16"×12	21.9	44.5	78.5	36

美制JIC螺纹

代码	规格	M
WSD12	04	7/16"×20
WSD13	05	1/2"×20



请按图示订货

WSD12-05



数量	1~19	20~
价格	100%	另行报价

未税价(元)



交货期	5
-----	---

液
压
管
件

K2