



角接触球轴承

◀ 单列
万能配对型

品牌	轴承类型 代码	轴承精度	后置代码	轴承材质		接触角
				国标	相当	
C&U	7	P4	未标注：尼龙保持架 DU：万能配对型	GCr15	SUJ2	B:40° C:15° AC:25°



■ 安装图



C&U



视角标准：第一视角



型号

7002C/P4DU-C&U

请按图示订货



● 优惠价

数量 1~9 10~
价格 100% 另行报价

未税价(元)



交货期

7

型号	主要尺寸(mm)					基本额定载荷(KN)		极限转速(rpm)		安装相关尺寸(mm)			重量(g) 参考
	d	D	B	r(min)	r ₁ (min)	Cr(动)	Cor(静)	脂润滑	油润滑	d _a (min)	D _a (max)	R _a (max)	
7000AC/P4DU-C&U	10	26	8	0.3	0.15	5.14	2.41	36000	50000	12.5	23.5	0.3	23
7001AC/P4DU-C&U	12	28				5.58	2.79	32000	45000	14.5	25.5		25
7002C/P4DU-C&U	15	32				9	6.24			3.39	17.5		29.5
7002AC/P4DU-C&U		35	11	0.6	0.3	5.97	3.24	27000	38000	20	30	0.6	46
7202AC/P4DU-C&U						7.39	3.9	26000	37000				47
7202B/P4DU-C&U	7.93					4.31	17000	24000	45				
7003C/P4DU-C&U	17	10	0.3	0.15	6.61	3.81	28000	40000	19.5	32.5	0.3	45	
7003AC/P4DU-C&U					6.3	3.65	25000	35000				46	
7203AC/P4DU-C&U					40	12	0.6	0.3				10.5	5.61
7203B/P4DU-C&U	9.03	5.54	16000	21000					66				
7004C/P4DU-C&U	20	42	14	1					0.6	11.1	6.56	24000	34000
7004AC/P4DU-C&U					10.6	6.27	21000	29000		80			
7204C/P4DU-C&U					14.5	8.05	23000	32000		98			
7204B/P4DU-C&U	47	12	0.6	0.3	13.3	7.63	13000	18000	26	41	0.6	102	
7005C/P4DU-C&U					11.7	7.44	21000	29000				91	
7005AC/P4DU-C&U					11.1	7.08	18000	25000				93	
7205C/P4DU-C&U	25	52	15	1	16.6	10.2	20000	28000	31	46	0.6	122	
7205AC/P4DU-C&U					15.9	9.77	17000	24000				125	
7205B/P4DU-C&U					14.8	9.39	11000	16000				129	
7305AC/P4DU-C&U	62	17	1.1		25.2	14.1	14000	20000	32	55		230	
7305B/P4DU-C&U					24.4		11000	15000				234	
7006C/P4DU-C&U					30		55	13				1	15.1
7206C/P4DU-C&U	23	14.7	17000	23000		190							
7206AC/P4DU-C&U	22.1	14.1	14000	20000		193							
7206B/P4DU-C&U	62	14	1	0.6	20.5	13.5	9400	13000	41	56	1	197	
7007C/P4DU-C&U					19.1	13.7	15000	22000				180	
7007AC/P4DU-C&U					18.2	11.1	13000	19000				281	
7207AC/P4DU-C&U	35	72	17	1.1	29.1	19.1	12000	17000	42	65		287	
7207B/P4DU-C&U					27.1	18.4	8100	11000				222	
7008AC/P4DU-C&U					19.5	16.1	12000	17000				355	
7208AC/P4DU-C&U	40	80	18	1.1	33.6	24.7	11000	15000	47	73		375	
7208B/P4DU-C&U					32.1	23	8300	11000				270	
7009C/P4DU-C&U					31.4	19.3	12000	17500				282	
7009AC/P4DU-C&U	75	16	1		23.1	18.3	11000	15000	51	69		404	
7209AC/P4DU-C&U					36.4	26.6	10000	14000				410	
7209B/P4DU-C&U					36	26.3	7400	9900				837	
7309AC/P4DU-C&U	100	25	1.5	1	68.4	44	8600	12000	53.5	91.5	1.5	854	
7309B/P4DU-C&U					58.3	40.1	6600	8900				457	
7210AC/P4DU-C&U					42.7	32.5	9400	13000				466	
7210B/P4DU-C&U	90	20	1.1	0.6	37.4	28.6	6700	9000	57	83	1	210	
7011C/P4DU-C&U					36.4	29.1	10000	14000				214	
7011AC/P4DU-C&U					34.5	27.6	8800	12000				600	
7211AC/P4DU-C&U	55	100	21	1.5	1	50.5	38.2	8500	12000	63.5	91.5	1.5	612
7211B/P4DU-C&U						46.3	36.1	6100	8200				765
7212AC/P4DU-C&U						58.2	46	7800	11000				780
7212B/P4DU-C&U	60	110	22	1.1	0.6	56.1	44.4	5700	7600	68.5	101.5	1	495
7013C/P4DU-C&U						41.5	37.2	9000	13000				509
7013AC/P4DU-C&U						39.3	35.4	7800	11000				945
7213C/P4DU-C&U	65	120	23	1.5	1	60.7	49.3	8400	12000	73.5	111.5	1.5	962
7213AC/P4DU-C&U						57.7	47.1	7100	9900				981
7213B/P4DU-C&U						63.6	52.6	5200	7000				690
7014C/P4DU-C&U	70	110	20	1.1	0.6	49.9	45.5	8300	11500	77	103	1	705
7014AC/P4DU-C&U						47.3	43.3	7100	10000				1090
7214AC/P4DU-C&U						72.5	60.6	6800	9400				1110
7214B/P4DU-C&U	125	24	1.5	1	69.1	57.8	4900	6500	78.5	116.5	1.5	1170	
7015AC/P4DU-C&U					68.6	58.3	4500	6000				1190	
7215AC/P4DU-C&U					72.2	61.5	6400	9000				980	
7215B/P4DU-C&U	130	25	1.5	1	68.6	58.3	4500	6000	83.5	121.5	1.5	1190	
7016C/P4DU-C&U					58.7	55.2	7300	10000				980	
7016AC/P4DU-C&U					55.5	52.5	6300	8800				994	
7216AC/P4DU-C&U	80	140	26	2	1	88.7	78	6000	8300	90	130	2	1390
7216B/P4DU-C&U						80.5	69.2	4300	5700				1420
7017AC/P4DU-C&U						88.7	78	6000	8300				1040
7217AC/P4DU-C&U	85	130	22	1.1	0.6	87.9	75.3	5600	7800	92	123	1	1780
7217B/P4DU-C&U						79.7	70.2	4000	5300				1820
7018AC/P4DU-C&U						63	62.4	5600	7850				1350
7218AC/P4DU-C&U	90	140	24	1.5	1	116.9	99.9	5300	7300	98.5	131.5	1.5	2180
7218B/P4DU-C&U						106.6	93.7	3800	5000				2220
7020AC/P4DU-C&U						71.2	73.1	5100	7200				1470