


方垫圈/方斜垫圈/接地垫圈/法式垫圈

方垫圈

代码	类型	材质	表面处理	适用标准
TBY60	方垫圈	SUS304	—	DIN 436-1990






视角标准：第一视角

型号	公称直径	d	D	t
TBY60	6	6.9	20	2.4
	8	9.3	25	3
	10	11	30	3
	12	13.5	40	4
	16	17.5	50	5
	20	22	60	5
	24	26	80	6
	27	30	90	6

方斜垫圈(GB/T 853-1988)

代码	类型	材质	表面处理	适用标准
TBY63	方斜垫圈	SUS304	—	GB/T 853-1988




视角标准：第一视角

型号	公称直径	d	D	t	h
TBY63	6	6.6	16		3.6
	8	9	18		3.8
	10	11	22	2	4.2
	12	13.5	28		4.8
	16	17.5	35		5.4
	18	20			
	20	22	40		7
	22	24			
	24	26			
	27	30	50	3	8
	30	33	60		9
	36	39	70		10

方斜垫圈(DIN 434)

代码	类型	材质	表面处理	适用标准
TBY61	方斜垫圈	Q235	镀蓝白锌	DIN 434




视角标准：第一视角

型号	公称直径	d	W	L	h
TBY61	8	9	9.36		
	10	11	11.43	21.35	22.65
	12	13.5	13.93	29.35	30.65
	16	17.5	17.93	35.2	36.8
	20	22	22.52	37.5	42.5
	24	26	26.52	53	59
					55.05
					56.95
					7.3
					9.7

接地垫圈

代码	类型	材质	表面处理	适用标准
TBY71	接地垫圈	65Mn	达克罗	SN 70093
TBY72			镀蓝白锌	
TBY73			镀彩锌	
TBY74		SUS304	—	





视角标准：第一视角

型号	公称直径	d	D	h	m	n	t
(65Mn)	3	3.1	6.2	0.95	0.8		0.6
	3.5	3.6	7.2	1.1	1	0.2	0.7
	4	4.1	8.2	1.15	1.2		0.8
	5	5.4	10.2	1.5			1
	6	6.1	12.2	1.8			1.2
	8	8.2	16.2	2.4	2		1.4
	10	10.2	20.25	2.6		0.4	1.6
(SUS304)	12	12.4	24.25				1.6
	16	16.4	32.3	3.96			2.5
	20	20.5	40.3	4.65	4.5		3

法式垫圈

代码	类型	材质	表面处理	适用标准
TBY81	法式垫圈	65Mn	达克罗	NFE 25511
TBY82			镀蓝白锌	
TBY84			—	
		SUS304	—	



视角标准：第一视角

型号	公称直径	D	d	t	h
(65Mn)	3	6		0.5	0.9
		8	3.35		1
	10			0.6	1.2
		8		0.8	1.2
	4	10	4.4	0.9	1.4
		14		1	1.8
	10			1	1.5
	5	12	5.4	1.1	1.8
		16		1.2	2.1
		12		1.2	1.85
	6	14	6.4	1.3	2.1
		18		1.4	2.5
(SUS304)	16			1.4	2.2
	8	18	8.58	2.35	2.35
		22		2.7	2.7
	10	20		1.6	2.6
		22	10.56		2.75
		27			3.1
		24		1.8	2.9
	12	27	12.83		3.1
		32		2	3.6
	14	30	14.83	2.4	3.7
	16	32	16.83	2.8	4.1
	20	40	21.02	3.2	4.9

方斜垫圈

代码	型号	公称直径
TBY61	10	12

法式垫圈

代码	型号	公称直径	D
TBY81	3	6	8



请按图示订货

TBY61—10

TBY81—3—D6



未税价(元)

优惠价

数量	1~99	100~
价格	100% 另行报价	100% 另行报价

TBY60/61/63



未税价(元)

优惠价

数量	1~999	1000~
价格	100% 另行报价	100% 另行报价

其余



交货期

7