



代码	类型	材质		允许位移量	弹簧常数公差
		国标	相当		
Y-YUL	外径基准不锈钢型	标准型	0Cr18Ni9 SUS304-WPB	L×40%	±10%



- ① 压紧长度为参考值，制作时会有少许差异。
 ② 使用次数：100万次。
 ③ 带()的L规格两端均未进行磨削加工。
 ④ 此系列为外径基准型弹簧，以保证外径公差进行生产，外径为负公差，适合配孔使用，内径仅做参考(按负公差)，选型时请注意。



RoHS



视角标准：第一视角

代码	型号		d	压紧长度	Fmax	允许负载 Nmax	弹簧常数 N/mm
	D	L					
2	0 -0.5	(5) ±0.7	0.2	1.65	2	0.98	0.49
		(10) ±0.7	0.26	5.07	4	1.96	
		(15) ±0.5	0.3	9.9	6	2.94	
		(20) ±0.6	0.32	14.1	8	3.92	
		(25) ±0.7	0.35	14.1	10	4.9	
3	0 -0.5	(5) ±0.7	0.3	2	2	2	1.00
		(10) ±0.7	0.35	3.7	4	3.9	
		(15) ±0.5	0.4	6.6	6	5.9	
		(20) ±0.6	0.4	6.6	8	7.8	
		(25) ±0.7	0.45	11.7	10	9.8	
4	0 -0.4	(5) ±0.7	0.35	2.1	2	2	1.00
		(10) ±0.7	0.45	5.3	4	3.9	
		(15) ±0.5	0.5	8	6	5.9	
		(20) ±0.6	0.55	13.75	8	7.8	
		(25) ±0.7	0.55	12.7	10	9.8	
5	0 -0.5	(5) ±0.7	0.4	2.2	2	2	1.00
		(10) ±0.7	0.5	4.75	4	3.9	
		(15) ±0.5	0.55	6.88	6	5.9	
		(20) ±0.6	0.65	29.9	8	7.8	
		(25) ±0.7	0.65	14.95	10	9.8	
6	0 -0.4	(5) ±0.7	0.45	2.3	2	2	1.00
		(10) ±0.7	0.55	4.4	4	3.9	
		(15) ±0.5	0.65	8.5	6	5.9	
		(20) ±0.6	0.7	12.6	8	7.8	
		(25) ±0.7	0.75	23.41	10	9.8	
7	0 -0.5	(5) ±0.7	0.45	2.3	2	2	1.00
		(10) ±0.7	0.55	4.4	4	3.9	
		(15) ±0.5	0.65	8.5	6	5.9	
		(20) ±0.6	0.7	12.6	8	7.8	
		(25) ±0.7	0.75	23.41	10	9.8	
8	0 -0.4	(5) ±0.7	0.45	2.3	2	2	1.00
		(10) ±0.7	0.55	4.4	4	3.9	
		(15) ±0.5	0.65	8.5	6	5.9	
		(20) ±0.6	0.7	12.6	8	7.8	
		(25) ±0.7	0.75	23.41	10	9.8	

代码	型号		d	压紧长度	Fmax	允许负载 Nmax	弹簧常数 N/mm
	D	L					
10	0 -0.5	10 ±0.7	0.75	4.7	4	3.9	0.98
		15 ±0.7	0.8	6.2	6	5.9	
		20 ±0.75	0.9	9.5	8	7.8	
		25 ±0.9	1.0	15.5	10	9.8	
		30 ±1.05	1.1	23.7	12	11.8	
12	0 -0.6	35 ±1.2	1.2	21.6	14	13.7	0.98
		40 ±1.35	1.3	32.5	16	15.7	
		45 ±1.5	1.4	46.2	18	17.7	
		50 ±1.8	1.5	58	20	19.6	
		60 ±2.1	1.6	77	24	23.5	
13	0 -0.6	70 ±2.4	1.7	12.8	28	25.5	2.94
		80 ±2.6	1.8	15.3	32	31.4	
		15 ±0.7	1.1	12.1	14	13.7	
		20 ±0.75	1.2	16.8	16	15.7	
		25 ±0.9	1.3	21.6	18	17.7	
16	0 -0.6	30 ±0.9	1.0	8.25	8	7.8	0.98
		35 ±1.05	1.1	14.85	10	9.8	
		40 ±1.2	1.2	21.6	12	11.8	
		45 ±1.35	1.3	32.5	14	13.7	
		50 ±1.5	1.4	46.2	16	15.7	
20	0 -0.74	60 ±1.8	1.5	58	20	19.6	2.94
		70 ±2.1	1.6	77	24	23.5	
		80 ±2.4	1.7	12.8	28	25.5	
		15 ±0.7	1.1	12.1	14	13.7	
		20 ±0.75	1.2	16.8	16	15.7	

Y-YUL

- ① 允许位移量Fmax：表示弹簧允许压缩的最大长度，超出此压缩量使用弹簧会缩短。
 ② 允许负载Nmax：表示压缩Fmax的负载，单位N。
 ③ 弹簧常数N/mm=(Nmax)/(Fmax)。



型号	
代码	D
Y-YUL	(3)
	10
	15

Y-YUL—D3—L5



优惠价	
数量	1~9 10~
价格	100% 另行报价

弹 簧 震 零 件