

代码	类型	主体			外螺纹			轴承
		材质		表面处理	材质		表面处理	材质
		国标	相当		国标	相当		
Y-EKC01	标准型	45	S45C	发黑	—	—	—	钢
Y-EKC02		LD30	A6061	喷细砂无电解镀镍	—	—	—	—
Y-EKC03		0Cr18Ni9	SUS304	喷细砂本色阳极氧化	—	—	—	—
Y-EKC04	窄幅型	45	S45C	发黑	45	S45C	发黑	不锈钢
Y-EKC06		LD30	A6061	喷细砂无电解镀镍	—	—	—	—
Y-EKC07		LD30	A6061	喷细砂本色阳极氧化	—	—	—	—
Y-EKC08	外螺纹型	0Cr18Ni9	SUS304	—	0Cr18Ni9	SUS304	—	—
Y-EKC09		0Cr18Ni9	SUS304	—	—	—	—	不锈钢




RoHS




轴承精度: GB/T 307.1 0 级
相当于 : JIS B 1514 0 级

- ① 如对防锈有要求, 请优先选用不锈钢材质或喷细砂无电解镀镍产品。
② 3D模型仅供参考, 具体尺寸请以参数表为准, 注意选型。

标准型
Y-EKC01/02/03/04



外螺纹型
Y-EKC06/07/08/09



6.3/



视角标准: 第一视角

型号		R	F	d	P	D	D ₁	B	标准轴承	M	G	F ₁	适用 圆皮带直径
代码	A												
标准型 Y-EKC01 Y-EKC02 Y-EKC03 Y-EKC04	(15)	1.1		4	11	17	13	4	694ZZ				2
	(20)				13	21	18		624ZZ				
	(30)			5	16	32	28		625ZZ				
	(20)	1.6	—	4	13	22	17	5	624ZZ	—	—	—	3
	(23)				16	25	20		625ZZ				
	(30)			5	16	32	27						
	(18)	2.1	8	6	11	20	14	6	685ZZ				4
	23				15	25	19		696ZZ				
	28					30	24		626ZZ	M6	3	1.0	
	30		12	8	19	32	26	8	698ZZ		4		5
	40			12	24	42	36		6901ZZ	M10	6	1.5	
	48					50	44		626ZZ		3		
	28	2.6	8	6		30	23	10	698ZZ	M6	4	1.0	6
	40				19	42	35						
	48			8		50	43						
外螺纹型 Y-EKC06 Y-EKC07 Y-EKC08 Y-EKC09	50	3.1	12	12		52	45	12	6901ZZ	M10	6	1.5	8
	38				24	40	32		628ZZ	M8	4	1.0	
	48			8		50	42						
	50	4.1		12		52	44	10	6001ZZ				10
	60				28	62	54		6904ZZ				
	100			20	37	102	94						
	50	5.1	12	12		52	42	12	6201ZZ	M10	6	1.5	10
	60				32	62	50						
	60					62	52						
	80			20	42	82	70		6004ZZ				
	(140)		—			142	130						

① 带()的尺寸不适用于外螺纹型。



请按图示订货

型号		R
代码	A	
Y-EKC01	20	1.1
Y-EKC02	30	
Y-EKC01—A20—R1.1		



未税价(元)

优惠价	
数量	1~9 10~
价格	100% 另行报价