




侧开口型

代码	类型	材质		表面处理	附件
		国标	相当		
GDC01	侧开口型	45	S45C	发黑	1个内六角圆柱头螺钉
GDC02		0Cr18Ni9	SUS304	喷细砂无电解镀镍	1个内六角圆柱头螺钉(不锈钢)
GDC06		LF2	A5052	喷细砂本色阳极氧化	
GDC08					



- ① D30~40有2个附件内六角圆柱头螺钉。
② 开口型, 安装孔D的公差H7为开口加工前的公差, 开口加工后由于有内部应力释放, 公差有可能增至H8左右, 不影响客户使用。
③ 如对防锈有要求, 请优先选用不锈钢材质、铝合金材质或喷细砂无电解镀镍产品。




型号		H										L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N	
代码	D _{H7}																									
GDC01 GDC02 GDC06 GDC08	8	(10)	(15)	(20)	25	30	40						H+10	15	7.5				11							
	10	(10)	(15)	(20)	25	30	40	50	60				H+11													
	12	(10)	(15)	(20)	25	30	40	50	60			62	H+12	18	9	5.8	37.8	50	6.6	12	M6深12	6.6	11	6.5		
	13		(15)	(20)	25	30	40	50	60																1.2~2.3	
	15		(15)	(20)	25	30	40	50	60				H+14	20	10											
	16		(15)	(20)	25	30	40	50	60																	
	20			(20)	25	30	40	50	60	80			85	H+18	25	12.5	7.8	52.8	70	9	18					
	25			(20)	25	30	40	50	60	80					30	15										
	30				(25)	30	40	50	60	80	102		H+21	35	17.5		61.8	82	6.6	22	M8深25	9	14	9		
	35				(25)	30	40	50	60	80	106		H+24			9.8	65.8	86		24					1.2~3.5	
40					40	50	60	80			111	H+27	40	20		69.8	91	9	27							





- ① 带()的H尺寸对应的螺孔M底孔贯通。 ② 可能出现螺孔M底孔贯穿的情况。

分离型

代码	类型	材质		表面处理	附件
		国标	相当		
GDF01	分离型	45	S45C	发黑	2个内六角圆柱头螺钉
GDF02		0Cr18Ni9	SUS304	喷细砂无电解镀镍	2个内六角圆柱头螺钉(不锈钢)
GDF06		LF2	A5052	喷细砂本色阳极氧化	
GDF08					



- ① D30~50有4个附件内六角圆柱头螺钉。
② 如对防锈有要求, 请优先选用不锈钢材质、铝合金材质或喷细砂无电解镀镍产品。



型号		H										L	H ₁	T	T ₁	S	W	L ₁	d	E	M	d ₂	d ₁	h	N	
代码	D																									
GDF01 GDF02 GDF06 GDF08	8	(10)	(15)	(20)	25	30	40					62	H+10	15	7.5					23	M6深12	6.6	11	6.5	1.2~2.3	
	10	(10)	(15)	(20)	25	30	40	50	60	H+11																
	12	(10)	(15)	(20)	25	30	40	50	60	H+12	18		9	5.8	37.8	50	6.6	24								
	13	(15)	(20)	25	30	40	50	60																		
	15	(15)	(20)	25	30	40	50	60																		
	16	(15)	(20)	25	30	40	50	60																		
	20	(20)	25	30	40	50	60	80	85	H+18	25	12.5	7.8	52.8	70	9	36									
	25	(20)	(25)	30	40	50	60	80		H+30	30	15														
	30	(25)	30	40	50	60	80																			
	35	(25)	30	40	50	60	80	110																		
40				30	40	50	60	80	116		40	20		75.8	96	9	56									
50						40	50	60	80	154	H+40	50	25	14.8	101.8	128	11	76	M12深25	14	20	13				

- ① 带()的H尺寸对应的螺孔M底孔贯通。 ② 可能出现螺孔M底孔贯穿的情况。

分离型

型号	D	H
GDF01	8	10 15 20
GDF02	10	10 15 20

GDF02 — D8 — H15



优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

交货期	5
-----	---



请按图示订货

未税价(元)