


螺钉夹紧型 单膜片/双膜片



标准型膜片式联轴器

代码	类型	材质		表面处理	附件
		主体	膜片		
DEG02	螺钉夹紧型	铝合金	单膜片	不锈钢	本色阳极氧化
DEG12			双膜片		

单膜片
DEG02




双膜片
DEG12



特点

- 高灵敏度、高扭矩刚性；
- 顺时针与逆时针回转特性完全相同；
- 零回转间隙；
- 不锈钢膜片补偿角向和轴向偏差；
- 适用于伺服电机、步进电机连接。



型号		d-e																																										
代码	D																																											
单膜片 DEG02 双膜片 DEG12	19	d	3			4			5			6			6.35		7		8																									
		e	3 4 5 6 6.35 7 8			4 5 6 6.35 7 8			5 6 6.35 7 8			6 6.35 7 8			6.35 7 8		7 8		8																									
	26	d	4			5			6			6.35			7			8			9		9.525		10																			
		e	4 5 6 6.35 7 8 9 9.525 10			5 6 6.35 7 8 9 9.525 10			6 6.35 7 8 9 9.525 10			6.35 7 8 9 9.525 10			7 8 9 9.525 10			8 9 9.525 10			9 9.525 10		9.525 10		10																			
	29	d	5			6			6.35			7			8			9			9.525		10		11		12		12.7		13		14											
		e	5 6 6.35 7 8 9 9.525 10 11 12 12.7 13 14			6 6.35 7 8 9 9.525 10 11 12 12.7 13 14			6.35 7 8 9 9.525 10 11 12 12.7 13 14			7 8 9 9.525 10 11 12 12.7 13 14			8 9 9.525 10 11 12 12.7 13 14			9 9.525 10 11 12 12.7 13 14			9.525 10 11 12 12.7 13 14		10 11 11 12 12.7 13 14		11 12 12 12.7 13 14		12 12.7 12.7 13 14		12.7 12.7 13 14		13 13 14		14 14											
	32	d	5			6			6.35			7			8			9			9.525		10		11		12		12.7		13		14											
		e	5 6 6.35 7 8 9 9.525 10 11 12 12.7 13 14			6 6.35 7 8 9 9.525 10 11 12 12.7 13 14			6.35 7 8 9 9.525 10 11 12 12.7 13 14			7 8 9 9.525 10 11 12 12.7 13 14			8 9 9.525 10 11 12 12.7 13 14			9 9.525 10 11 12 12.7 13 14			9.525 10 11 12 12.7 13 14		10 11 11 12 12.7 13 14		11 12 12 12.7 13 14		12 12.7 12.7 13 14		12.7 12.7 13 14		13 13 14		14 14											
	34	d	6			6.35			7			8			9			9.525			10		11		12		12.7		13		14													
		e	6 6.35 7 8 9 9.525 10 11 12 12.7 13 14			6.35 7 8 9 9.525 10 11 12 12.7 13 14			7 8 9 9.525 10 11 12 12.7 13 14			8 9 9.525 10 11 12 12.7 13 14			9 9.525 10 11 12 12.7 13 14			9.525 10 11 12 12.7 13 14		10 11 11 12 12.7 13 14		11 12 12 12.7 13 14		12 12.7 13 14		12.7 13 14		13 14 14		14														
	39	d	8			9			9.525			10			11			12			12.7			13			14			15			16											
		e	8 9 9.525 10 11 12 12.7 13 14 15 16			9 9.525 10 11 12 12.7 13 14 15 16			9.525 10 11 12 12.7 13 14 15 16			10 11 12 12.7 13 14 15 16			11 12 12.7 13 14 15 16			12 12.7 13 14 15 16			12.7 13 14 15 16			13 14 15 16			14 15 16			15 16 16														
	44	d	9			9.525			10			11			12			12.7			13			14			15			16			17			18			19			20		
		e	9 9.525 10 11 12 12.7 13 14 15 16 17 18 19 20			9.525 10 11 12 12.7 13 14 15 16 16 17 18 19 20			10 11 12 12.7 13 14 15 16 17 18 19 20			11 12 12.7 13 14 15 16 17 18 19 20			12 12.7 13 14 15 16 17 18 19 20			12.7 13 14 15 16 17 18 19 20			13 14 15 16 17 18 19 20			14 15 16 17 18 19 20			15 16 17 18 19 20			16 17 18 19 20			17 18 18 19 19 20			18 19 19 20 20								

型号																	容许安装偏差			重量*
代码	D	L	L ₁	L ₂	d ₁	d ₂	W	A	F	M	锁紧扭矩 (N·m)	额定扭矩 (N·m)	最高转速* (r/min)	惯性力矩* (kg·m ²)	静态扭 转刚度 (N·m/rad)	径向 (mm)	角向 (°)	轴向 (mm)	(g)	
单膜片 DEG02	19	19.3	9.0		8.5		1.3	6.0	3.0	M2.5	1.0~1.1	1.0		6.33×10 ⁻⁷	1400				±0.1	12
	26	25.4	11.4		11.5		2.6	9.0	4.0	M3	1.5~1.9	2.0		2.61×10 ⁻⁶	3700				±0.15	27
	29	26.4	11.9		14.5		2.6	10.5	4.0	M3	1.5~1.9	3.0		4.10×10 ⁻⁶	3900				±0.15	43
	32	28.0	12.25	—	15.1	—	3.5	11.0	4.0	M3	3.4~4.1	4.0	10000	7.10×10 ⁻⁶	5700	0.02	1		±0.2	46
	34	32.5	14.5		16.6		3.5	12.0	4.75	M4	3.4~4.1	5.0		9.62×10 ⁻⁶	8100				±0.2	58
	39	34.3	15.0		17.0		4.3	13.0	5.0	M4	3.4~4.1	10.0		1.68×10 ⁻⁵	18000				±0.25	82
双膜片 DEG12	44	34.6	15.0		21.0		4.6	16.0	5.0	M4	3.4~4.1	12.0		2.48×10 ⁻⁵	20000				±0.3	102
	19	26.6	9.0	6.0	8.5	8.3	1.3	6.0	3.0	M2.5	1.0~1.1	1.0		9.10×10 ⁻⁷	700	0.10			±0.2	17
	26	35.0	11.4	7.0	11.5	12	2.6	9.0	4.0	M3	1.5~1.9	2.0		3.61×10 ⁻⁶	1850	0.15			±0.3	37
	29	35.7	11.9	6.7	14.5	14.5	2.6	10.5	4.0	M3	1.5~1.9	3.0		4.10×10 ⁻⁶	2200	0.15			±0.3	43
	32	41.0	12.25	9.5	15.1	14	3.5	11.0	4.0	M3	3.4~4.1	4.0	10000	7.10×10 ⁻⁶	2850	0.18	2		±0.4	62
	34	44.8	14.5	8.8	16.6	16	3.5	12.0	4.75	M4	3.4~4.1	5.0		1.33×10 ⁻⁵	4050	0.18			±0.4	80
	39	48.6	15.0	10.0	17.0	17	4.3	13.0	5.0	M4	3.4~4.1	10.0		2.58×10 ⁻⁵	9000	0.24			±0.5	118
	44	49.6	15.0	10.4	21.0	22	4.6	16.0	5.0	M4	3.4~4.1	12.0		4.23×10 ⁻⁵	10000	0.24			±0.6	150

① *1根据孔径尺寸不同，轴的可传递摩擦力矩有时会有时联轴器额定扭矩小。

② *2最大孔径时的值。



请按照图示订货

型号	代码	D	d-e
DEG02	19	d	3
DEG12	19	e	3 4 5 6

DEG02—D19—d3—e6

可选加工

型号	代码	D	d-e	可选加工代码
DEG02	19	d	3	DC
DEG12	19	e	3 4 5 6	DC


DEG02—D19—d3—e6—DD



可选加工

代码	技术说明
DC	d孔侧键槽加工 选型方法 DC ① 当d孔径≥6mm时才能选择键槽加工。
DD	e孔侧键槽加工 选型方法 DD ① 当e孔径≥6mm时才能选择键槽加工。

键槽尺寸表



轴径尺寸		键槽尺寸		
Ød, Øe (mm)	宽度b (mm)	深度t (mm)	公差	公差
Ø6~Ø7.99	2	1		
Ø8~Ø10	3	1.4	±0.0125	
Ø10.01~Ø12	4	1.8		
Ø12.01~Ø17	5	2.3	±0.015	
Ø17.01~Ø22	6	2.8		



优惠价

数量	1~10	11~
价格	100%	另行报价



交货期

7

未税价(元)

+0.1
0