


代码	类型	螺纹	材质		表面处理	适用标准	强度等级
			国标	相当			
TBK50			35	S35C	镀镍		
TBK51			45	S45C	发黑		
TBK52					镀锌	DIN 934-1987	
TBK54			0Cr17Ni12Mo2	SUS316			
TBK55			0Cr18Ni9	SUS304			
TBK56	标准型	粗牙	黄铜			GB/T 6170-2015	
TBK57						DIN 934-1987	
TBK64			35K(碳钢)		发黑	GB/T 6170-2015	
TBK63					镀蓝白锌	DIN 934-1987	10级
TBK66			10B21		发黑		
TBK68					镀蓝白锌	GB/T 6170-2015	12级
TBK69			35CrMo		发黑		



□ DIN 934-1987

型号	代码	M	P	m		S		e
				(max)	(min)	(max)	(min)	
(S35C)	TBK50	2*	0.4	1.6	1.35	4	3.82	4.32
		2.5*	0.45	2	1.75	5	4.82	5.45
		3	0.5	2.4	2.15	5.5	5.32	6.01
		4	0.7	3.2	2.9	7	6.78	7.66
		5	0.8	4	3.7	8	7.78	8.79
(S45C)	TBK51	6	1	5	4.7	10	9.78	11.05
	TBK52	8	1.25	6.5	6.14	13	12.73	14.38
		10	1.5	8	7.64	17	16.73	18.9
		12	1.75	10	9.64	19	18.67	21.1
(SUS304)	TBK55	16	2	13	12.3	24	23.67	26.75
		20	2.5	16	14.9	30	29.16	32.95
		24	3	19	17.7	36	35	39.55
		3	0.5	2.4	2.15	5.5	5.32	6.01
		4	0.7	3.2	2.9	7	6.78	7.66
(SUS316)	TBK54	5	0.8	4	3.7	8	7.78	8.79
		6	1	5	4.7	10	9.78	11.05
		8	1.25	6.5	6.14	13	12.73	14.38
		10	1.5	8	7.64	17	16.73	18.9
		12	1.75	10	9.64	19	18.67	21.1
(黄铜)	TBK67	2	0.4	1.6	1.35	4	3.82	4.32
		2.5	0.45	2	1.75	5	4.82	5.45
		3	0.5	2.4	2.15	5.5	5.32	6.01
		4	0.7	3.2	2.9	7	6.78	7.66
		5	0.8	4	3.7	8	7.78	8.79
(35K(碳钢))	TBK63	6	1	5	4.7	10	9.78	11.05
		8	1.25	6.5	6.14	13	12.73	14.38
		10	1.5	8	7.64	17	16.73	18.9
		12	1.75	10	9.64	19	18.67	21.1
		16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95	

□ GB/T 6170-2015

型号	代码	M	P	m		S		e	
				(max)	(min)	(max)	(min)		
(SUS304)	TBK56	(2)*	0.4	1.6	1.35	4	3.82	4.32	
		4*	0.7	3.2	2.9	7	6.78	7.66	
		5*	0.8	4.7	4.4	8	7.78	8.79	
		6*	1	5.2	4.9	10	9.78	11.05	
		8*	1.25	6.8	6.44	13	12.73	14.38	
		10*	1.5	8.4	8.04	16	15.73	17.77	
		12*	1.75	10.8	10.37	18	17.73	20.03	
		14*	2	12.8	12.1	21	20.67	23.36	
		16*	2	14.8	14.1	24	23.67	26.75	
		18*	2.5	15.8	15.1	27	26.16	29.56	
		20*	2.5	18	16.9	30	29.16	32.95	
		22	3	19.4	18.1	34	33	37.29	
(35K(碳钢)·发黑)	TBK57	24*	21.5	20.2	36	35	39.55		
		27*	23.8	22.5	41	40	45.2		
		30*	3.5	25.6	24.3	46	45	50.85	
		33	3.5	28.7	27.4	50	49	55.37	
		36*	4	31	29.4	55	53.8	60.79	
		(42)*	4.5	34	32.4	65	63.1	71.3	
	(35K(碳钢)·镀蓝白锌)	TBK64	3	0.5	2.15	2.4	5.32	5.5	6.01
			4	0.7	2.9	3.2	6.78	7	7.65
			6	1	4.9	5.2	9.78	10	11.05
			8	1.25	6.44	6.8	12.73	13	14.38
			10	1.5	8.04	8.4	15.73	16	17.77
	(10B21·发黑)	TBK66	12	1.75	10.37	10.8	17.73	18	20.03
		14	2	12.1	12.8	20.67	21	23.36	
		16	2	14.1	14.8	23.67	24	26.75	
		18	2.5	15.1	15.8	26.16	27	29.56	
		20	2.5	16.9	18	29.16	30	32.95	
		22	3	18.1	19.4	33	34	37.29	
		24	3	20.2	21.5	35	36	39.55	
		4	0.7	2.9	3.2	6.78	7	7.65	
(35CrMo·镀蓝白锌)	TBK68	6	1	4.9	5.2	9.78	10	11.05	
		8	1.25	6.44	6.8	12.73	13	14.38	
		8	1.25	6.44	6.8	12.73	13	14.38	
		10	1.5	8.04	8.4	15.73	16	17.77	
		12	1.75	10.37	10.8	17.73	18	20.03	
		14	2	12.1	12.8	20.67	21	23.36	
		16	2	14.1	14.8	23.67	24	26.75	
		18	2.5	15.1	15.8	26.16	27	29.56	
		20	2.5	16.9	18	29.16	30	32.95	
		22	3	18.1	19.4	33	34	37.29	
		24	3	20.2	21.5	35	36	39.55	
	(35CrMo·发黑)	TBK69	27	22.5	23.8	40	41	45.2	
		30	24.3	25.6	45	46	50.85		
		33	3.5	27.4	28.7	49	50	55.37	
		36	4	29.4	31	53.8	55	60.79	
		39	4	31.8	33.4	58.8	60	66.44	
		42	4.5	32.4	34	63.1	65	71.3	
		45	4.5	34.4	36	68.1	70	76.95	
		48	5	36.4	38	73.1	75	82.6	

① 带*的规格不适用TBK50。

② 带*规格不适用TBK51。



请按图示订货

型号	
代码	M
TBK54	20
TBK55	24
TBK54—M24	



未税价(元)

优惠价	
数量	价格
1~4	100%
5~	另行报价



① TBK50



② 其余

① TBK56仅适用带*号规格。 ② 带(规格不适用于TBK57。