



法兰型导向轴支座

分离型·安装孔通孔


代码	类型		材质		表面处理
			国标	相当	
GAY01	分离型	安装孔通孔	45	S45C	发黑
GAY02					喷细砂无电解镀镍
GAY06		对边法兰型	0Cr18Ni9	SUS304	—
GAY11					发黑
GAY12			45	S45C	喷细砂无电解镀镍
GAY16					—




① 如对防锈有要求，请优先选用不锈钢材质或喷细砂无电解镀镍产品。



圆法兰型
GAY01/02/06



对边法兰型
GAY11/12/16



6.3/



视角标准：第一视角

型号			L	D ₁	H	T	B	P	W	S	F	d	X	Y	d ₁	d ₂	M		
代码	圆法兰型	对边法兰型	D _{H7}																
			8	+0,015 0	19	24.8	39	5	12	32	27	25	20	3.5	7.5	3.5	4.5	7.5	M4
GAY01 GAY02 GAY06		GAY11	10		21	29.8	49		14	40	32	33	23	4.5	10	3			
		GAY12	12	+0,018 0	23	31.8	52	6	15	42	34	35	25		11	4			
		GAY16	16		32	34.8	56		24	46	37	37	27	5.5	12	5	5.5	9	M5
			20		34	39.8	64	8		52	42	43	30		14				
			25	+0,021 0	40	44.8	69		30	57	47	46	34	6.6	17	6			
			30		42	54.8	79	10		67	57	50	45		20	10	6.6	12	M6



请按图示订货

型号	
代码	D H7
GAY01	8
GAY02	10

GAY02—D8



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价



交货期
5

怡合达
AUTOMATION EXPERT
自动化专家