

单列圆柱滚子轴承





- ◀ 外圈单挡边，内圈双挡边
- ◀ 无外圈，内圈双挡边

品牌	类型	轴承精度	后置代码	轴承材质	
				国标	相当
HRB	NF: 外圈单挡边，内圈双挡边 RN: 无外圈，内圈双挡边	P0	E: 内部加强设计 M: 铜保持架	GCr15	SUJ2



NF: 外圈单挡边，内圈双挡边

RN: 无外圈，内圈双挡边



视角标准：第一视角

◻ 外圈单挡边，内圈双挡边

型号	d	D	B	r1 (min)	r2 (min)	Ew	d1	D1	额定载荷(KN)		极限转速(r/min)		安装尺寸				重量 (kg) 参考
									Cr(动)	Cor(静)	脂润滑	油润滑	da (min)	Db (min)	ra (max)	rb (max)	
NF206EM-HRB	30	62	16	1	0.6	55.5	41.3	51.9	37.5	36.5	9500	12000	34	57		0.6	0.2
NF306EM-HRB		72	19	1.1	1.1	62	45	58.5	51.6	48.4	9000	11000	36.5	64	1	1	0.36
NF207EM-HRB	35		17		0.6	64	48.3	60.7	48.7	48.2	8500	10000	39	66		0.6	0.3
NF307EM-HRB		80	21	1.5		70.2	51.5	66.3	65	53.3	8000	9500	41.5	72	1.5		0.47
NF208EM-HRB	40		18	1.1	1.1	71.5	54.2	67.1	53.9	53.2	7500	9000	46.5	73	1	1	0.37
NF308EM-HRB		90	23	1.5	1.5	80	57.7	75.4	80.4	78			48	82	1.5	1.5	0.64
NF209EM-HRB	45	85	19	1.1	1.1	76.5	59.2	72.1	61.3	64.1	6700	8000	51.5	78	1	1	0.42
NF309EM-HRB		100	25	1.5	1.5	88.5	64.7	83.6	97.6	98.3	6300	7500	53	91	1.5	1.5	0.87
NF210EM-HRB	50	90	20	1.1	1.1	81.5	64.2	77.1	64.1	69.3			56.5	84	1	1	0.48
NF310EM-HRB		110	27	2	2	97	71.2	91.7	110	113	5000	6000	59	99	2	2	1.12
NF211EM-HRB	55	100	21	1.5	1.1	90	70.9	85.2	84.2	96.7	6000	7000	61.5	92	1.5	1.5	0.65
NF2314EM-HRB	70	150	51			133	97.5	126.2	275	325	3600	4300	81	136			4
NF220EM-HRB	100	180	34	2.1	2.1	163	127	155.3	247	303	3200	3800	111	166	2	2	3.45
NF224EM-HRB	120	215	40			195.5	153	186.4	341	430	2400	3000	131	199			5.75

1Kg=9.81N

◻ 无外圈，内圈双挡边

型号	d	d1	B	r2 (min)	Ew	额定载荷(KN)		极限转速(r/min)		安装尺寸			重量(kg) 参考
						Cr(动)	Cor(静)	脂润滑	油润滑	da(min)	Db(min)	ra(max)	
RN228M-HRB	140	179	42	3	221	391	510	2000	2600	153	225	2.5	8.3

1Kg=9.81N



请按图示订货

型号
RN228EM-HRB
RN228M-HRB



未标价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

7