


抽芯铆钉

开口型平圆头/开口型沉头/封闭型扁圆头




代码	类型	材质	表面处理	适用标准
TBC61	开口型平圆头	SUS304	—	GB/T 12618-2006
TBC64		SUS316		
TBC62	开口型沉头	SUS304	—	GB/T 12617-2006
TBC63		SUS316		
TBC65	封闭型扁圆头	SUS304	—	GB/T 12615-2004
TBC66		SUS316		


开口型平圆头
TBC61/64



开口型沉头
TBC62/63



封闭型扁圆头
TBC65/66



开口型平圆头

代码	型号	d	L	dk	开孔直径	K max	P min	d1 max
	3.2	5 6 8 10 12 14 16 20			3.3~3.4			2.15
	4	6 8 10 12 14 16 18 20 25		8	4.1~4.2	1.7		2.75
	4.8	6 8 10 12 14 16 18 20 25		9.5	4.9~5.0	2		3.2
	5	8 10 16			5.1~5.2	2.1	27	3.25
	6	10 12 14 16		12	6.1~6.2	2.5		
	6.4	12 16 20 25 30		13	6.5~6.6	2.7		3.9

代码	型号	d	L	dk		K max	P min	d1 max
				min	max			
(SUS316) TBC64	3.2	6 8 9 10 12 16		5.8	6.7	1.3	25	2.15
	4	6 8 9 10 12 13 14 16		6.9	8.4	1.7	27	2.75
	4.8	8 10 12 13 16 18 20 25 30 35		8.3	10.1	2		3.2

开口型沉头

代码	型号	d	L	dk		K max	P min	d1 max
				min	max			
(SUS304) TBC62	3	6 7 8 9 10		5.4	6.3	1.3	25	2.05
	3.2	5 6 7 8 9 10		5.8	6.7			2.15
	4	6 8 9 10 11 12 13 14 16 18 20 25		6.9	8.4	1.7		2.75
	4.8	8 10 12 13 16 20 25 30		8.3	10.1	2		3.2
	5	10 12 14 16		8.7	10.5	2.1	27	3.25
	6	12 16 20		10.8	12.6	2.5		3.6
(SUS316) TBC63	6.4	12 16		11.6	13.4	2.7		3.83
	3.2	10		5.8	6.7	1.3	25	2.15
	4	8 10 12 14 16		6.9	8.4	1.7		2.75
	4.8	10 12 14 16 20 25		8.3	10.1	2	27	3.2

封闭型扁圆头

代码	型号	d	L	dk		K max	P min	d1 max
				min	max			
(SUS304) TBC65	3	6 8 10		5.76	6.24	1.4	25	2.15
	3.2	6 7 8 9 10 12 14 16		6.9	8.4	1.7		2.75
	4	8 10 12 13 16 18 20 25		9.21	9.79	2	27	3.2
	4.8	8 10 11 12 13 14 16 18 20 25		9.31	9.89			3.9
	5	10 12 13 14 16 20 25		13.4	11.6	2.7		
(SUS316) TBC66	6.4	14 16 20 25		5.76	6.24	1.4	25	2.15
	3.2	8 10		6.9	8.4	1.7		2.75
	4	8 10 12 16		9.21	9.79	2	27	3.2



型号		L
代码	d	
TBC61	3	4 6 8

TBC61—d3—L5



优惠价	
数量	1~100 101~
价格	100% 另行报价

