


夹具用衬套



来图定制



L	引导部长度
5 ~ 14.9	1
15 ~ 29.9	2
30 ~	3

[illegible]

视角标准：第一视角

型号	D公差		最小单位0.01	最小单位0.1	R	H	T	
代码	D	p6	m6	P	L			
Dp6	5	+0.020	+0.012	2.20~3.00	3.0~5.0	0.5以下	9	
	6	+0.012	+0.004	3.00~4.00	3.0~5.5			2.5
	7			3.51~5.00	3.0~8.0			
	8			4.51~6.00				
	9	+0.024	+0.015	4.51~6.50	3.0~12.0			
	10	+0.015	+0.006	6.51~8.00				
	11			8.00~9.00	3.0~17.0	0.5		
	12			8.51~9.00				
	13			8.51~10.00				
	14	+0.029	+0.018	9.00~11.00				
Dm6	15	+0.018	+0.007	10.51~12.00	10.0~37.0			
	17			10.51~13.00				
	18							
	19			12.51~14.00				
	20				5.0~35.0	1.0	5	
	21			13.51~15.00	10.0~37.0			
	22				5.0~35.0			
	25	+0.035	+0.021	13.51~17.00				
	26	+0.022	+0.008	15.51~19.00		30		
	27			15.51~19.00				
28			16.51~20.00	10.0~37.0				
29								
YLF64	30			20.51~24.00		1.5	6	
	31	+0.042	+0.025		5.0~35.0			
	32	+0.026	+0.009	25.01~29.00	12.0~52.0			
	33							



可选加工

代码	TD()	DA	RE
技术说明	变更肩厚 	增加粘接用槽 $L \leq 13.0$时 $L > 13.0$时	增加内径R
	选型方法 TD4 ① 最小单位1 ② D12以下规格不适用	选型方法 DA ① $L \leq 13.0$ 时，加工2道 ② $L > 13.0$ 时，加工3道 ③ $D \leq 13$ 时， $D-P \geq 3$ ④ $D \leq 14$ 时， $D-P \geq 4$ ⑤ 仅适用于标准型且 $L > 9$ 以上规格	选型方法 RE ① 壁厚1.5以下不适用

型号		最小单位0.01	最小单位0.1	可选加工代码
代码	D	P	L	
YLF41	30	20.51~24	10~37	(D) RE
YLF42	35	25.01~29	12~52	

YLF41-D35-P26-L50-TD4



未税价(元)

数量	1~4	5~
价格	100%	另行报价