

DZ47-60小型断路器



3极/4极
正泰品牌

适用范围:

- DZ47-60小型断路器, 主要用于交流50Hz, 额定电压至400V, 额定电流至60A的线路中起过载、短路保护作用, 同时也可以在不正常情况下不频繁地通断电器装置和照明线路, 但不适用于保护电动机;
- 符合标准: GB/T 10963.1、IEC 60898-1, 获得CCC认证。

技术参数:

- 额定电压: 230V/400V AC(1P), 400V AC(2P、3P、4P);
- 额定电流: 6A、10A、15A、16A、20A、25A、32A、40A、50A、60A;
- 瞬时脱扣类型: C型、D型;
- 污染等级: 2级;
- 防护等级: IP20;
- 安装类别: II、III类;
- 机械寿命: 4000次;
- 电气寿命: 4000次。





视角标准: 第一视角



型号	额定电流(A)	极数	脱扣特性	额定电压	分断能力
DZ47-60 3P C1A	1	3P	C	400V AC	6KA
DZ47-60 3P C2A	2				
DZ47-60 3P C3A	3				
DZ47-60 3P C4A	4				
DZ47-60 3P C5A	5				
DZ47-60 3P C6A	6				
DZ47-60 3P C10A	10				
DZ47-60 3P C15A	15				
DZ47-60 3P C16A	16				
DZ47-60 3P C20A	20				
DZ47-60 3P C25A	25				
DZ47-60 3P C32A	32				
DZ47-60 3P C40A	40				
DZ47-60 3P C50A	50				
DZ47-60 3P C60A	60				
DZ47-60 3P D1A	1				
DZ47-60 3P D2A	2				
DZ47-60 3P D3A	3				
DZ47-60 3P D4A	4				
DZ47-60 3P D5A	5				
DZ47-60 3P D6A	6				
DZ47-60 3P D10A	10				
DZ47-60 3P D15A	15				
DZ47-60 3P D16A	16				
DZ47-60 3P D20A	20				
DZ47-60 3P D25A	25				
DZ47-60 3P D32A	32				
DZ47-60 3P D40A	40				
DZ47-60 3P D50A	50				
DZ47-60 3P D60A	60				
DZ47-60 4P C1A	1	4P	C		
DZ47-60 4P C2A	2				
DZ47-60 4P C3A	3				
DZ47-60 4P C4A	4				
DZ47-60 4P C5A	5				
DZ47-60 4P C6A	6				
DZ47-60 4P C10A	10				
DZ47-60 4P C15A	15				
DZ47-60 4P C16A	16				
DZ47-60 4P C20A	20				
DZ47-60 4P C25A	25				
DZ47-60 4P C32A	32				
DZ47-60 4P C40A	40				
DZ47-60 4P C50A	50				
DZ47-60 4P C60A	60				
DZ47-60 4P D1A	1			4P	D
DZ47-60 4P D2A	2				
DZ47-60 4P D3A	3				
DZ47-60 4P D4A	4				
DZ47-60 4P D5A	5				
DZ47-60 4P D6A	6				
DZ47-60 4P D10A	10				
DZ47-60 4P D15A	15				
DZ47-60 4P D16A	16				
DZ47-60 4P D20A	20				
DZ47-60 4P D25A	25				
DZ47-60 4P D32A	32				
DZ47-60 4P D40A	40				
DZ47-60 4P D50A	50				
DZ47-60 4P D60A	60				

脱扣曲线图



请按图示订货

型号
DZ47-60 3P C6A
DZ47-60 3P C10A

报价方式: FAX, 电话, 邮件, 网络