

美标矩形弹簧



轻载荷弹簧(蓝色)

代码	类型	材质	最大压缩量
YMSB	轻载荷型	9254V	L×40%

□ L尺寸公差

L	公差
25~64	±3%
76~114	±2.5%
127~305	±2%

- ① 载荷(±10%)
- ① 直角度(3°以下)
- ① 负载(N)=弹簧常数(N/mm)×压缩量
- ① 理论使用次数: 30万次
- ① 弹簧颜色和圈数可能会因生产批次的不同有差异, 但产品性能均符合标准, 不影响使用!
- ① 参考标准NAAMS标准



视角标准: 第一视角

型号	轴径	弹簧常数	使用方法
代码 孔径D 长度L	D _d	(N/mm)	30万次F=L×40% F(mm) 负载(N)
YMSB	9.53	25.4	10.5 10.2 107
		31.75	8.8 12.7 111
		38.1	7.4 15.2 112
		44.45	6.5 17.8 115
		50.8	5.4 20.3 110
		63.5	4.6 25.4 116
	12.7	76.2	3.7 30.5 112
		304.8	1.1 121.9 128
		25.4	19.3 10.2 196
		31.75	14.4 12.7 182
		38.1	11.9 15.2 181
		44.45	10.5 17.8 187
YMSB	15.88	50.8	9.6 20.3 196
		63.5	7.9 25.4 200
		76.2	6.1 30.5 187
		88.9	5.3 35.6 187
		114.3	4 45.7 184
		139.7	3.5 55.9 196
	19.05	165.1	2.5 66 162
		190.5	2.1 76.2 160
		304.8	12 121.9 149
		25.4	28.7 10.2 292
		31.75	21.7 12.7 276
		38.1	18.9 15.2 288
YMSB	25.4	44.45	16.8 17.8 299
		50.8	15.1 20.3 306
		63.5	11.4 25.4 289
		76.2	10.2 30.5 310
		88.9	8.8 35.6 311
		101.6	7.7 40.6 313
	31.75	304.8	2.6 121.9 320
		25.4	56 10.2 569
		31.75	44.8 12.7 560
		38.1	35 15.2 534

型号	轴径	弹簧常数	使用方法
代码 孔径D 长度L	D _d	(N/mm)	30万次F=L×40% F(mm) 负载(N)
YMSB	9.53	44.45	30.8 17.8 548
		50.8	26.3 20.3 534
		63.5	21 25.4 534
		76.2	17.7 30.5 539
		88.9	14.5 35.6 517
		101.6	13.1 40.6 534
YMSB	12.7	114.3	11.2 45.7 512
		127	10.5 50.8 534
		139.7	9.6 55.9 538
		152.4	8.8 61 534
		165.1	8.2 66 544
		190.5	6.7 76.2 507
YMSB	15.88	304.8	4.2 121.9 512
		31.75	78.8 12.7 1001
		38.1	65.3 15.2 995
		44.45	56 17.8 996
		50.8	46.9 20.3 954
		76.2	29.9 30.5 913
YMSB	19.05	88.9	25.4 35.6 903
		101.6	21.9 40.6 890
		114.3	19.3 45.7 881
		127	16.8 50.8 854
		139.7	15.4 55.9 861
		152.4	14 61 854
YMSB	25.4	177.8	12.6 71.1 897
		203.2	10.5 81.3 854
		304.8	7 121.9 854
		38.1	86.9 15.2 1324
		44.45	71.1 17.8 1264
		50.8	65.8 20.3 1338
YMSB	31.75	76.2	50.4 25.4 1281
		88.9	42 30.5 1281
		101.6	35 35.6 1245
		127	30.8 40.6 1253

型号	轴径	弹簧常数	使用方法
代码 孔径D 长度L	D _d	(N/mm)	30万次F=L×40% F(mm) 负载(N)
YMSB	9.53	114.3	28 45.7 1281
		127	25 50.8 1272
		139.7	22.4 55.9 1253
		152.4	21 61 1281
		177.8	18.2 71.1 1295
		203.2	15.4 81.3 1253
YMSB	12.7	254	12.6 101.6 1281
		304.8	10.5 121.9 1281
		50.8	92.8 20.3 1886
		63.5	74.8 25.4 1899
		76.2	63 30.5 1922
		88.9	52.5 35.6 1868
YMSB	15.88	101.6	43.6 40.6 1772
		114.3	40.3 45.7 1841
		127	36.8 50.8 1868
		139.7	32.4 55.9 1810
		152.4	29.8 61 1815
		177.8	26.8 71.1 1906
YMSB	19.05	203.2	23.1 81.3 1879
		254	18.6 101.6 1886
		304.8	14.9 121.9 1815
		63.5	175.1 25.4 4448
		76.2	145.3 30.5 4430
		88.9	118.5 35.6 4216
YMSB	25.4	101.6	105.1 40.6 4270
		114.3	92.8 45.7 4243
		127	82.3 50.8 4181
		139.7	70.9 55.9 3963
		152.4	68.3 61.0 4163
		177.8	54.6 71.1 3886
YMSB	31.75	203.2	49.9 81.3 4057
		254	37.8 101.6 3843
		304.8	32.4 121.9 3950



请按图示订货

代码	型号	D	L
YMSB	9.53	25.4	31.75

YMSB—D9.53—L25.4



未税价(元)

数量	1~9	10~
价格	100%	另行报价



交货期

12

12