


内六角圆柱头螺钉

粗牙 / 细牙
标准型 强度等级A2-70

代码	类型	螺纹	材质		强度等级
			国标	相当	
TAC21	标准型	全牙/半牙	0Cr18Ni9	SUS304	A2-70
TAC05		粗牙			
TAC09		全牙			
		细牙			



适用标准: DIN 912-1983、GB/T 70.1-2000



粗牙 常规型

型号		L										V	P	D		K		S	
代码	M												螺距	max	min	max	min	max	min
TAC21	1.6	3	4	5	6	8	10	12	14	16			0.35	3.14	2.86	1.6	1.46	1.56	1.52
	2	3	4	5	6	8	10	12	14	16	18	20	22	25	30	35	40		
	2.5	3	4	5	6	8	10	12	14	16	18	20	22	25	30				
	3	5	6	8	10	12	14	16	18	20	22	25	30	35	40				
	4	5	6	8	10	12	14	16	18	20	22	25							
													20						
	5	6	8	10	12	14	16	18	20	22	25		全牙	0.8	8.72	8.28	5	4.82	4.095
													22						
	6	8	10	12	14	16	18	20	22	25	30		全牙	1	10.22	9.78	6	5.7	5.14
													24						
	8	35	40	45	50	55	60	65	70	75	80	85	90	100	110	120	130		
	10	40	45	50	55	60	65	70	75	80	90	95	100	110	120	130	140	150	
	12	45	50	55	60	65	70	75	80	85	90	100	110	120	130	140	150		
	14	55	60	65	70	75	80	85	90	100	110	120	130	140	150				
	16	60	65	70	80	90	100												
	20	80	90	100	110	120	130	140	150				全牙	2.5	30.33	29.67	20	19.48	17.05
													52						

粗牙 加长型

型号		L														V	P 螺距	D		K		S		
代码	M																	max	min	max	min	max	min	
TAC05	3	30 35 40 45 50 55 60															0.5	5.68	5.32	3	2.86	2.58	2.52	
	4	30 35 40 45 50 55 60 65 70 75 80														100 110 120	0.7	7.22	6.78	4	3.82	3.08	3.02	
	5	30 35 40 45 50 55 60 65 70 75 80 85 90															0.8	8.72	8.28	5	4.82	4.095	4.02	
	6	30 35 40 45 50 55 60 65 70 75 80 85 90														100 110 120 130 140 150	1	10.22	9.78	6	5.7	5.14	5.02	
	8	20 25	40 45 50 55 60 65 70 75 80 85 90 95 100 110 120 130 140 150 160														全牙	1.25	13.27	12.73	8	7.64	6.14	6.02
	10	45 50 55 60 65 70 75 80 85 90														100 110 120 130 140 150	1.5	16.27	15.73	10	9.64	8.175	8.025	
	12	55 60 65 70 75 80 85 90														100 110 120 130 140 150	1.75	18.27	17.73	12	11.57	10.175	10.025	
	16	65 70 75 80 90														100 110 120 130 140 150	2	24.33	23.67	16	15.57	14.212	14.032	
	20	80 90														100 110 120 130 140 150	2.5	30.33	29.67	20	19.48	17.23	17.05	

细牙

型号		L										V	P	D		K		S	
代码	M												螺距	max	min	max	min	max	min
TAC09	6	10	12	16	20	25	30	35	40	45	50		0.75	10.22	9.78	6	5.7	5.14	5.02
	8	16	20	25	30	35	40	45	50	60	70	80	90	100					
	10	20	25	30	35	40	45	50	60	70	80	90	100						
	12	20	25	30	35	40	45	50	60	70	80	90	100						



型号		L									
代码	M										
(3)	5	6	8	10							
(4)	5	6	8	10							
(5)	5	6	8	10							

TAC21-M3-L6



优惠价	
数量	1~49 50~
价格	100% 另行报价

未税价(元)



交货期	
3	