


代码	类型	螺纹	材质	表面处理	强度等级
TAC02	标准型	全牙/半牙	ML40Cr	镀镍	12.9
TAC22		全牙			
TAC03		全牙/半牙			



① 适用标准: GB/T 70.1-2000, DIN 912-1983

视角标准: 第一视角

② 镀镍(全牙/半牙)

代码	M	L	V	P 螺距	D		K		S	
					max	min	max	min	max	min
TAC02	2	4 5 6 8 10 12 14 16 20	全牙	0.4	3.98	3.62	2	1.86	1.56	1.52
	2.5	4 5 6 8 10 12 16 18 20		0.45	4.68	4.32	2.5	2.36	2.06	2.02
	3	5 6 8 10 12 14 16 20 25	全牙	0.5	5.68	5.32	3	2.86	2.58	2.52
				18	30 35 40 50					
	4	5 6 8 10 12 14 16 20 25	全牙	0.7	7.22	6.78	4	3.82	3.08	3.02
				20	30 35 40 45 50 55 60 65 70 75					
	5	6 8 10 12 14 16 20 25 30	全牙	0.8	8.72	8.28	5	4.82	4.095	4.02
				22	35 40 45 50 55 60 65 70 75 80					
	6	8 10 12 14 16 20 25 30	全牙	1.0	10.22	9.78	6	5.7	5.14	5.02
				24	40 45 50 55 60 65 70 75 80					
	8	12 16 20 25 30 35	全牙	1.25	13.27	12.73	8	7.64	6.14	6.02
				28	40 45 50 55 60					
10	16 20 25 30 35 40	全牙	1.5	16.27	15.73	10	9.64	8.175	8.025	
			32	45 50 55 60						
12	16 20 25 30 35 40 45 50	全牙	1.75	18.27	17.73	12	11.57	10.175	10.025	
			36	55 60						

③ 镀镍(全牙)

代码	M	L	V	P 螺距	D		K		S	
					max	min	max	min	max	min
TAC22	3	30 35 40	全牙	0.5	5.68	5.32	3	2.86	2.58	2.52
	4	30 35 40 45 50		0.7	7.22	6.78	4	3.82	3.08	3.02
	5	30 35 40 45 50		0.8	8.72	8.28	5	4.82	4.095	4.02
	6	40 45 50 55 60 65 70 75 80		1.0	10.22	9.78	6	5.7	5.14	5.02

④ 镀达克罗(全牙/半牙)

代码	M	L	V	P 螺距	D		K		S	
					max	min	max	min	max	min
TAC03	3	5 6 8 10 12 16 20 25	全牙	0.5	5.68	5.32	3	2.86	2.58	2.52
	4	5 6 8 10 12 16 20 25	全牙	0.7	7.22	6.78	4	3.82	3.08	3.02
	5	6 8 10 12 14 16 20 25	全牙	0.8	8.72	8.28	5	4.82	4.095	4.02
	6	8 10 12 14 16 20 25 30	全牙	1.0	10.22	9.78	6	5.7	5.14	5.02
	8	12 16 20 25 30 35 40	全牙	1.25	13.27	12.73	8	7.64	6.14	6.02
10	16 20 25 30 35 40	全牙	1.5	16.27	15.73	10	9.64	8.175	8.025	
										32



请按图示订货

型号	
代码	M
TAC02	2.5
L	
	4 5 6 8 10 12
	5 6 8 10 12

TAC02—M2—L6



未税价(元)

优惠价	
数量	价格
1~45	另行报价
46~	另行报价



交货期	
7	