

工业级管道配件


带颈平焊/带颈对焊

法兰 标准: HG/T 20615-2009(美标)

过程控制

带颈平焊

代码	法兰类型	密封面形式	材质	公称压力	参考标准
XMS07	带颈平焊	突面(RF)	SUS304	Class150	HG/T 20615-2009
XMS08	(SO)		SUS316		(美标)




视角标准: 第一视角

型号		NPS	适用 钢管外径	法兰外径 D	连接尺寸				C	B	N	H	d	f ₁
代码	公称尺寸				K	L	n	适用螺栓						
XMS07	DN15	1/2"	21.3	90	60.3				9.6	22.5	30	14	34.9	2
	DN20	3/4"	26.9	100	69.9				11.2	27.5	38		42.9	
	DN25	1"	33.7	110	79.4	16		M14	12.7	34.5	49	16	50.8	
	DN32	1 1/4"	42.4	115	88.9		4		14.3	43.5	59	19	63.5	
	DN40	1 1/2"	48.3	125	98.4				15.9	49.5	65	21	73	
XMS08	DN50	2"	60.3	150	120.7			M16	17.5	61.5	78	24	92.1	
	DN65	2 1/2"	76.1	180	139.7	18			20.7	77.6	90	27	104.8	
	DN80	3"	88.9	190	152.4					90.5	108	29	127	
	DN100	4"	114.3	230	190.5				22.3	116	135	32	157.2	
	DN125	5"	139.7	255	215.9		8			143.5	164	35	185.7	
	DN150	6"	168.3	280	241.3	22		M20	23.9	170.5	192	38	215.9	
	DN200	8"	219.1	345	298.5				27	221.5	246	43	269.9	

带颈对焊

代码	法兰类型	密封面形式	材质	公称压力	参考标准
XMS09	带颈对焊	突面(RF)	SUS304	Class150	HG/T 20615-2009
XMS10	(WN)		SUS316		(美标)



视角标准: 第一视角

型号		NPS	钢管外径 A	法兰外径 D	连接尺寸				C	B	N	H	d	f ₁
代码	公称尺寸				K	L	n	适用螺栓						
XMS09	DN15	1/2"	21.3	90	60.3				9.6	15.5	30	46	34.9	2
	DN20	3/4"	26.9	100	69.9				11.2	21	38	51	42.9	
	DN25	1"	33.7	110	79.4	16		M14	12.7	27	49	54	50.8	
	DN32	1 1/4"	42.4	115	88.9		4		14.3	35	59	56	63.5	
	DN40	1 1/2"	48.3	125	98.4				15.9	41	65	60	73	
XMS10	DN50	2"	60.3	150	120.7			M16	17.5	52	78	62	92.1	
	DN65	2 1/2"	76.1	180	139.7	18			20.7	66	90	68	104.8	
	DN80	3"	88.9	190	152.4					77.5	108		127	
	DN100	4"	114.3	230	190.5				22.3	101.5	135	75	157.2	
	DN125	5"	139.7	255	215.9		8			127	164	87	185.7	
	DN150	6"	168.3	280	241.3	22		M20	23.9	154	192		215.9	
	DN200	8"	219.1	345	298.5				27	203	246	100	269.9	



请按图示订货

型号	
代码	公称尺寸
XMS09	DN15
XMS10	DN20
XMS09—DN15	



未税价(元)

● 优惠价	数量	1~49	50~
	价格	100%	另行报价



交货期
8