


# 拉伸弹簧

## 中载型

| 代码     | 类型  |        |     | 材质       |            | 挂钩相对角度 |
|--------|-----|--------|-----|----------|------------|--------|
|        |     |        |     | 国标       | 相当         |        |
| Y-YAUS | 中载型 | 半圆形单挂钩 | 标准型 | 0Cr18Ni9 | SUS304-WPB | 180°   |

① 弹簧两端挂钩保持水平或者垂直状态，无法保证挂钩开口方向每批都一致，不影响使用。



视角标准：第一视角

| 代码     | 型号 |     | 线径 d | 动态负载时      |        | 初始张力 (N) | 弹簧常数 N/mm |  |      |
|--------|----|-----|------|------------|--------|----------|-----------|--|------|
|        | D  | L   |      | 最大位移量 Fmax | 最大载荷 N |          |           |  |      |
| Y-YAUS | 2  | 10  | 0.3  | 3.8        | 3.53   | 0.69     | 0.75      |  |      |
|        |    | 15  |      | 6.7        |        |          | 0.42      |  |      |
|        |    | 20  |      | 9.6        |        |          | 0.30      |  |      |
|        |    | 25  |      | 12.6       |        |          | 0.23      |  |      |
|        | 3  | 10  | 0.4  | 3.5        | 4.41   | 0.88     | 0.98      |  |      |
|        |    | 15  |      | 6.0        |        |          | 0.59      |  |      |
|        |    | 20  |      | 9.0        |        |          | 0.39      |  |      |
|        |    | 25  |      | 12.0       |        |          | 0.29      |  |      |
|        | 4  | 15  | 0.5  | 15.6       | 6.37   | 1.18     | 0.23      |  |      |
|        |    | 20  |      | 20.3       |        |          | 0.22      |  |      |
|        |    | 25  |      | 24.0       |        |          | 0.22      |  |      |
|        |    | 30  |      | 28.7       |        |          | 0.22      |  |      |
|        | 5  | 15  | 0.6  | 5.6        | 8.53   | 1.57     | 1.27      |  |      |
|        |    | 20  |      | 8.9        |        |          | 0.78      |  |      |
|        |    | 25  |      | 13.7       |        |          | 0.49      |  |      |
|        |    | 30  |      | 17.3       |        |          | 0.39      |  |      |
|        | 6  | 35  | 0.8  | 23.7       | 17.26  | 3.53     | 0.29      |  |      |
|        |    | 40  |      | 24.5       |        |          | 0.28      |  |      |
|        |    | 45  |      | 28.4       |        |          | 0.25      |  |      |
|        |    | 50  |      | 32.2       |        |          | 0.22      |  |      |
|        | 8  | 20  | 1.0  | 6.7        | 24.52  | 4.9      | 2.06      |  |      |
|        |    | 25  |      | 9.3        |        |          | 1.47      |  |      |
|        |    | 30  |      | 12.7       |        |          | 1.08      |  |      |
|        |    | 35  |      | 15.6       |        |          | 0.88      |  |      |
| 10     | 40 | 1.2 | 18.7 | 30.99      | 5.49   | 0.69     |           |  |      |
|        | 45 |     | 20.6 |            |        | 0.68     |           |  |      |
|        | 50 |     | 24.5 |            |        | 0.57     |           |  |      |
|        | 55 |     | 25.0 |            |        | 0.50     |           |  |      |
|        | 60 |     | 29.7 |            |        | 0.47     |           |  |      |
|        | 65 |     | 31.6 |            |        | 0.47     |           |  |      |
|        | 70 |     | 34.2 |            |        | 0.47     |           |  |      |
|        | 75 |     | 38.8 |            |        | 0.47     |           |  |      |
|        | 80 |     | 43.3 |            |        | 0.67     |           |  |      |
|        |    |     |      |            |        | 47.2     |           |  | 0.60 |
|        |    |     |      |            |        |          |           |  | 0.55 |
|        |    |     |      |            |        |          |           |  | 0.55 |

| 代码     | 型号  |     | 线径 d | 动态负载时      |        | 初始张力 (N) | 弹簧常数 N/mm |
|--------|-----|-----|------|------------|--------|----------|-----------|
|        | D   | L   |      | 最大位移量 Fmax | 最大载荷 N |          |           |
| Y-YAUS | 12  | 35  | 1.6  | 8.5        | 62.76  | 14.71    | 5.69      |
|        |     | 40  |      | 11.8       |        |          | 4.12      |
|        |     | 45  |      | 14.3       |        |          | 3.33      |
|        |     | 50  |      | 16.8       |        |          | 2.84      |
|        | 14  | 55  | 1.8  | 19.3       | 74.53  | 16.67    | 2.45      |
|        |     | 60  |      | 22.3       |        |          | 2.16      |
|        |     | 65  |      | 24.5       |        |          | 1.96      |
|        |     | 70  |      | 27.2       |        |          | 1.77      |
|        | 16  | 75  | 2.0  | 28.8       | 86.3   | 19.61    | 1.67      |
|        |     | 80  |      | 32.7       |        |          | 1.47      |
|        |     | 90  |      | 36.3       |        |          | 1.35      |
|        |     | 100 |      | 41.0       |        |          | 1.20      |
|        |     | 40  |      | 10.2       |        |          | 5.69      |
|        |     | 45  |      | 13.1       |        |          | 4.41      |
|        |     | 50  |      | 16.4       |        |          | 3.53      |
|        |     | 55  |      | 19.7       |        |          | 2.94      |
|        | 60  |     | 21.1 |            |        | 2.75     |           |
|        | 65  |     | 24.6 |            |        | 2.35     |           |
|        | 70  |     | 27.6 |            |        | 2.06     |           |
|        | 75  |     | 31.1 |            |        | 1.86     |           |
|        | 80  |     | 32.8 |            |        | 1.77     |           |
|        | 90  |     | 37.5 |            |        | 1.60     |           |
|        | 100 |     | 42.8 |            |        | 1.40     |           |
|        | 125 |     | 60.0 |            |        | 1.00     |           |
|        | 45  |     | 11.7 |            |        | 5.69     |           |
|        | 50  |     | 15.1 |            |        | 4.41     |           |
|        | 55  |     | 17.4 |            |        | 3.82     |           |
|        | 60  |     | 21.3 |            |        | 3.14     |           |
|        | 65  |     | 23.4 |            |        | 2.84     |           |
|        | 70  |     | 26.8 |            |        | 2.45     |           |
|        | 75  |     | 29.6 |            |        | 2.26     |           |
|        | 80  |     | 32.7 |            |        | 2.10     |           |
|        | 90  |     | 37.8 |            |        | 1.77     |           |
|        | 100 |     | 45.3 |            |        | 1.47     |           |
|        | 125 |     | 56.7 |            |        | 1.20     |           |
|        | 150 |     | 71.5 |            |        | 0.95     |           |

① 初始张力·弹簧常数为参考值。负载(kgf)=负载N×0.101972



请按图示订货

| 型号     |    |    |
|--------|----|----|
| 代码     | D  | L  |
| Y-YAUS | 3  | 10 |
|        | 15 |    |

Y-YAUS-D3-L10



未税价(元)

| 优惠价 |           |
|-----|-----------|
| 数量  | 1~19 20~  |
| 价格  | 100% 另行报价 |