


锁紧螺母

牙腹锁紧型·三/六槽 圆形


代码	类型	槽数	材质		热处理	表面处理
			国标	相当		

特点：该产品锁紧铜与螺纹呈30°角设计，不承受作用于螺纹上的轴向负荷。当螺母锁紧时，螺纹面不会解除轴向负荷，螺母不会变形。等间距锁紧铜可以用来调整即将装到轴上其他部件的偏差。由于锁紧铜不会变形，螺母经多次拆装仍可以保持精密度。

本产品自带螺钉。



螺纹精度：ISO 4H
端面偏摆：0.005



视角标准：第一视角

型号	代码	公称尺寸	螺距	D	H	d	t	n-g	N-M	扭紧力矩 (NM)
BKJ73	M12	1.5		30	14	25		3-4		
	M14	1.5								
	M15	1.0							3-M6	8
	M16	1.5								
	M17	1.0				27				
	M18	1.5		32						
	M20	1.0			16	34	2		3-M5	4.5
	M22			38		33		3-5		
	M24									
	M25								3-M6	8
	M27			40		35				
	M30			45	18	41				
	M33			50		45				
	M35									
	M36	1.5		52		46				
	M39									
	M40			58		52				
	M42			62	20	56	2.5	3-6		
	M45			65		59				
	M48			70		64				
	M50									
	M52			73		66				
	M55	2.0		75		68			3-M8	18
	M56	1.5								
	M60	2.0		80		73				
	M64	1.5			85	78		3-8		
	M65									
	M68									
	M70	2.0		92		84				
	M72			94	24	86	3.5			
	M75									
	M76			98		90				

型号	代码	公称尺寸	螺距	D	H	d	t	n-g	N-M	扭紧力矩 (NM)
BKJ73	M80			105	24	98		3-8		
	M85			110		102				
	M90			120		108			3-M8	18
	M95			125	26	117				
	M100			130		118				
	M105			140		125		6-10		
	M110			145	28	132				
	M115	2.0		150		137				
	M120			155		142				
	M125			160	30	147				
	M130			165		152				
	M135			175		160	5	6-12	3-M10	35
	M140			180		165				
	M145			190	32	175				
	M150			195		180				
	M155			200						
	M160			210	34	190	6	6-14		
	M165									
	M170	3.0		220		200				
	M180			230	36	205				
	M190			240		215		6-16		
	M200			250		225				
	M210	4.0		260	38	245	7		3-M12	60
	M220	3.0		270		255				
	M240	4.0		290		268	9			
	M260	3.0		310	40	288		6-20		
	M270			320		298				
	M280	4.0		330		308			3-M14	100
	M300			360	42	336	11	6-24		



请按图示订货

型号	代码	公称尺寸	螺距	D
BKJ73	M12	1.5		30
	M14			

BKJ73—M12—1.5



未税价(元)

优惠价	数量	1~9	10~
价格	100%	另行报价	



交货期	5
-----	---