


双列圆柱滚子轴承

轴承精度:P5级
圆柱孔型/圆锥孔型


代码	类型	轴承精度	后置代码	轴承材质	
				国标	相当
BFA73	外圈无挡边	P5级	未标注(圆柱孔) K(圆锥孔, 锥度1:12) W33(轴承外圈有润滑油槽和3个润滑油孔)	GCr15	SUJ2
	圆柱孔型				




圆柱孔型





安装图



圆锥孔型



安装图



视角标准: 第一视角

代码	型号		d	D	B	r (min)	Ew	基本额定载荷 (KN)		极限转速rpm (参考)		安装尺寸					重量 (Kg) (参考)	
	轴承型号							Cr(动)	Cor(静)	脂润滑	油润滑	d _b (min)	d _{1b} (min)	d _a		r ₁ (max)		
	圆柱孔型	圆锥孔型												max	min			
BFA73	—	NN3005K/W33	25	47	16	0.6	41.3	25.8	30	14000	17000	29	29	43	42	0.6	0.122	
	NN3006/W33	NN3006K/W33	30	55	19		48.5	31	37	12000	14000	35	36	50	50		1.193	
	NN3007/W33	NN3007K/W33	35	62	20		55	39.5	50	10000	12000	40	41	57	56		0.236	
	NN3008/W33	NN3008K/W33	40	68	21	1	61	48.7	64.6	9000	11000	45	46	63	62		0.302	
	NN3009/W33	NN3009K/W33	45	75			67.5	57.6	78.9	8500	10000	50	51	70	69		0.393	
	NN3010/W33	NN3010K/W33	50	80			72.5	65.4	90.6	7500	9000	55	56	75	74		0.419	
	NN3011/W33	NN3011K/W33	55	90			81	75.7	108	6700	8000	61.5	62	83.5	83		0.63	
	NN3012/W33	NN3012K/W33	60	95	26		86.1	77.4	114	6300	7500	66.5	67	88.5	88	1	0.681	
	NN3013/W33	NN3013K/W33	65	100			91	81.5	124	6000	7100	71.5	72	93.5	93		0.731	
	—	NN3014K/W33	70	110		1.1	100	98.8	151	5600	6700	76.5	77	103.5	102		1.01	
	NN3015/W33	NN3015K/W33	75	115		30	105	96.5	149	5300	6300	81.5	82	108.5	107		1.11	
	NN3016/W33	NN3016K/W33	80	125			113	123	194	4800	6000	86.5	87	118.5	115		1.48	
	NN3017/W33	NN3017K/W33	85	130		34	118	126	203	4500	5600	91.5	92	123.5	120		1.55	
	NN3018/W33	NN3018K/W33	90	140			127	143	228	4300		98	99	132	129		2.01	
	—	NN3019K/W33	95	145		37	132	154	255		5000	103	104	137	134	1.5	2.09	
	NN3020/W33	NN3020K/W33	100	150			137	161	274	4000		4800	108	109	142	139		2.09
	NN3021/W33	NN3021K/W33	105	160	41		146	201	328	3800	4500	114	115	151	148		2.79	
	NN3022/W33	NN3022K/W33	110	170	45		155	231	380	3400	4300	119	121	161	157		3.56	
	NN3024/W33	NN3024K/W33	120	180	46	2	165	229	241	3200	3800	129	131	171	167		3.92	
	NN3026/W33	NN3026K/W33	130	200	52		182	265	457	3000	3600	139	141	191	185		5.71	
	NN3028/W33	NN3028K/W33	140	210	53		192	270	477	2800	3400	149	151	201	195		6.21	
	—	NN3030K/W33	150	225	56		206	335	585	2600	3000	161	162	214	209	2	7.53	
	—	NN3032K/W33	160	240	60		219	375	660	2400	2800	171	172	229	222		8.59	
	—	NN3034K/W33	170	260	67	2.1	236	450	805	2200	2600	181	183	249	239		12.2	
	—	NN3036K/W33	180	280	74		255	565	995		2400	191	193	269	258		16	
	—	NN3038K/W33	190	290	75		265	595	1080			201	203	279	268		17.4	
	—	NN3040K/W33	200	310	82		282	707	1260	1800	2200	211	214	299	285		20.8	
	—	NN3044K/W33	220	340	90		310	815	1480	1700	2000	233	236	327	313		28.2	
	—	NN3048K/W33	240	360	92	3	330	855	1660	1500	1800	253	256	347	334	2.5	31.7	
	—	NN3052K/W33	260	400	104		364	1030	1920	1400	1700	276	278	384	368		45.8	
	—	NN3056K/W33	280	420	106		384	1109	2150	1300	1500	296	298	404	388		49.3	
	—	NN3060K/W33	300	460	118	4	418	1290	2460	1200	1400	316	319	444	422	3	68.6	
	—	NN3064K/W33	320	480	121		438	1350	2670	1100	1300	336	340	464	442		76.6	

1 Kg=9.81N



请按图示订货

代码	型号	
	轴承型号	
	圆柱孔型	圆锥孔型
BFA73	—	NN3005K/W33
	NN3006/W33	NN3006K/W33

BFA73—NN3006/W33



未税价(元)

优惠价	数量	1~9	10~
	价格	100%	另行报价



交货期

6