


压缩弹簧

内径基准不锈钢型


代码	类型	材质		允许位移量	弹簧常数公差
		国标	相当		
Y-YVUR	内径基准不锈钢型 标准型	0Cr18Ni9	SUS304-WPB	L×60%	±10%



- 特点：以内径为基准的圆线螺旋弹簧。
- ① 压紧长度为参考值，因批量不同会有偏差。
- ② 使用次数：100万次。
- ③ 带()的L规格进行磨削加工。
- ④ 此系列为内径基准型弹簧，以保证内径公差进行生产，内径为正公差，适合配轴使用，外径仅做参考(按正公差)，选型时请注意。



RoHS



代码	型号		D ₁	d	压紧长度	F _{max}	允许负载 N _{max}	弹簧常数 N/mm	代码	型号		D ₁	d	压紧长度	F _{max}	允许负载 N _{max}	弹簧常数 N/mm
	D	L								D	L						
Y-YVUR	5	15	±0.7	5.9	0.45	5.0	9	2.65	10	20	±0.8	11.4	0.70	5.6	12	3.53	0.29
		20	±0.7				25	±0.75		15	4.41						
		25	±0.75				30	±0.9		18	5.29						
		(30)	±0.9				35	±1		21	6.17						
		35	±1				40	±1		24	7.06						
		40	±1				45	±1		27	7.94						
		45	±1				50	±1		30	8.82						
		50	±1				15	±0.7		9	2.65				0.30		
		20	±0.7				12	3.53									
		25	±0.75				15	4.41									
		30	±0.9				18	5.29									
		35	±1				21	6.17									
	40	±1	24	7.06													
	45	±1	27	7.94													
	50	±1	30	8.82													
	55	±1.65	33	9.70													
	60	±1.8	36	10.59													
	65	±1.95	39	11.47													
	8	20	±0.7	9.3	0.65	6.8	12	3.53	12	20	±0.8	13.6	0.80	7.2		15	4.41
		25	±0.75				25	±0.75		18	5.29						
		30	±0.9				30	±0.9		21	6.17						
		35	±1				35	±1		24	7.06						
		40	±1				40	±1		27	7.94						
		45	±1				45	±1		30	8.82						
50		±1	50				±1	33		9.70							
55		±1.65	55				±1.65	36		10.59							
60		±1.8	60				±1.8	39		11.47							
65		±1.95	65				±1.95	42		12.36							
70		±2	70				±2	48		14.12							
12		20	±0.7				9.3	0.65		6.8	12				3.53	16	20
	25	±0.75	25	±0.75	18	5.29											
	30	±0.9	30	±0.9	21	6.17											
	35	±1	35	±1	24	7.06											
	40	±1	40	±1	27	7.94											
	45	±1	45	±1	30	8.82											
	50	±1	50	±1	33	9.70											
	55	±1.65	55	±1.65	36	10.59											
	60	±1.8	60	±1.8	39	11.47											
	65	±1.95	65	±1.95	42	12.36											
	70	±2	70	±2	48	14.12											
	16	20	±0.7	9.3	0.65	6.8			12		3.53	18	20	±0.8	18.2		1.10
25		±0.75	25				±0.75	18	5.29								
30		±0.9	30				±0.9	21	6.17								
35		±1	35				±1	24	7.06								
40		±1	40				±1	27	7.94								
45		±1	45				±1	30	8.82								
50		±1	50				±1	33	9.70								
55		±1.65	55				±1.65	36	10.59								
60		±1.8	60				±1.8	39	11.47								
65		±1.95	65				±1.95	42	12.36								
70		±2	70				±2	48	14.12								

- ① 允许位移量F_{max}: 表示弹簧允许压缩的最大长度，超出此压缩量使用弹簧会缩短。
- ② 允许负载N_{max}: 表示压缩F_{max}的负载，单位N。
- ③ 弹簧常数N/mm=(N_{max})/(F_{max})。



型号		
代码	D	L
Y-YVUR	5	35

请按图示订货 Y-YVUR—D5—L30



● 优惠价
数量 1~9 10~
价格 100% 另行报价

未标价(元)