





代码	类型		材质		热处理		爪硬度	表面处理
			本体	爪	本体	爪		
ZFB25	带固定爪	锯齿爪	45	SKH51	淬火回火 硬度32~38HRC	淬火回火	60~62HRC	发黑
ZFB26		平面爪						
ZFB27		树脂爪						

锯齿爪
ZFB25平面爪 ZFB26
树脂爪 ZFB27

EX

Example
使用示例

来图定制



视角标准：第一视角

型号		W	W ₁	H	H ₁	M	D	L ₁	L ₂	L ₃	L ₄	夹紧力(N)		容许紧固扭矩(N·m)	
代码	规格											ZFB25/26	ZFB27	ZFA25/26	ZFA27
ZFB25 ZFB26 ZFB27	8	63	19	9	12	1.5	8	6	19	20	55	3100~6900	1000~2300	17	5
		80								25	72	4100~7800	1300~2500		
	10	80	25	11	16	2.5	10	8.5	23	24	70	5600~11400	1900~3900	34	10
		100								32	90	6600~12700	2200~4100		
	12	80	32	13	19	3.5	12	10	27	18	69	8400~14700	2900~5000	58	17
		100								33	89	7900~16900	2600~5600		
	16	100								43	114	9300~18500	3000~5900	115	34
		125								23	85	12700~22400	4400~7700		
		100								38	110	13100~25500	4300~8500		
		125	38	17	25	4	16	12	32	58	145	13600~28000	4400~9000		
		160													



请按图示订货

型号		L
代码	规格	
ZFB25	8	63
ZFB26	8	80

ZFB25—8—L63



未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价



交货期

6