

标准型

| 代码 | 类型 | 螺纹 | 材质 | | 表面处理 | 适用标准 |
|-------|-----|----|--------------|--------|------|----------------|
| | | | 国标 | 相当 | | |
| TBK50 | 标准型 | 粗牙 | 35 | S35C | 镀锌 | DIN 934-1987 |
| TBK51 | | | 45 | S45C | 发黑 | |
| TBK52 | | | — | — | 镀锌 | |
| TBK54 | | | 0Cr17Ni12Mo2 | SUS316 | — | |
| TBK55 | | | 0Cr18Ni9 | SUS304 | — | |
| TBK56 | | | — | — | — | |
| TBK57 | 标准型 | 粗牙 | 35(碳钢) | — | 发黑 | GB/T 6170-2015 |
| TBK67 | | | 黄铜 | — | — | DIN 934-1987 |
| TBK58 | 标准型 | 细牙 | 45 | S45C | 发黑 | GB/T 6171-2000 |
| TBK59 | | | — | — | 镀锌 | |
| TBK65 | | | 0Cr18Ni9 | SUS304 | — | |

TBK51/58

TBK52/59




TBK54/55/56/65

TBK57



TBK67



视角标准：第一视角

粗牙(DIN 934-1987)

| 型号 | M | 螺距 P | m | | S | | | e |
|--------------------------|-------|------|-----|------|-----|-------|-------|---|
| | | | max | min | max | min | min | |
| (S35C) TBK50 | 2* | 0.4 | 1.6 | 1.35 | 4 | 3.82 | 4.32 | |
| | 2.5*※ | 0.45 | 2 | 1.75 | 5 | 4.82 | 5.45 | |
| | 3 | 0.5 | 2.4 | 2.15 | 5.5 | 5.32 | 6.01 | |
| | 4 | 0.7 | 3.2 | 2.9 | 7 | 6.78 | 7.66 | |
| (S45C) TBK51 TBK52 | 5 | 0.8 | 4 | 3.7 | 8 | 7.78 | 8.79 | |
| | 6 | 1.0 | 5 | 4.7 | 10 | 9.78 | 11.05 | |
| (SUS304) TBK55 | 8 | 1.25 | 6.5 | 6.14 | 13 | 12.73 | 14.38 | |
| | 10 | 1.5 | 8 | 7.64 | 17 | 16.73 | 18.9 | |
| | 12 | 1.75 | 10 | 9.64 | 19 | 18.67 | 21.1 | |
| (黄铜) TBK67 | (16) | 2.0 | 13 | 12.3 | 24 | 23.67 | 26.75 | |
| | (20) | 2.5 | 16 | 14.9 | 30 | 29.16 | 32.95 | |
| | (24) | 3.0 | 19 | 17.7 | 36 | 35 | 39.55 | |
| | 3 | 0.5 | 2.4 | 2.15 | 5.5 | 5.32 | 6.01 | |
| (SUS316) TBK54 | 4 | 0.7 | 3.2 | 2.9 | 7 | 6.78 | 7.66 | |
| | 5 | 0.8 | 4 | 3.7 | 8 | 7.78 | 8.79 | |
| | 6 | 1.0 | 5 | 4.7 | 10 | 9.78 | 11.05 | |
| | 8 | 1.25 | 6.5 | 6.14 | 13 | 12.73 | 14.38 | |
| | 10 | 1.5 | 8 | 7.64 | 17 | 16.73 | 18.9 | |
| | 12 | 1.75 | 10 | 9.64 | 19 | 18.67 | 21.1 | |
| | 16 | 2.0 | 13 | 12.3 | 24 | 23.67 | 26.75 | |
| | 20 | 2.5 | 16 | 14.9 | 30 | 29.16 | 32.95 | |
| | 24 | 3.0 | 19 | 17.7 | 36 | 35 | 39.55 | |

粗牙(GB/T 6170-2015)

| 型号 | M | 螺距 P | m | | S | | | e |
|-------------------|-------|------|------|-------|-----|-------|-------|---|
| | | | max | min | max | min | min | |
| (SUS304) TBK56 | (2)* | 0.4 | 1.6 | 1.35 | 4 | 3.82 | 4.32 | |
| | 4* | 0.7 | 3.2 | 2.9 | 7 | 6.78 | 7.66 | |
| | 5* | 0.8 | 4.7 | 4.4 | 8 | 7.78 | 8.79 | |
| | 6* | 1.0 | 5.2 | 4.9 | 10 | 9.78 | 11.05 | |
| | 8* | 1.25 | 6.8 | 6.44 | 13 | 12.73 | 14.38 | |
| | 10* | 1.5 | 8.4 | 8.04 | 16 | 15.73 | 17.77 | |
| | 12* | 1.75 | 10.8 | 10.37 | 18 | 17.73 | 20.03 | |
| | 14* | 2.0 | 12.8 | 12.1 | 21 | 20.67 | 23.36 | |
| | 16* | 2.0 | 14.8 | 14.1 | 24 | 23.67 | 26.75 | |
| | 18* | 2.0 | 15.8 | 15.1 | 27 | 26.16 | 29.56 | |
| (碳钢) TBK57 | 20* | 2.5 | 18 | 16.9 | 30 | 29.16 | 32.95 | |
| | 22 | 2.5 | 19.4 | 18.1 | 34 | 33 | 37.29 | |
| | 24* | 3.0 | 21.5 | 20.2 | 36 | 35 | 39.55 | |
| | 27* | 3.0 | 23.8 | 22.5 | 41 | 40 | 45.2 | |
| | 30* | 3.5 | 25.6 | 24.3 | 46 | 45 | 50.85 | |
| | 33 | 3.5 | 28.7 | 27.4 | 50 | 49 | 55.37 | |
| | 36* | 4.0 | 31 | 29.4 | 55 | 53.8 | 60.79 | |
| | (42)* | 4.5 | 34 | 32.4 | 65 | 63.1 | 71.3 | |

TBK56仅适用带*号规格。 TBK57(带)规格不适用于TBK57。

带的规格不适用TBK50。 带(带)规格不适用TBK67。 带*规格不适用TBK51。

细牙(GB/T 6171-2000)

| 型号 | M | 螺距 P | m | | S | | | e |
|-----------------|-----|------|------|-------|-----|-------|-------|---|
| | | | max | min | max | min | min | |
| (S45C) TBK58 | 8 | — | 6.8 | 6.44 | 13 | 12.73 | 14.38 | |
| | 10 | 1.0 | 8.4 | 8.04 | 16 | 15.73 | 17.77 | |
| | 12 | 1.25 | 10.8 | 10.37 | 18 | 17.73 | 20.03 | |
| | 14 | — | 12.8 | 12.1 | 21 | 20.67 | 23.36 | |
| | 16 | — | 14.8 | 14.1 | 24 | 23.67 | 26.75 | |
| | 18 | 1.5 | 15.8 | 15.1 | 27 | 26.16 | 29.56 | |
| | 20 | — | 18 | 16.9 | 30 | 29.16 | 32.95 | |
| | 22 | — | 19.4 | 18.1 | 34 | 33 | 37.29 | |
| 24 | 2.0 | 21.5 | 20.2 | 36 | 35 | 39.55 | | |

细牙(GB/T 6171-2000)

| 型号 | M | 螺距 P | m | | S | | | e |
|-------------------|----|------|------|-------|-------|-------|-------|---|
| | | | max | min | max | min | min | |
| (S45C) TBK59 | 10 | 1.0 | 8.4 | 8.04 | 16 | 15.73 | 17.77 | |
| | 12 | 1.25 | 10.8 | 10.37 | 18 | 17.73 | 20.03 | |
| | 14 | — | 12.8 | 12.1 | 21 | 20.67 | 23.36 | |
| | 16 | 1.5 | 14.8 | 14.1 | 24 | 23.67 | 26.75 | |
| (SUS304) TBK65 | 10 | 1.0 | 8.4 | 8.04 | 16 | 15.73 | 17.77 | |
| | 12 | 1.25 | 10.8 | 10.37 | 18 | 17.73 | 20.03 | |
| | 14 | — | 12.8 | 12.1 | 21 | 20.67 | 23.36 | |
| | 16 | 1.5 | 14.8 | 14.1 | 24 | 23.67 | 26.75 | |
| 20 | — | 18 | 16.9 | 30 | 29.16 | 32.95 | | |



| 型号 | M |
|-------|----|
| TBK54 | 20 |
| TBK54 | 24 |



| 优惠价 |
|--------------|
| 数量 1~4 5~ |
| 价格 100% 另行报价 |




交货期
5



交货期
7

左旋螺纹

| 代码 | 类型 | 螺纹 | 材质 | | 表面处理 |
|-------|----------|----|----------|--------|------|
| | | | 国标 | 相当 | |
| TBK25 | 左旋 螺纹 | 粗牙 | 碳钢 | — | 镀锌 |
| TBK26 | | | — | — | 发黑 |
| TBK27 | | 细牙 | 0Cr18Ni9 | SUS304 | — |
| TBK28 | | | — | — | — |



视角标准：第一视角

| 型号 | M | 螺距 P | m | | S | | | e | |
|-------------------------------|-----|------|-----|----|-----|------|-----|-------|-------|
| | | | 粗牙 | 细牙 | max | min | max | | min |
| 粗牙 TBK25 TBK26 TBK27 | 4 | 0.7 | — | — | 3.2 | 2.9 | 7 | 6.78 | 7.66 |
| | 5 | 0.8 | — | — | 4 | 3.7 | 8 | 7.78 | 8.79 |
| | 6 | 1.0 | — | — | 5 | 4.7 | 10 | 9.78 | 11.05 |
| | 8* | 1.25 | 1.0 | — | 6.5 | 6.14 | 13 | 12.73 | 14.38 |
| | 10* | 1.5 | — | — | 8 | 7.64 | 17 | 16.73 | 18.9 |
| | 12* | 1.75 | — | — | 10 | 9.64 | 19 | 18.67 | 21.1 |
| 细牙 TBK28 | 16* | 2.0 | 1.5 | — | 13 | 12.3 | 24 | 23.67 | 26.75 |
| | 18* | 2.5 | — | — | 15 | 14.3 | 27 | 26.16 | 29.56 |
| | 20* | 2.5 | 2.0 | — | 16 | 14.9 | 30 | 29.16 | 32.95 |
| | 24* | 3.0 | — | — | 19 | 17.7 | 36 | 35 | 39.55 |

TBK25/26/28仅适用带*号规格。



请按图示订货 TBK25—M4



| 优惠价 |
|--------------|
| 数量 1~49 50~ |
| 价格 100% 另行报价 |



交货期
7