

代码	类型		材质	
			国际	相当
BPT01	带侧板内圈型	圆柱型	GCr15	SUJ2
BPT02			9Cr18M0	SUS440C
BPT21	球面型	球面型	GCr15	SUJ2
BPT22			9Cr18M0	SUS440C


圆柱型D公差：

D	公差
16	$0_{-0.008}^0$
19~30	$0_{-0.009}^0$
32~47	$0_{-0.011}^0$
52~80	$0_{-0.013}^0$
85~90	$0_{-0.015}^0$


球面型D公差： $0_{-0.05}^0$




圆柱型
BPT01/02



球面型
BPT21/22



❶ 不承诺品牌。



型号		密封圈	drf6	D	B	r	基本额定负荷(KN)				极限转速 (rpm)	重量 (g)
							Cr(动)		Cor(静)			
代码	规格						钢	不锈钢	钢	不锈钢		
圆柱型 BPT01 BPT02	5		7	16	7.8	0.5	2.71	2.17	23.9	19.12	16800	8.9
	6		10	19	9.8	0.5	4.16	3.33	45.5	36.4	14000	13.9
	8		12	24		1	5.65	4.52	58.9	47.12	10500	23.5
	10		14	30		1	9.79	7.83	96.8	77.44	8400	42.5
	12		16	32	11.8	1	10.5	8.4	10.9	8.72	7000	49.5
	15		20	35		1	12.4	9.92	14.3	11.44	5600	50
球面型 BPT21 BPT22	17	—	22	40		1.5	17.6	14.08	20.9	16.72	4940	90
	20	(无密封圈)	25	47	15.8	1.5	19.4	15.52	24.5	19.6	4200	135
	25		30	52		1.5	20.8	16.64	28.4	22.72	3360	152
	30		38	62		1.5	30.5	24.4	45.4	36.32	2800	255
	35		42	72		1.5	32.4	25.92	50.6	40.48	2400	375
	40		50	80	19.8	1.5	35.9	28.72	54.4	43.52	2100	420
	45		55	85		2	37.4	29.92	66.4	53.12	1870	460
	50		60	90		2	38.9	31.12	71.7	57.36	1680	500

❶ 上表中极限转速数值仅适用润滑脂型号，若采用油润滑的型号极限转速为上述数值的160%左右。

❷ 规格5~8为尼龙保持架，规格8以上为钢制保持架。



请按图示订货

型号		密封圈	dr
代码	规格		
BPT01	5	—	7
BPT02	6	(无密封圈)	10

BPT01—5



未标价(元)

优惠价		
数量	1~9	10~
价格	100%	另行报价



交货期
5