

ISO标准矩形弹簧


◀ 中载荷弹簧(蓝色)

代码	类型	材质	最大压缩量
YSIM	中载荷型	SWOSC-V	L×37.5%

□ L尺寸公差

L	公差
89以下	±1
102以上	±1%

- ① 载荷(±10%)
- ① 直角度(3°以下)
- ① 负载(N)=弹簧常数(N/mm)×压缩量
- ① 理论使用次数: 30万次(L×25%为100万次)
- ① 弹簧颜色和圈数可能会因生产批次不同而异, 但产品性能均符合标准, 不影响使用!
- ① 参考标准 ISO 10243-2019



型号		轴径 D _d	弹簧常数 N/mm	使用方法 30万次 F=L×37.5%			
代码	孔径D			长度L	Fmm	负载N	
YSIM	10	5	25	16	9.4	150.4	
			32	13	12	156	
			38	11.9	14.2	169	
			44	10.3	16.5	170	
			51	8.9	19.1	170	
			64	7.5	24	180	
	76	6.2	28.5	176.7			
	305	1.6	114	182.4			
	25	30	9.4	282			
	32	24.8	12	297.6			
	38	21.4	14.2	303.9			
	44	18	16.5	297			
	12.5	6.3	6.3	51	15.5	19.1	296.1
	64			12.1	24	290.4	
	76			10.2	28.5	290.7	
	89			8.4	33.3	279.7	
	305			2.4	114	273.6	
	25			49.4	9.4	464.4	
	32	38.5	12	462			
	38	33.9	14.2	481.4			
	44	30	16.5	495			
	51	26.4	19.1	504.2			
	16	8	8	64	20.5	24	492
	76			17.8	28.5	507.3	
	89			15.2	33.3	506.2	
	102			13.5	38.2	515.7	
	305			4.3	114	490.2	
	25			98	9.4	921.2	
	32	72.6	12	871.2			
	38	56	14.2	795.2			
	44	47.5	16.5	783.8			
	51	41.7	19.1	796.5			
	64	32.3	24	775.2			
	76	25.1	28.5	715.4			
	20	10	10	89	22	33.3	732.6
	102			19.8	38.2	756.4	
	115			18.1	43.1	780.1	
	127			16.6	47.6	790.2	
	139			15.1	52.1	786.7	
	152			13.2	57	752.4	
	305	6.1	114	695.4			
	25	157	9.4	1476			
	32	118	12	1416			
	38	93	14.2	1321			
	44	80.8	16.5	1333			
	51	68.6	19.1	1310			
	64	53	24	1272			
	25	12.5	12.5	76	43.2	28.5	1231
89	38.2			33.3	1272		
102	33			38.2	1261		
115	28			43.1	1207		
127	25.9			47.6	1233		
139	23.2			52.1	1209		
152	20.8	57	1186				
178	17.8	66.7	1187				

型号		轴径 D _d	弹簧常数 N/mm	使用方法 30万次 F=L×37.5%			
代码	孔径D			长度L	Fmm	负载N	
YSIM	25	12.5	203	15.8	76.1	1202	
			305	10.2	114	1163	
			38	185	14.2	2627	
			44	158	16.5	2607	
			51	134	19.1	2559	
			64	99	24	2376	
	76	80.5	28.5	2294			
	89	69.1	33.3	2301			
	102	58.8	38.2	2246			
	32	16	16	115	51.5	43.1	2220
	127			44.8	47.6	2132	
	139			42.3	52.1	2204	
	152			37.8	57	2155	
	178			32.5	66.7	2168	
	203			28.9	76.1	2199	
	254	22.2	95.2	2113			
	305	18.3	114	2086			
	51	182	19.1	3476			
	64	140	24	3360			
	76	108	28.5	3078			
	89	90.7	33.3	3020			
	102	81	38.2	3094			
	115	71.8	43.1	3095			
	40	20	20	127	62.7	47.6	2985
	139			57.5	52.1	2996	
	152			51.6	57	2941	
	178			44.1	66.7	2941	
	203			36.7	76.1	2793	
	254			30.1	95.2	2866	
	305	24.6	114	2804			
	64	209	24	5016			
	76	168	28.5	4788			
	89	140	33.3	4662			
	102	119	38.2	4546			
	115	106	43.1	4569			
	50	25	25	127	97	47.6	4617
	139			87	52.1	4533	
	152			80	57	4560	
	178			69.5	66.7	4636	
	203			59.8	76.1	4551	
	229			50.9	85.8	4367	
	254	46	95.2	4379			
	305	38.6	114	4400			
	76	320	28.5	9120			
	89	260	33.3	8658			
	102	221	38.2	8442			
	115	187	43.1	8060			
	127	168	47.6	7997			
63	38	38	152	136	57	7752	
178			114	66.7	7604		
203			100	76.1	7610		
229			89.2	85.8	7653		
254			78.4	95.2	7464		
305			64.7	114	7376		



型号	孔径D	长度L
YSIM	10	25
		32

请按图示订货 YSIM-D10-L25



优惠价
数量 1~9 10~
价格 100% 另行报价

未税价(元)



交货期
7