


# 吊环螺钉/吊环螺母



## 吊环螺钉

代码	类型	材质		表面处理	
		国标	相当		
TBF01	吊环螺钉	带螺母	Q235	SS400	镀锌
TBF02		无螺母	0Cr18Ni9	SUS304	—
TBF03		带螺母	Q235	SS400	镀锌
TBF04	无螺母	0Cr18Ni9	SUS304	—	

带螺母  
TBF01  
TBF02



无螺母  
TBF03  
TBF04



本产品适用标准: GB/T 825-1988  
DIN 580-2010  
JIS B 1168-1994

视角标准: 第一视角

型号	M	载荷(T)	螺距P	a		b		D		E		H		V	螺帽	
				TBF01/03	TBF02/04	TBF01/03	TBF02/04	TBF01/03	TBF02/04	TBF01/03	TBF02/04	TBF01/03	TBF02/04		B	T
带螺母	6	0.14	1	36.3	28	19.7	15.7	8.3	6.3	20.3	15.3	37.5	28	13	10	5
	8			36.3	36.3	19.7	19.7	9.3	20.3	20.3	37.5	37.5	13	6.5		
	10			45.3	45.3	24.7	24.7	10.3	10.3	25.3	25.3	46.5	17	8		
无螺母	12	0.34	1.75	54.3	54.3	29.7	29.7	12.3	12.3	30.3	30.3	55	55	20.5	19	10
	14*			63	—	35	—	14	—	35	—	62	—	21	14	
	16			63.3	63.3	34.7	34.7	12.5	12.5	35.3	35.3	64.5	64.5	27	24	13
20	1.2	2.5	72.3	72.3	39.7	39.7	16.3	16.3	40.3	40.3	71	71	30	30	17	



① 带\*规格不适用TBF02/04。

## 吊环螺母-标准型/高脚型



代码	类型	材质		表面处理
		国标	相当	
TBF21	标准型	Q235	SS400	镀锌
TBF22	高脚型	0Cr18Ni9	SUS304	—

① TBF21/22 适用标准: DIN 582-2010

标准型  
TBF21  
TBF22



高脚型  
TBF26



视角标准: 第一视角

## 标准型

型号	M	a	b	H	E	K
(SS400)	8	36	20	36	20	8.5
	10	45	25	45	25	10
(SUS304)	12	54	30	53	30	11
	16	63	35	62	35	13
	20	72	40	71	40	16

## 高脚型

型号	M	a	b	d	H	D	K
TBF26	6	26	16	5.3	33	12	12
	8	31.5	20	5.9	40	15.3	14
	10	40.5	25	7.7	48	19.4	15
	12	48	30	9.4	60	23.7	21.5
	16	60	35	12.2	72	28	25
	20	68.5	40	14.8	83	33.6	30
	24	89	50	19.4	108	37.3	44



请按图示订货

型号	M	a
(TBF22)	8	36
TBF22	10	45
TBF21—M8		



未税价(元)

### 优惠价

数量	1~499	500
价格	100%	另行报价

① TBF26



未税价(元)

### 优惠价

数量	1~99	100~
价格	100%	另行报价

① 其余




### 交货期

7

## 吊环螺母-环型

代码	类型	材质		表面处理
		国标	相当	
TBF31	环型	0Cr18Ni9	SUS304	—



视角标准: 第一视角

型号	M	a	d	H	D	K
TBF31	10	55	7	43	18.5	12.1
	12	65	9	52	21	14.1
	14				23.2	15
	16	73	10	55.2	25.5	15.2
	20	82		67.5	31.8	19.8
	24	95.5	12	80	41.8	23.5



请按图示订货

型号	M
(TBF32)	10
TBF31—M10	12



未税价(元)

### 优惠价

数量	1~100	101~
价格	100%	另行报价



### 交货期

7