


代码	类型	螺纹	材质		硬度	表面处理	强度等级
			国标	相当			
TAH02	全牙	粗牙	10B21		—	镀蓝白锌	4.8
TAH03			8.8				
TAH01			35CrMo	SCM435	32~39HRC	发黑	8.8
TAH51			0Cr18Ni9	SUS304			A2-70
TAH52			0Cr17Ni12Mo2	SUS316	—	—	A4-70
TAH55			—	H62黄铜	—	—	—

TAH01

TAH51



① 强度等级是指螺栓的抗拉强度。

例：8.8

表示屈服点或耐力的最小值为抗拉强度的80%  
表示抗拉强度的最小值为800N/mm<sup>2</sup>

例：A2-70

表示抗拉强度的最小值为700N/mm<sup>2</sup>  
钢种分类为A2(奥氏体不锈钢)

① TAH01/51/52/55 适用标准：DIN 933-1987  
GB/T 5783-2016  
ISO 4017-2011

① TAH02 适用标准：GB/T 30-1976  
① TAH03 适用标准：GB/T 5783-2016

视角标准：第一视角

① 10B21(强度等级4.8级)

代码	型号	L	P 螺距	S	K
TAH02	4	6 8 10 12 16 20 25 30 35 40	0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45 50	0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60	1.0	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 100	1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 100	1.75	19	7.5
	14	30 35 40 45 50 55 60 65 70 80 90 100	2.0	22	8.8
	16	30 35 40 45 50 55 60 65 70 75 80 90 100	2.0	24	10
	18	40 45 50 55 60 65 70 75 80 85 90 100	2.5	27	11.5
	20	40 45 50 55 60 65 70 75 80 85 90 100	2.5	30	12.5
	22	50 55 60 70 75 80 90 100	3.0	34	14
	24	50 60 70 75 80 90 100	3.0	36	15

① 10B21(强度等级8.8级)

代码	型号	L	P 螺距	S	K
TAH03	4	8 10 12 14 16 20 25 30 35 40	0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45 50	0.8	8	3.5
	6	8 10 12 16 20 25 30 35 40 45 50 55 60 70 80 90 100	1.0	10	4
	8	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 100 110 120 130	1.5	16	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 100 110 120 130	1.75	18	7.5
	14	30 35 40 45 50 55 60 65 70 75 80 90 100 110 120 130	2.0	21	8.8
	16	30 35 40 45 50 55 60 65 70 75 80 85 90 100 110 120 130	2.0	24	10
	18	40 45 50 55 60 65 70 75 80 90 100 110 120 130	2.5	27	11.5
	20	40 45 50 55 60 65 70 75 80 85 90 100 110 120 130	2.5	30	12.5
	22	50 55 60 65 70 75 80 85 90 100 110 120 130	3.0	34	14
	24	50 55 60 65 70 75 80 85 90 100 110 120 130	3.0	36	15
	27	60 70 80 90 100 110 120 130	3.5	41	17
	30	70 80 90 100 110 120 130	3.5	46	18.7
36	70 80 90 100 110 120 130	4.0	55	22.5	

① SCM435

代码	型号	L	P 螺距	S	K
TAH01	5	8 10 12 16 20 25 30 35 40 45	0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75	1.0	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100 110 120 130	1.75	19	7.5
	16	30 35 40 45 50 55 60 65 70 75 80 90 100 110 120 130	2.0	24	10
	20	60 90 100 110 120 130 140 150 160 180 190 200 220 350	2.5	30	12.5

① SUS304

代码	型号	L	P 螺距	S	K
TAH51	4	8 10 12 16 20 25 30 35 40 45	0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45 50	0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75	1.0	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.75	19	7.5

① SUS316

代码	型号	L	P 螺距	S	K
TAH52	4	8 10 12 16 20 25 30 35 40 45	0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45	0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75	1.0	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100	1.75	19	7.5

① H62黄铜

代码	型号	L	P 螺距	S	K
TAH55	6	10 12 16 20 25 30	1.0	10	4
	8	20 25 30 35 40 50 60	1.25	13	5.3
	10	20 25 30 35 40 50 60	1.5	17	6.4
	12	30 35 40 45 50 60	1.75	19	7.5

① SCM435

代码	型号	L
TAH01	M5	L10



未税价(元)

● 优惠价

数量 1~45 46~  
价格 100% 另行报价



交货期

3



交货期

7

① TAH01/51

① 其余

请按图示订货