

导热硅胶垫

◀ 方形

减震防护类

G3


代码	类型	材质	颜色
NFD01			灰白色
NFD02			深灰色
NFD03			浅蓝色
NFD04	方形	导热硅胶	草绿色
NFD05			深蓝色
NFD06			土黄色
NFD07			暗红色
NFD08			浅灰色

□ A/B公差

A·B	公差
200以下	±1.0
201~400	±2.0

□ T公差

T	公差
0.5~2	±0.10
3~5	±0.20



型号		最小单位1		硬度 (邵氏)	比重 g/cm ³	撕裂强度 KN/m	耐温范围 °C	击穿电压 KV	体积电阻 Ω.cm	导热系数 W/m.k	防火性能
代码	T	A	B								
NFD01				C30	2.0	≥0.8	-40~200	≥4	1.1×10 ¹⁶	1.2	V-0
NFD02	0.5				2.4 ±0.1	≥0.8				1.5 ±0.1	
NFD03	1				2.65	≥0.65				2.0	
NFD04	2	10~400	10~200		2.6	≥0.6				2.5	
NFD05	3			3.0 ±0.2							
NFD06	4			C40	3.15 ±0.2	≥0.45	4.0				
NFD07	5				3.35	≥0.35	5.0				
NFD08					3.5	≥0.3	6.0 ±0.3				



型号		最小单位1		硬度 (邵氏)
代码	T	A	B	
NFD01	1			C30
NFD02	2	10~400	10~200	

NFD02 — T2 — A100 — B100 — C30



● 优惠价	
数量	1~9 10~
价格	100% 另行报价



交货期	9
-----	---

