



# 精密型 耐热快速接头

- 直接头
- 内六角孔直接头
- 外螺纹

## 直接头

| 代码 | 类型 | 材质 |     |       | 表面处理 |
|----|----|----|-----|-------|------|
|    |    | 主体 | 螺纹部 | 密封部材料 | 主体   |

J-XP01 外螺纹 直接头 黄铜 黄铜 耐热NBR 镀镍



视角标准：第一视角

| 型号     | 公称 | R  | D    | E  | B    | C1   | C2   | A   | L    | S  | 喷嘴  | 有效断面     | 重量  |
|--------|----|----|------|----|------|------|------|-----|------|----|-----|----------|-----|
| 代码     | d  | 型号 |      |    |      |      |      |     |      |    | 直径  | 面积 (mm²) | (g) |
| J-XP01 | 4  | M5 | M5   |    | 22.5 |      |      | 2.8 | 19.8 | 10 | 2.4 | 2        | 8   |
|        |    | 1  | R1/8 | 6  | 23.7 | 17.6 | 15   | 8   | 19.7 | 10 | 3   | 4.5      | 10  |
|        |    | 2  | R1/4 |    | 25.2 |      |      | 11  | 19.2 | 14 |     |          | 19  |
|        | 6  | M5 | M5   |    | 24.4 |      |      | 2.8 | 21.6 | 12 | 2.4 | 2        | 12  |
|        |    | 1  | R1/8 | 8  | 24.8 | 19.5 | 16   | 8   | 20.8 | 14 | 5   | 11       | 17  |
|        |    | 2  | R1/4 |    | 26.2 |      |      | 11  | 20.1 | 14 |     |          | 31  |
|        | 8  | 3  | R3/8 |    | 27   |      |      | 12  | 20.6 | 17 |     |          | 18  |
|        |    | 1  | R1/8 |    | 29.9 |      |      | 8   | 25.9 | 14 | 6   |          | 19  |
|        |    | 2  | R1/4 | 10 | 32.8 | 20.2 | 17   | 11  | 22.6 | 17 | 7   | 20       | 29  |
|        | 10 | 3  | R3/8 |    | 27.5 |      |      | 12  | 21.2 | 17 | 7   |          | 30  |
|        |    | 1  | R1/8 |    | 32.8 |      |      | 8   | 28.8 | 17 | 6   | 23       | 27  |
|        |    | 2  | R1/4 | 12 | 32.3 | 23.2 | 19.5 | 11  | 26.3 | 17 | 8.5 |          | 32  |
| J-XP01 | 12 | 3  | R3/8 |    | 31.8 |      |      | 12  | 25.5 | 17 | 9   | 35       | 54  |
|        |    | 4  | R1/2 |    | 32.9 |      |      | 15  | 24.7 | 21 | 9   |          | 51  |
|        |    | 2  | R1/4 |    | 38.9 |      |      | 11  | 32.9 | 17 | 8.5 | 47       | 45  |
|        | 14 | 3  | R3/8 |    | 34.9 | 26.3 | 23   | 12  | 28.6 | 21 | 11  | 50       | 59  |
|        |    | 4  | R1/2 |    | 36.9 |      |      | 15  | 28.7 |    |     |          |     |



请按图示订货

| 型号 | 公称 | R  |
|----|----|----|
| 代码 | d  | 型号 |

J-XP01-d4-M5



未税价(元)

| 数量 | 1~29 | 30~  |
|----|------|------|
| 价格 | 100% | 另行报价 |





交货期

1

## 内六角孔直接头

| 代码 | 类型 | 材质 |     |       | 表面处理 |
|----|----|----|-----|-------|------|
|    |    | 主体 | 螺纹部 | 密封部材料 | 主体   |

J-XP11 外螺纹 内六角孔直接头 黄铜 黄铜 耐热NBR 镀镍



视角标准：第一视角

| 型号     | 公称 | R    | D    | P <sub>1</sub> | P <sub>2</sub> | B    | C <sub>1</sub> | C <sub>2</sub> | A    | L    | S    | 喷嘴<br>直径 | 有效新面积<br>(mm <sup>2</sup> ) | 重量<br>(g) |    |
|--------|----|------|------|----------------|----------------|------|----------------|----------------|------|------|------|----------|-----------------------------|-----------|----|
| 代码     | d  | 型号   |      |                |                |      |                |                |      |      |      |          |                             |           |    |
| J-XP11 | 4  | M5   | M5   |                |                | 22.4 |                |                | 2.8  | 19.7 |      |          | 2                           | 7         |    |
|        |    | 1    | R1/8 | 6              | 9.7            |      | 22.7           | 17.6           | 15   | 8    | 18.7 | 2.5      | 2.6                         | 9         |    |
|        | 2  | R1/4 |      | 13.7           |                |      |                |                | 11   | 16.7 |      |          | 5.2                         | 15        |    |
|        | 6  | M5   | M5   |                |                | 23.8 |                |                | 2.8  | 21   | 2.5  | 2.6      | 2                           | 9         |    |
|        |    | 1    | R1/8 | 8              | 11.8           |      | 24.6           |                |      | 8    | 20.6 |          |                             | 11        | 11 |
|        |    | 2    | R1/4 |                | 13.7           | 11.8 |                | 19.5           | 16   | 11   | 17.7 | 4        | 4.2                         | 11        | 15 |
|        | 3  | R3/8 |      | 16.8           |                | 23.8 |                |                | 12   | 17.4 |      |          |                             | 24        |    |
|        | 8  | 1    | R1/8 |                |                | 27.9 |                |                | 8    | 23.9 | 5    | 5.3      |                             | 13        | 13 |
|        |    | 2    | R1/4 | 10             | 13.7           | 27.1 |                | 20.2           | 17   | 11   | 21.1 |          | 6.3                         | 17        | 16 |
|        |    | 3    | R3/8 |                | 16.8           |      | 24.2           |                |      | 12   | 17.9 | 6        |                             | 23        | 23 |
|        | 10 | 1    | R1/8 |                |                | 32.8 |                |                | 8    | 28.8 | 5    | 5.3      | 23                          | 25        | 25 |
|        |    | 2    | R1/4 | 12             | 17.5           |      | 32.3           |                |      | 11   | 26.3 |          |                             | 29        | 29 |
|        |    | 3    | R3/8 |                |                | 31.8 |                | 23.2           | 19.5 | 12   | 25.4 | 6        | 6.3                         | 17        | 35 |
|        | 12 | 4    | R1/2 |                | 20.8           |      | 32.8           |                |      | 15   | 24.6 |          |                             | 54        | 54 |
|        |    | 2    | R1/4 |                |                | 38.9 |                |                |      | 11   | 32.9 | 6        | 6.3                         | 20        | 44 |
|        |    | 3    | R3/8 | 14             | 20.8           | 20.8 | 34.9           | 26.3           | 23   | 12   | 28.6 |          |                             | 45        | 45 |
| 4      |    | R1/2 |      |                | 36.9           |      |                |                | 15   | 28.7 | 8    | 8.4      | 40                          | 60        |    |



请按图示订货

| 型号 | 公称 | R  |
|----|----|----|
| 代码 | d  | 型号 |

J-XP11-d4-M5



未税价(元)

| 数量 | 1~29 | 30~  |
|----|------|------|
| 价格 | 100% | 另行报价 |



交货期

1

气动接头

D8