


代码	类型	介质	调节阀
BMZ76	面板式	气体	带阀
BMZ77			不带阀
BMZ78		液体	带阀
BMZ79			不带阀


❗ (内螺纹接口型)安装螺纹接头时,需用扳手固定住接口外部的扁位,以防在安装过程中将主体螺纹处拧裂。

带阀
BMZ76/78

规格: 4




规格: 6




不带阀
BMZ77/79

规格: 4



规格: 6



视角标准: 第一视角

● 介质: 气体

代码	规格	测量范围 (L/min)	连接方式	精度	A	B	C	D	M	F
带阀 BMZ76 不带阀 BMZ77	4	0.1(0.1~1)	Ø6快插	±4%	94	27	21	14	—	70
		0.2(0.2~2)								
		0.25(0.25~2.5)								
		1(1~4)								
		1A(1~10)								
	6	1B(1~12)	PT1/4" (内螺纹)	±4%	102	30	25	18	M18×1.5	76
		0.5(0.5~5)								
		1(1~10)								
		2(2~20)								
		4(4~40)								
		5(5~50)								
		6(6~60)								
		10(10~100)								

● 介质: 液体

代码	规格	测量范围 (L/min)	连接方式	精度	A	B	C	D	M	F
带阀 BMZ78 不带阀 BMZ79	4	6(6~60ML/min)	Ø6快插	±4%	94	27	21	14	—	70
		8(8~80ML/min)								
		10(10~100ML/min)								
		40(40~400ML/min)								
		2(2~20LPH)	PT1/4" (内螺纹)	±4%	102	30	25	18	M18×1.5	76
	6	4(4~40LPH)								
		6(6~60LPH)								
		10(10~100LPH)								

● 介质: 气体

代码	规格	测量范围 (L/min)
BMZ76	4	0.1(0.1~1)
BMZ77	4	0.2(0.2~2)

BMZ76—4—0.2

● 介质: 液体

代码	规格	测量范围 (L/min)
BMZ78	4	6(6~60ML/min)
BMZ79	4	8(8~80ML/min)

BMZ78—4—8



请按图示订货



未税价(元)

● 优惠价

数量	1~99	100~
价格	100%	另行报价



交货期

8