


# Y形绝缘压着端子

◀ SV系列·紫铜

代码	类型	材质		表面处理
		端头	绝缘	
ZNA47	Y形绝缘压着端子	紫铜	PVC	镀锡



视角标准：第一视角

销售方式	每袋数量
袋	见参数表

型号 代码	压接规格	螺丝规格	颜色	包装 (PCS/袋)	适用电线规格		外形尺寸(mm)							电流 (max)	适用压接钳 代码	
					截面积 mm <sup>2</sup>	美标线规 AWG	d <sub>2</sub>	W	F	L	H	d <sub>1</sub>	D			T
ZNA47	1.25	3	R(红) BL(蓝) BK(黑) Y(黄)	100	0.5~1.5	22~16	3.2	5.7	6.5	21.5	10.5	1.7	4.4	0.7	19A	ZI14 (详见怡合达 电商平台)
		3.5					5.7									
		4					6.4									
		5					8.1									
		6					9.5									
		8					12	11								
	2	3	3.2	5.7	1.5~2.5	16~14	4.3	6.4	6.5	21.5	10.5	2.3	4.7	0.8	27A	
		3.5	3.7	5.7												
		4	4.3	6.4												
		5	5.3	8.1												
		6	6.4	9.5												
		8	8.4	13.5			11.5	27								
	3.5	3	3.2	5.7	2.5~4	14~12	3.7	5.7	7	25.3	13	2.9	6.2	1	37A	
		3.5	3.7	5.7												
		4	4.3	8												
		5	5.3	8.3			25.5									
		6	6.4	12			9.5	28.5								
		8	8.4	14			11.5	30.7								
	5.5	3.5	3.7	5.7	4~6	12~10	4.3	8.3	7.5	26	13.5	3.4	6.5	1	48A	
		4	4.3	8.3			25.5									
		5	5.3	9			26									
		6	6.4	9			26									
		8	8.4	14			11.5	30.7								
		10	10	14			11.5	30.7								
8	4	4.3	7.2	6~10	8	4.3	7.2	7.2	28.3	16	4.5	8	1.2	62A		
	5	5.3	9			8.1	30									
	6	6.4	12			8.3	31.3									
	8	8.4	13.8			10.7	32.9									
	10	10	14			11.5	30.7									
	12	12	14			11.5	30.7									
14	4	4.3	11	10~16	6	4.3	11	9.5	37.5	23	5.8	10.5	1.4	88A		
	5	5.3	11			9.5	39.3									
	6	6.4	12			9.5	40.2									
	8	8.4	13.8			10.7	39.5									
	10	10	14			11.5	30.7									
	12	12	14			11.5	30.7									
22	5	5.3	11	16~25	4	5.3	11	9.5	39.3	24	7.7	13	1.8	115A		
	6S	6.4	12			9.5	40.2									
	6	6.4	12			9.5	40.2									
	8	8.4	13.8			10.7	39.5									



型号		螺丝规格	颜色	包装 (PCS/袋)
代码	压接规格			
ZNA47	1.25	3	R(红)	100
	2	3.5	BL(蓝)	1000

ZNA47-1.25-3-R-1000