


| 代码 | 类型 | 材质 | |
|---------|-------|--------|--------|
| | | 底座 | 螺杆 |
| Y-QBC01 | 带防滑槽型 | SUS304 | SUS304 |

- 特点:
- 用于外装, 表面光亮。
 - 不锈钢材质, 防锈、耐腐蚀。
 - 耐高温范围: -35°C~80°C, 耐高温性能好。
- 用途:
- 医疗设备, 半导体设备, 工业机械。
- 注意:
- ① 由于市面上钢材位为5mm一个梯度, 且存在公差, 因此车制底座公差-2~0mm均为合理范围。
 - ② 请根据脚杯螺杆尺寸M进行相关配件选择, 详见脚杯可选配件汇总。



视角标准: 第一视角

| 型号 | | | | | | | | | 型号 | | | | | | | | | | |
|---------|------|------|------|----|----|------|----------------|---------|---------------|-----|----|-----|------|------|------|------|----------------|---------|---------------|
| 代码 | D | M | L | S | H | V | V ₁ | 承载 (kg) | 参考重量 (kg/pcs) | 代码 | D | M | L | S | H | V | V ₁ | 承载 (kg) | 参考重量 (kg/pcs) |
| Y-QBC01 | 40 | 8 | 50 | 14 | | 6 | 6 | 400 | 0.2 | 100 | 16 | 100 | 24 | 10 | 13 | 1800 | | | 1.23 |
| | | | 75 | | | | | | 1.25 | | | | | | | | | | |
| | | | 100 | | | | | | 1.27 | | | | | | | | | | |
| | | 125 | 1.29 | | | | | | | | | | | | | | | | |
| | | 50 | 1.31 | | | | | | | | | | | | | | | | |
| | | 75 | 1.33 | | | | | | | | | | | | | | | | |
| | 12 | 100 | 1.35 | | | | | | | | | | | | | | | | |
| | | 125 | 1.32 | | | | | | | | | | | | | | | | |
| | | 150 | 1.35 | | | | | | | | | | | | | | | | |
| | | 50 | 0.45 | | | | | | | | | | | | | | | | |
| | | 75 | 0.46 | | | | | | | | | | | | | | | | |
| | | 100 | 0.47 | | | | | | | | | | | | | | | | |
| | 60 | 12 | 125 | 19 | 8 | 10 | 800 | 0.48 | 200 | 20 | 30 | 26 | 13 | 16 | 2500 | | | | 1.42 |
| | | | 150 | | | | | 1.46 | | | | | | | | | | | |
| | | | 75 | | | | | 1.5 | | | | | | | | | | | |
| | | 100 | 1.53 | | | | | | | | | | | | | | | | |
| | | 125 | 1.93 | | | | | | | | | | | | | | | | |
| | | 150 | 1.98 | | | | | | | | | | | | | | | | |
| | 16 | 125 | 2.03 | | | | | | | | | | | | | | | | |
| | | 150 | 2.15 | | | | | | | | | | | | | | | | |
| | | 75 | 0.49 | | | | | | | | | | | | | | | | |
| | | 100 | 0.51 | | | | | | | | | | | | | | | | |
| | | 125 | 0.51 | | | | | | | | | | | | | | | | |
| | | 150 | 0.53 | | | | | | | | | | | | | | | | |
| 20 | 100 | 0.55 | | | | | | | | | | | | | | | | | |
| | 125 | 0.74 | | | | | | | | | | | | | | | | | |
| | 150 | 0.76 | | | | | | | | | | | | | | | | | |
| | 75 | 0.78 | | | | | | | | | | | | | | | | | |
| | 100 | 0.8 | | | | | | | | | | | | | | | | | |
| | 125 | 0.82 | | | | | | | | | | | | | | | | | |
| 80 | 16 | 150 | 24 | 10 | 13 | 1400 | 0.82 | 300 | 24 | 30 | 13 | 16 | 19 | 2800 | | | | 2.14 | |
| | | 75 | | | | | 2.17 | | | | | | | | | | | | |
| | | 100 | | | | | 2.22 | | | | | | | | | | | | |
| | 125 | 2.28 | | | | | | | | | | | | | | | | | |
| | 150 | 2.31 | | | | | | | | | | | | | | | | | |
| | 75 | 0.78 | | | | | | | | | | | | | | | | | |
| 20 | 100 | 0.82 | | | | | | | | | | | | | | | | | |
| | 125 | 0.84 | | | | | | | | | | | | | | | | | |
| | 150 | 0.89 | | | | | | | | | | | | | | | | | |
| | 75 | 0.82 | | | | | | | | | | | | | | | | | |
| | 100 | 0.87 | | | | | | | | | | | | | | | | | |
| | 125 | 0.87 | | | | | | | | | | | | | | | | | |
| 24 | 100 | 0.89 | | | | | | | | | | | | | | | | | |
| | 125 | 0.89 | | | | | | | | | | | | | | | | | |
| | 150 | 0.94 | | | | | | | | | | | | | | | | | |
| | 200 | 0.92 | | | | | | | | | | | | | | | | | |
| | 100 | 0.87 | | | | | | | | | | | | | | | | | |
| | 125 | 0.87 | | | | | | | | | | | | | | | | | |
| 100 | 20 | 150 | 30 | 23 | 13 | 16 | 1800 | 0.89 | 100 | 24 | 36 | 29 | 16 | 19 | 3000 | | | | 2.16 |
| | | 200 | | | | | | 2.2 | | | | | | | | | | | |
| | | 250 | | | | | | 2.25 | | | | | | | | | | | |
| | 300 | 2.28 | | | | | | | | | | | | | | | | | |
| | 75 | 0.82 | | | | | | | | | | | | | | | | | |
| | 100 | 0.87 | | | | | | | | | | | | | | | | | |
| 125 | 0.87 | | | | | | | | | | | | | | | | | | |
| 24 | 100 | 0.89 | | | | | | | | | | | | | | | | | |
| | 125 | 0.89 | | | | | | | | | | | | | | | | | |
| | 150 | 0.94 | | | | | | | | | | | | | | | | | |
| | 200 | 0.92 | | | | | | | | | | | | | | | | | |
| | 100 | 0.87 | | | | | | | | | | | | | | | | | |
| | 125 | 0.87 | | | | | | | | | | | | | | | | | |
| 300 | 30 | 150 | 36 | 16 | 19 | 2200 | 0.89 | 300 | 30 | 46 | 24 | 24 | 3200 | | | | | 2.24 | |
| | | 200 | | | | | 2.32 | | | | | | | | | | | | |
| | | 250 | | | | | 2.36 | | | | | | | | | | | | |
| | 300 | 2.42 | | | | | | | | | | | | | | | | | |
| | 75 | 0.82 | | | | | | | | | | | | | | | | | |
| | 100 | 0.87 | | | | | | | | | | | | | | | | | |
| 125 | 0.87 | | | | | | | | | | | | | | | | | | |



| 型号 | | | | |
|---------|----|---|----|----|
| 代码 | D | M | L | S |
| Y-QBC01 | 40 | 8 | 75 | 14 |

Y-QBC01-D40-M12-L50

可选加工(见P471)

| 型号 | | | | | 可选加工代码 |
|---------|----|---|----|----|----------|
| 代码 | D | M | L | S | |
| Y-QBC01 | 40 | 8 | 75 | 14 | WS WL BS |

Y-QBC01-D40-M12-L50-WS

可选配件(见P466~470)

| 型号 | | | | | 可选配件代码 |
|---------|----|---|----|----|--------|
| 代码 | D | M | L | S | |
| Y-QBC01 | 40 | 8 | 75 | 14 | LI JF |

Y-QBC01-D40-M12-L50-LH



优惠价

| 数量 | 1~9 | 10~ |
|----|------|------|
| 价格 | 100% | 另行报价 |

未税价(元)



| 代码 | 技术说明 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|----------------------|---|----|----|----|----|----|---|----|---|----|----|----|----|----|----|------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|--|--|
| WS | 螺杆末端加工外四角 | 选型方法 WS <table border="1"> <thead> <tr> <th>M</th> <th>n</th> <th>e</th> </tr> </thead> <tbody> <tr><td>10</td><td>6</td><td></td></tr> <tr><td>12</td><td>8</td><td>10</td></tr> <tr><td>14</td><td>10</td><td>12</td></tr> <tr><td>16</td><td>12</td><td>13.5</td></tr> <tr><td>20</td><td>14</td><td>15</td></tr> <tr><td>24</td><td>18</td><td>22</td></tr> </tbody> </table> | M | n | e | 10 | 6 | | 12 | 8 | 10 | 14 | 10 | 12 | 16 | 12 | 13.5 | 20 | 14 | 15 | 24 | 18 | 22 | | | | | | | | | | | |
| | | M | n | e | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 12 | 13.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 14 | 15 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 18 | 22 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| WL | 螺杆末端加工外六角 | 选型方法 WL <table border="1"> <thead> <tr> <th>M</th> <th>n1</th> <th>e1</th> </tr> </thead> <tbody> <tr><td>10</td><td>6</td><td></td></tr> <tr><td>12</td><td>8</td><td>10</td></tr> <tr><td>14</td><td>9</td><td></td></tr> <tr><td>16</td><td>10</td><td></td></tr> <tr><td>20</td><td>13</td><td>14</td></tr> <tr><td>24</td><td>16</td><td>18</td></tr> <tr><td>30</td><td>20</td><td>21</td></tr> </tbody> </table> | M | n1 | e1 | 10 | 6 | | 12 | 8 | 10 | 14 | 9 | | 16 | 10 | | 20 | 13 | 14 | 24 | 16 | 18 | 30 | 20 | 21 | | | | | | | | |
| | | M | n1 | e1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 9 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 13 | 14 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 16 | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 20 | 21 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| BS | 螺杆末端加工扳手槽 | 选型方法 BS <table border="1"> <thead> <tr> <th>M</th> <th>n2</th> <th>ee</th> <th>e2</th> </tr> </thead> <tbody> <tr><td>10</td><td>8</td><td>8</td><td></td></tr> <tr><td>12</td><td>10</td><td></td><td></td></tr> <tr><td>14</td><td>12</td><td>10</td><td>12</td></tr> <tr><td>16</td><td>13</td><td></td><td></td></tr> <tr><td>20</td><td>17</td><td></td><td></td></tr> <tr><td>24</td><td>20</td><td>15</td><td>18</td></tr> <tr><td>30</td><td>26</td><td></td><td></td></tr> </tbody> </table> | M | n2 | ee | e2 | 10 | 8 | 8 | | 12 | 10 | | | 14 | 12 | 10 | 12 | 16 | 13 | | | 20 | 17 | | | 24 | 20 | 15 | 18 | 30 | 26 | | |
| | | M | n2 | ee | e2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | 8 | 8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 10 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 14 | 12 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 16 | 13 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 20 | 17 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 24 | 20 | 15 | 18 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 30 | 26 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

| 代码 | 技术说明 | | | | | | | | | | | | | | | | | | | | | | |
|----|--------------------------------------|--|----|----|----|----|---|---|----|---|----|----|---|----|----|----|------|----|----|----|----|----|----|
| NS | 螺杆末端加工内四角 | 选型方法 NS <table border="1"> <thead> <tr> <th>M</th> <th>n3</th> <th>e3</th> </tr> </thead> <tbody> <tr><td>10</td><td>5</td><td></td></tr> <tr><td>12</td><td>6</td><td>10</td></tr> <tr><td>14</td><td>8</td><td>12</td></tr> <tr><td>16</td><td>10</td><td>13.5</td></tr> <tr><td>20</td><td>14</td><td>15</td></tr> <tr><td>24</td><td>18</td><td>20</td></tr> </tbody> </table> | M | n3 | e3 | 10 | 5 | | 12 | 6 | 10 | 14 | 8 | 12 | 16 | 10 | 13.5 | 20 | 14 | 15 | 24 | 18 | 20 |
| | | M | n3 | e3 | | | | | | | | | | | | | | | | | | | |
| 10 | 5 | | | | | | | | | | | | | | | | | | | | | | |
| 12 | 6 | 10 | | | | | | | | | | | | | | | | | | | | | |
| 14 | 8 | 12 | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | 13.5 | | | | | | | | | | | | | | | | | | | | | |
| 20 | 14 | 15 | | | | | | | | | | | | | | | | | | | | | |
| 24 | 18 | 20 | | | | | | | | | | | | | | | | | | | | | |
| NL | 螺杆末端加工内六角 | 选型方法 NL <table border="1"> <thead> <tr> <th>M</th> <th>n4</th> <th>e4</th> </tr> </thead> <tbody> <tr><td>10</td><td>4</td><td>5</td></tr> <tr><td>12</td><td>6</td><td>8</td></tr> <tr><td>14</td><td>8</td><td>10</td></tr> <tr><td>16</td><td>10</td><td>12</td></tr> <tr><td>20</td><td>12</td><td>15</td></tr> <tr><td>24</td><td>16</td><td>18</td></tr> </tbody> </table> | M | n4 | e4 | 10 | 4 | 5 | 12 | 6 | 8 | 14 | 8 | 10 | 16 | 10 | 12 | 20 | 12 | 15 | 24 | 16 | 18 |
| | | M | n4 | e4 | | | | | | | | | | | | | | | | | | | |
| 10 | 4 | 5 | | | | | | | | | | | | | | | | | | | | | |
| 12 | 6 | 8 | | | | | | | | | | | | | | | | | | | | | |
| 14 | 8 | 10 | | | | | | | | | | | | | | | | | | | | | |
| 16 | 10 | 12 | | | | | | | | | | | | | | | | | | | | | |
| 20 | 12 | 15 | | | | | | | | | | | | | | | | | | | | | |
| 24 | 16 | 18 | | | | | | | | | | | | | | | | | | | | | |
| MS | 铆死底座与螺杆 铆死状态 正常状态 | 选型方法 MS ① 底座与螺杆铆死，可以提高底座和螺杆的连接刚度，但是底座与螺杆无法相对转动； ② 铆死后调节是底座也会随螺杆一起转动。 ③ 不适用于万向类型、橡胶底座型和非铆接组装的脚杯。 | | | | | | | | | | | | | | | | | | | | | |

- ① 请根据脚杯螺杆尺寸M进行加工参数的选择；
- ② 加工部不带镀层，有防锈漆；
- ③ 工具可根据不同加工类型进行选择，可选用开口扳手、活动扳手、内四角扳手、内六角扳手等。