


一字槽紧定螺钉

代码	类型	螺纹	材质		表面处理
			国标	相当	

TAY52 平端 粗牙 0Cr18Ni9 SUS304 —



适用标准: GB/T 73-1985

视角标准: 第一视角

型号	代码	M	L	n	h	d
TAY52	2	2 3 4 6 8	0.45	0.31	0.84	0.31
	2.5	3 4 5	0.6	0.46	0.95	0.46
	3	5 6 8 10 14	0.6	0.46	1.05	0.46
	4	4 6 16	0.8	0.66	1.42	0.66
	5	4 6 8 10	1	0.86	1.63	0.86
	6	6 8 20 30	1.2	1.06	2	1.06
	8	6 25	1.51	1.26	2.5	1.26



请按图示订货

型号	代码	M	L
TAY52	3	3	3
TAY52	4	4	4

TAY52—M3—L5



未税价(元)

优惠价

数量 1~99 100~
价格 100% 另行报价

交货期


7

内六角喉塞

代码	类型	材质		表面处理
		国标	相当	

TAY36 内六角喉塞 ML40Cr 发黑

规格M≥27, 材质为SCM440。




适用标准: DIN 906

视角标准: 第一视角

Example
使用示例

压缩弹簧的压板

TAY36/TAN系列(P838)



保护未使用的螺孔

TAY36/TAN系列(P838)



齿轮箱等注油孔的盖子

TAY36/TAN系列(P838)




型号	代码	M	P 螺距	h	S	L
TAY36	10	10			5	
	12	12				
	14	14		6	6.5	10
	16	16	1.5		8	
	18	18			10	
	20	20		6.5	7	12
	22	22		6	6.5	

型号	代码	M	P 螺距	h	S	L
TAY36	24	24				
	26	26				
	27	27		6	6.5	14
	28	28	1.5			
	30	30				12
	33	33			17	

内六角圆柱头喉塞

代码	类型	材质	表面处理	适用标准
----	----	----	------	------

TAY40 内六角圆柱头喉塞 SUS304 — DIN 908




视角标准: 第一视角



六角头喉塞

代码	类型	材质	表面处理	适用标准
----	----	----	------	------

TAY41 六角头喉塞 SUS304 — DIN 910



视角标准: 第一视角



型号	代码	M	P 螺距	D	K	h	S	L
TAY40	10	10	1	14		5	5.15	8
	12	12		17				
	14	14		19	3	7	6.15	
	16	16		21				12
	18	18		23			8.19	
	20	20	1.5	25		7.5	10.19	
	22	22		27				14
	24	24		29	4			
	26	26		31			12.23	
	27	27		32		9		16
	30	30		36			17.23	

型号	代码	M	P 螺距	D	K	h	S	L
TAY41	10	10	1	14			10	7
	12	12		17				
	14	14		19	3.5	6.5	13	11
	16	16		21				
	18	18		23			17	
	20	20	1.5	25		8.5	19	13
	22	22		27				
	24	24		29	4.5	9.5	22	
	26	26		31				
	27	27		32		10.5	24	15
	30	30		36				



请按图示订货

型号	代码	M
TAY40	10	10
TAY40	12	12

TAY40—M10



未税价(元)

优惠价

数量 1~49 50~
价格 100% 另行报价

交货期

5