

代码	带轮类型	皮带宽度	齿距	材质		胀套	表面处理			使用 胀套代码	
				带轮	法兰		带轮	法兰	胀套		
ECD41	H075	19.1	12.7	铝合金	铝合金	S45C	本色阳极氧化		—	EUX16 EUX17 EUX18	
ECD43				S45C	SPCC			发黑			
ECD44								喷砂镀镍			
ECD46				铝合金	铝合金			本色阳极氧化			—
ECD48	H100	25.4							发黑		
ECD49				S45C	SPCC			喷砂镀镍			
ECD51				铝合金	铝合金			本色阳极氧化			—
ECD53	H150	38.1							发黑		
ECD54				S45C	SPCC			喷砂镀镍			
ECD56				铝合金	铝合金			本色阳极氧化			—
ECD58	H200	50.8							发黑		
ECD59				S45C	SPCC			喷砂镀镍			




① 当同步轮材质为S45C时，挡圈存在折边式。

带轮形状
E形带轮形状
F形

3/2


② Y取值规则如下：

带轮类型	内径d	Y
H075	12~29	18
H100	12~22	22
	≥24	23.5
H150	12~32	28
	≥35	32
H200	12~32	35
	≥35	39



视角标准：第一视角

齿形 (ISO标准齿条尺寸)



③ 带*号R尺寸适用于19以下齿数。

④ 由于本体宽度限制，部分规格本体无导入部位J，胀套贯穿本体。

⑤ “可选加工”见同步轮产品简介(适用WC/WD/WE/FC可选加工)。

型号		带轮 形状	轴孔规格d _{H7} (根据胀套孔径尺寸表选择)								P.D.	O.D.	F	E	A	W
			H075		H100		H150		H200							
代码	齿数		E形	F形	E形	F形	E形	F形	E形	F形						
ECD41-H075 ECD43-H075 ECD44-H075 ECD46-H100 ECD48-H100 ECD49-H100 ECD51-H150 ECD53-H150 ECD54-H150 ECD56-H200	14		12~16	12~16	12~16	12~16	12~16	12~16	12~16	12~16	56.60	55.22	61	45	H075 A:21 W:26	
	15		14~19		14~19		14~19	14~19	14~19	14~19	60.64	59.27	67	50		
	16		14~20		14~20		14~20	14~20	14~20	14~20	64.68	63.31	70	56		
	17		14~22		14~22		14~22	14~22	14~22	14~22	68.72	67.35		60		
	18		14~22	14~19	14~22	14~22	14~22	14~22	14~22	14~22	72.77	71.39	80	60		
	19		14~28		14~28	14~28	14~28	14~28	14~28	14~28	76.81	75.44	87	67		
	20		14~28		14~28	14~28	14~28	14~28	14~28	14~28	80.85	79.48	87	67		
	21		14~32		14~32	14~30	14~32	14~32	14~32	14~32	84.89	83.52	95	75		
	22		14~32		14~32	14~30	14~32	14~32	14~32	14~32	88.94	87.56				
	24	E	19~32	19	19~32	19~30	19~32	19~32	19~32	19~32	97.02	95.65	104	84		
ECD49-H100	25	F	19~32	19	19~35	19~30	19~35	19~35	19~35	19~35	101.06	99.69	111	90	H150 A:40 W:45	
ECD51-H150	26				20~35	20~35	20~35	20~35	20~35	20~35	105.11	103.73	111	90		
ECD53-H150	28				20~40	20~40	20~40	20~40	20~40	20~40	113.19	111.82	123	102	H200 A:54 W:59	
ECD54-H150	30				20~45	20~45	20~45	20~45	20~45	20~45	121.28	119.90	127	105		
ECD56-H200	32		20~32								129.36	127.99	135	115	H200 A:54 W:59	
ECD58-H200	34							20~50	20~50	137.45	136.07	144	125			
ECD59-H200	36				20~30					145.53	144.16	152	130			
	38									153.62	152.24	165	140			
	40				20~50		20~50	20~50		161.70	160.33	170	150			
	42									169.79	168.41	180	155			
	44		—						—	—	177.87	176.50	190	170		
	48										194.04	192.67	205	180		
	50										202.13	200.76	210	185		



请按图示订货

型号	带轮形状	轴孔规格d _{H7}
代码	齿数	H075
ECD41-H075	14	E形 12~16
ECD46-H100	15	F形 14~19

ECD41-H075—15—E—d15

⑥ 可选加工

型号	带轮形状	轴孔规格d _{H7}	可选加工代码
代码	齿数	H075	
ECD41-H075	14	E形 12~16	WC WD WE FC
ECD46-H100	15	F形 14~19	

ECD41-H075—15—E—d15—WC



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5

⑦ 胀套孔径尺寸表

d _{H7}	容许最大扭矩N·m	D	(L)
12	44.1	28.5	
14	63.7	30.5	
15	80.4	31.5	
16	83.3	33.0	6.5
17	92.2	33.5	
18	95.1	34.5	
19	98.1	35.5	
20	216.0	42.0	
22	255.0	44.0	
24	363.0	46.0	8
25	392.0	47.0	
28	441.0	50.0	
30	500.0	52.0	8.5
32	530.0	54.0	
35	883.0	62.0	
40	1079.0	67.0	10
45	1285.0	72.0	
50	1706.0	77.0	10.5

⑧ 此表仅适用EUX16/18,EUX17尺寸表参考P2093。