





卡扣式圆形连接器

方法兰插座
防水型 锌合金

代码	类型	连接方式	材质			表面处理	
			外壳	绝缘体	接触体	外壳	接触体
ZIX78	防水型	方法兰插座	卡扣连接	锌合金	热塑塑料PPS (耐高温260℃)	铜	镀铬 镀金



型号		规格	芯数	端头	d	d ₁	L ₁	L	B	A	D	K	适配插头
代码	外壳形状												代码
ZIX78	Z (方法兰插座)	16	2	J(插针) K(插孔)	15.8	18	9.7	21.6	20	26	16.5	3.2	ZIX49
			3										
			4										
			5										
			7										
			9										
		10											
		20	2	19.8	22	9.8	22	29	20.5				
			3										
			4										
			5										
			6										
			7										
		24	2	23.8	26	10	23	26	32	24.5			
			3										
			4										
			5										
			6										
			7										
		28	2	27.8	30	9.8	30	36	28.5				
3													
4													
5													
6													
7													
8													
9													



请按图示订货

型号		规格	芯数	端头
代码	外壳形状			
ZIX78	Z	16	4	J(插针)
			5	K(插孔)

ZIX78-Z-16-4-K

性能表

接插方式	卡扣连接
接线方式	焊接
接插次数	500次
温度范围	-40℃~+85℃
防护等级	IP67